


## **Technical Data Sheet**

## **Elegante Veneer Costato**

Pre-glued non-woven fabric TNT

Usage: See Havwoods quick reference guide to choosing the correct floor



Available Colours	
Makassar	American walnut
Ebony	Grey oak
Teak	Light grey
Oak	White oak
Light American walnut	Gabon ebony
Rosewood	Thermo oak

Please ask a member of staff for more details about our available colours

Product Details	
Pattern	Ribbed
Specie	Ayous (Triplochiton scleroxylon)
Finish	Unfinished
Profile	PAR
Edge Profile	Square Edge
Dimensions	3130x1220mm

Technical Criteria	
Origin	Europe
Responsible Certification	FSC® Certified (FSC-C009500)
Janka Hardness Rating	430 lbf (1.910N)

Installation and Warranty: All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by Hawwoods International. At the time of writing and publiciation of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.





Havwoods Limited, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire LA5 9FD

Tel: +44 (0)1524 737 000; Fax: +44 (0)1524 737 001 info@havwoods.com www.havwoods.com

<sup>^</sup> Please note that this is a smoked/fumed product. This reactive process will typically generate a wider range of colour variation in the product.

<sup>\*</sup> Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

<sup>\*\*</sup> This product may require on-site sanding prior to applying a suitable finish

<sup>#</sup> Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended

<sup>‡</sup> Pack lengths will either 1950mm or 2400mm dependant upon stock availability.