

Technical Data Sheet

BPF19/1611/220 Jutland

Henley

Usage: See Havwoods quick reference guide to choosing the correct floor



Installation Methods

Fully Bonded	Yes* (recommended)
Nailed	Yes*
Floated on underlay	No
Over Underfloor Heating	Yes*# (Please ask for our technical guidelines)

Grading Criteria

Typically, character grade will include both heartwood and sapwood and allows a wider range of colour variation. Knots are larger and you should expect checks (cracks across the growth ring). The colour of the filler is intended to complement the natural structure of the wood, where features such as knots are in contrast to the surrounding timber, and it may vary from batch to batch.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. Please ask for further details

Product Details

Product Code	BPF19/1611/220
Product Range	Henley
Construction	Multi Layered Engineered
Specie	European Oak (Quercus Robur)
Pattern	1-Strip
Process	Distressed & Smoked
Finish	UV Oiled
Profile	Tongue & Groove
Edge Profile	2-Sided Hand Cut Bevelled Edge
Top Layer	4mm European Oak (Quercus Robur)
Backing	Birch Plywood (Betula spp.)
Thickness	19mm (3/4")
Width	220mm (8 5/8")
Length	1950-2400mm‡ (8 5/8") (May include up to 25% shorter boards)
Pack Size	TBC
Grade	Character
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

Technical Criteria

Origin	Europe
Responsible Certification	Please ask a member of staff for details
Janka Hardness Rating	1,120 lbf (4,980N)
Formaldehyde Emission	BLQ ppm - TSCA VI Compliant
Slip testing	65/39 PTV (BS 7976-2:2002+A1:2013)
Critical Radiant Flux	Class I - ASTM E 648
Thermal Conductivity	λ 0.17 W/m K (EN 12664)



[^] Please note that this is a smoked/fumed product. This reactive process will typically generate a wider range of colour variation in the product.

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

** This product may require on-site sanding prior to applying a suitable finish

Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.

‡ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.

Installation and Warranty: All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.



Havwoods International (North America)
151 W 18th St, New York, NY 10111, USA

Tel - 1 347 523 8930 (WOOD)
info@havwoodsusa.com
www.havwoods.com/us