

Technical Data Sheet

HW8702 ANCIENT OAK HAVWOODS SIGNATURE COLLECTION - HAND GRADE PREMIER

Usage: See Havwoods quick reference guide to choosing the correct floor



The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. Due to the size of this photograph, it does not provide any indication of grading. Please refer to our separate grading rules. No rights can be derived from them.

Product Details

| | |
|---------------|--|
| Product Code | HW8702 |
| Product Range | Havwoods Signature collection - Hand Grade Premier |
| Construction | Multi Layered Engineered |
| Species | Bog Oak (Quercus Robur) |
| Pattern | 1-Strip |
| Process | Brushed |
| Finish | Natural Hardwax Oiled |
| Profile | Tongue & Groove |
| Edge Profile | 4-Sided Bevelled |
| Top Layer | 5mm Bog Oak (Quercus Robur) |
| Backing | Birch/Alder Plywood (Betula L.) |
| Thickness | 20mm |
| Width | 250mm - 350mm varied widths supplied |
| Length | 1500-3000mm (May include up to 25% shorter boards) |
| Pack Size | TBC |
| Grade | Prime |
| Maintenance | Comprehensive maintenance instructions and materials are available from Havwoods for all floors. |

Installation Methods

| | |
|-------------------------|---|
| Fully Bonded | Yes* (recommended) |
| Nailed | No |
| Floated on underlay | No |
| Over Underfloor Heating | Yes*# (Please ask for our technical guidelines) |

Grading Criteria

Typically, prime grade has few, if any knots, and these will be of minimal size. There will also be a minimal amount of sapwood and filler, if any at all. Where filler is used its colour is selected to complement the wood rather than to match it exactly and the colour of the filler may vary from batch to batch. There will be a relatively small amount of colour variation in the timber itself.

NB: The product grading criteria is an approximation only. Please ask for details. Contact your Havwoods consultant on 1300 428 966.

Technical Criteria

| | |
|--|---------------------------------|
| Origin | Europe |
| Sustainability | FSC® Certified |
| Janka Hardness Rating | 4.98 kN |
| Formaldehyde Emission | E1(EN 717-1) |
| Pentachlorophenol Emission | < 5ppm (CEN/TR 14823) |
| Slip Testing | USRV 104 (CEN/TS 15676:2007-11) |
| European reaction to fire classification | NPD |
| Thermal Conductivity | λ 0.15 W/m K (EN 12667:2001) |



^ Please note that this is a smoked/fumed product. This reactive process will typically generate a wider range of colour variation in the product.

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

** This product may require on-site sanding prior to applying a suitable finish

Temperature of top-face must never be allowed to exceed 27°C. Under Floor Heating UFH protocol to control temperature conditions is recommended.

‡ Pack lengths will either be 1950mm or 2400mm dependent upon stock availability.

Installation and Warranty: All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

© This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in the sheet are intended only as illustrations. No rights can be derived from them.



Havwoods Australia, 6 Spitfire Place,
Rutherford, NSW 2320
1300 428 966
info@havwoods.com.au
www.havwoods.com.au