

# **TECHNICAL DATA SHEET**

## HW31022 TAIZE

## PUREPANEL

USAGE: SEE HAVWOODS QUICK REFERENCE GUIDE TO CHOOSING THE CORRECT FLOOR.



The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. Due to the size of this photograph, it does not provide any indication of grading. Please refer to our separate grading rules. No rights can be derived from them.

## **PRODUCT DETAILS**

Product Code	HW31022	
Product Range	PurePanel	
Construction	Engineered Double Sided	
Species	European Oak Veneer	
Pattern	Veneered Panel	
Process	Brushed & Stained	
Finish	Matt Lacquered	
Profile	PAR	
Edge Profile	Square Edge	
Top Layer	European Oak	
Backing	MDF	
Thickness	19mm	
Width	1220mm	
Length	3050mm	
Grade	Mix Match Quarted Sawn	
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods Ltd. for all floors. Contact your Havwoods consultant on 1300 428 966.	

\* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

\*\* This product may require on-site sanding prior to applying a suitable finish

# Temperature of top-face must never be allowed to exceed 27°C. Under Floor Heating (UFH) protocol to control temperature conditions is recommended.

#### INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Havwoods Limited, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. No rights can be derived from them.

## INSTALLATION METHODS

Fully Bonded	Yes	
Nailed	No	

## **FEATURES & BENEFITS**

- Endless opportunites across a multitude of applications

- Premium quality, European timber veneer that is FSC® certified

- 9 of Havwoods most popular on-trend colours

- Mix-match production technique ensures each panel is consistent in colour and quality

Ready-to-use and require no additional finishing on-site

- Matching PureEdge trim available for the perfect sealed finish

- 19mm PurePanel includes moisture resistant core

## **TECHNICAL CRITERIA**

Origin	Belgium
Sustainability	FSC <sup>®</sup> Certified
Formaldehyde Emission	E1 (EN717-1/2)
Pentachlorophenol Emission	PCP Free
European reaction to fire classification	Dfl-s1-d0
Thermal Conductivity	λ 0.11 W/mK

HAVWOODS BRISBANE SHOWROOM 2/36 Doggett Street Newstead, QLD 4006

HAVWOODS SYDNEY SHOWROOM 28 Margaret Street Sydney CBD, NSW 2000

HAVWOODS MELBOURNE SHOWROOM 9-11 Claremont Street South Yarra VIC 3141

HAVWOODS NEWCASTLE SHOWROOM 150 King Street Newcastle, NSW 2300

1300 428 966 | info@havwoods.com.au www.havwoods.com.au

