

Technical Data Sheet

HW22506 Black

Hushwood

Usage: See Havwoods quick reference guide to choosing the correct floor



Yes*
Asia
Please ask a member of staff for details

Yes*

Installation Methods

Fully Bonded

Product Details	
Product Code	HW22506
Product Range	Hushwood
Construction	Acoustic PET Panel Reconstituted Veneer
Specie	Ayous (Triplochiton scleroxylon)
Pattern	Fluted Panel
Finish	Unfinished
Profile	PAR
Edge Profile	Square Edge
Top Layer	2mm Ayous (Triplochiton scleroxylon)
Thickness	21mm
Width	600mm
Length	3000mm
Pack Size	TBC
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

* This product hav prequire on-site sanding prior to applying a suitable finish

Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.

‡ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.

Installation and Warranty. All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.





Carnforth, Lancashire LA5 9FD

Tel: +44 (0)1524 737 000; Fax: +44 (0)1524 737 001 info@havwoods. www.havwoods.com

[^] Please note that this is a smoked/fumed product. This reactive process will typically generate a wider range of colour variation in the product.

^{*} Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.