

## **Technical Data Sheet**

## HW3410503 Red Painted - 2400x600

Hushwood

Usage: See Havwoods quick reference guide to choosing the correct floor



Fully Bonded	Yes <sup>a</sup>
Screwed	Yes*
Technical Criteria	
Origin	Europe

FSC® Certified (FSC-C009500)



<b>Product Details</b>	
Product Code	HW3410503
Product Range	Hushwood
Construction	Wood Wool
Specie	Spruce (Picea Abies)
Pattern	Rectangle Panel
Finish	Painted
Profile	PAR
Edge Profile	Square Edge
Top Layer	(Picea Abies)
Thickness	25mm
Width	600mm
Length	2400mm
Pack Size	TBC
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

# remperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions \$\frac{1}{2}\$ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.

Installation and Warranty: All Hawwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Hawwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.





Carnforth, Lancashire LA5 9FD

Tel: +44 (0)1524 737 000; Fax: +44 (0)1524 737 001 info@havwoods.

<sup>^</sup> Please note that this is a smoked/fumed product. This reactive process will typically generate a wider range of colour variation in the product.

<sup>\*</sup> Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.  $\ensuremath{^{\star\star}}$  This product may require on-site sanding prior to applying a suitable finish

<sup>#</sup>Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.