

## **Technical Data Sheet**

## HW3410604 Yellow Painted - 600x600

Hushwood

Usage: See Havwoods quick reference guide to choosing the correct floor



| Fully Bonded              | Yes*                         |
|---------------------------|------------------------------|
| Screwed                   | Yes*                         |
|                           |                              |
|                           |                              |
| Technical Criteria        |                              |
| Origin                    | Europe                       |
| Responsible Certification | FSC® Certified (FSC-C009500) |
|                           |                              |



| <b>Product Details</b> |  |
|------------------------|--|
| Product Code           | HW3410604  |
| Product Range          | Hushwood   |
| Construction           | Wood Wool  |
| Specie                 | Spruce (Picea Abies)   |
| Pattern                | Square Panel   |
| Finish                 | Painted  |
| Profile                | PAR  |
| Edge Profile           | Square Edge  |
| Top Layer              | (Picea Abies)  |
| Thickness              | 25mm   |
| Width                  | 600mm  |
| Length                 | 600mm  |
| Pack Size              | TBC  |
| Maintenance            | Comprehensive maintenance instructions and materials are available from Havwoods for all floors. |

# remperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions \$\frac{1}{2}\$ Pack lengths will either 1950mm or 2400mm dependant upon stock availability.

Installation and Warranty: All Hawwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Hawwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.





Carnforth, Lancashire LA5 9FD

Tel: +44 (0)1524 737 000; Fax: +44 (0)1524 737 001 info@havwoods.

<sup>^</sup> Please note that this is a smoked/fumed product. This reactive process will typically generate a wider range of colour variation in the product.

<sup>\*</sup> Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.  $\ensuremath{^{\star\star}}$  This product may require on-site sanding prior to applying a suitable finish

<sup>#</sup>Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.