

Technical Data Sheet

HW241311 M13 Oak **PurePanel 3D**

Usage: See Havwoods quick reference guide to choosing the correct floor



Installation Methods	

Fully Bonded	Yes*	
Screwed	Yes*	

Technical Criteria

Origin	Europe
Responsible Certification	Please ask a member of staff for details

Product Details

Product Code	HW241311
Product Range	PurePanel 3D
Construction	Milled Oak/Plywood
Finish	Unfinished
Profile	PAR
Edge Profile	Square Edge
Thickness	16mm
Width	1200mm
Length	2400mm
Pack Size	TBC
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

^ Please note that this is a smoked/fumed product. This reactive process will typically generate a wider range of colour variation in the product. * Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.
** This product may require on-site sanding prior to applying a suitable finish
Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.

* Pack lengths will either 1950mm or 2400mm dependant upon stock availability.
Installation and Warranty: All Havwoods floor must be installed by a competent installer who will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by Hawwoods International. At the time of writing and publiciation of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.



Havwoods Limited, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire LA5 9FD

Tel: +44 (0)1524 737 000; Fax: +44 (0)1524 737 001 info@havwoods. www.havwoods.com

19-JUNE-2024/UK/INT

Version 1