

Technical Data Sheet

HW6204 CROYDON **V COLLECTION**

Usage: See Havwoods quick reference guide to choosing the correct floor



The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. Due to the size of this photograph, it does not provide any indication of grading. Please refer to our separate grading rules. No rights can be derived from them.

Product Details		
Product Code	HW6204	
Product Range	V Collection	
Construction	Multi-Layered Engineered	
Species	European Oak (Quercus Robur)	
Pattern	1-Strip	
Process	Light Brushed	
Finish	Matt Lacquered	
Profile	Tongue & Groove	
Edge Profile	Micro Bevelled Edge	
Top Layer	3mm European Oak (Quercus Robur)	
Backing	Eucalyptus Plywood (Eucalyptus Grandis)	
Thickness	14.5mm	
Width	190mm	
Length	1910mm (Packs contain split lengths, with up to 25% shorter boards. These may be half or 1/3 lengths)	
Pack Size	2.1734m²	
Grade	Rustic	
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.	

Installation Methods		
Fully Bonded	Yes*	
Nailed	No	
Floated on underlay	No	
Over Underfloor Heating	Yes*# (Please ask for our technical guidelines)	

Grading Criteria

Rustic grade, also known as natural grade, allows a virtually limitless size and number of knots. Heartwood will be used, there will be colour variation, sapwood and filler. You should expect checks (cracks across the growth ring) and possibly some end shake (cracks between the rings). The colour of the filler is carefully selected to compliment the wood rather than to match it exactly and it may vary from batch to $% \left\{ 1,2,...,n\right\}$ batch

NB: The product grading criteria is an approximation only. Please ask for details. Contact your Havwoods consultant on 1300 428 966.

Technical Criteria	
Origin	Cambodia
Sustainability	Havwoods timber is sourced from sustainably managed forests that also adhere to local illegal logging legislation.
Janka Hardness Rating	4.98 kN
Indoor Air Quality	FloorScore® Certified (SCS-FS-06231)
Formaldehyde Emission	E1 (EN 717-1)
Pentachlorophenol Emission	< 5ppm (CEN/TR 14823)
Slip Testing	P3 - Slip report available
Reaction to Fire	4.1 kW/m ² - AS ISO 9239.1-2003
Thermal Conductivity	λ 0.15 W/mK (EN 12664)



- ^ Please note that this is a smoked/furned product. This reactive process will typically generate a wider range of colour variation in the product.
- * Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

 ** This product may require on-site sanding prior to applying a suitable finish

standards worldwide.

Temperature of top-face must never be allowed to exceed 27°C. Under Floor Heating UFH protocol to control temperature conditions is recommended. ‡ Pack lengths will either be 1950mm or 2400mm dependent upon stock availability.

Installation and Warranty: All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors

which have been installed by a competent flooring installer adhering to Australian standards or equivalent

© This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in the sheet are intended only as illustrations. No rights can be derived from them.





lavwoods Australia, 6 Spitfire Place, Rutherford, NSW 2320 1300 428 966 info@havwoods.com.au www.havwoods.com.au