



# **Technical Data Sheet**

Version 1.0

# HW217026 Oyster TreeAzzo

### Specification

| Pattern              | Terrazzo                    |
|----------------------|-----------------------------|
| Construction         | Multi Layered Engineered    |
| Top Layer Specie     | Epoxy Resin & Wood Elements |
| Surface Process      | Sanded                      |
| Finish               | Natural Oiled               |
| Connection System    | PAR                         |
| Edge Profile         | Square Edge                 |
| Backing              | Hardwood Plywood            |
| Wear Layer Thickness | 5mm                         |
| Total Thickness      | 23mm                        |
| Width                | 1200mm                      |
| Length               | 2500mm                      |
| Pack Size            | TBC                         |
|                      |                             |

#### Key:

^ Please note that this is a smoked/ fumed product. This reactive process will typically generate a wider range of colour variation in the product.

\*\* This product may require on-site sanding prior to applying a suitable finish

‡ Pack lengths will vary between the specified minimum and maximum lengths depending upon stock availability.

\* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

# Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.

## Installation Methods

| Fully Bonded            | Yes* (recommended) |
|-------------------------|--------------------|
| Nailed/Screwed          | No                 |
| Floated on Underlay     | No                 |
| Over Underfloor Heating | No                 |

All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

### **Technical Criteria**

| Origin                          | Europe                |
|---------------------------------|-----------------------|
| Formaldehyde Emissions          | E1 (EN 717-1)         |
| Pentachlorophenol Emissions     | < 5ppm (CEN/TR 14823) |
| Slip Testing                    | NPD                   |
| Reaction to Fire Classification | Dfl-s1 (EN 13501-1)   |
| Thermal Resistance              | NPD                   |





# For More Information Contact Our Experienced Team:

Tel: +44 (0)1524 737 000 | Fax: +44 (0)1524 737 001 Email: info@havwoods.com

Comprehensive maintenance instructions and materials are available from Havwoods for all floors.



This technical data sheet was written by Havwoods International. At the time of writing and publication, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this document are intended only as illustrations. No rights can be derived from them.

