

## Technical Data Sheet

## HW240404 Simplista C9

### Simplista

Usage: See Havwoods quick reference guide to choosing the correct floor



The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. Due to the size of this photograph, it does not provide any indication of grading. Please refer to our separate grading rules. No rights can be derived from them.

### Installation Methods

Fully Bonded	Yes* (recommended)
Nailed	No
Floated on underlay	Yes*
Over Underfloor Heating	Yes*# (Please ask for our technical guidelines)

### Product Information

Flexible MDF panels that are primed and suitable for walls, ceilings and cabinetry.

Bring dimension and interest to interiors. These flexible panels are pre-primed ready to be painted in any hue, ideal for adding a splash of personality to walls and curvaceous elements alike.

**NB:** The product grading criteria is an approximation only. Please ask for details. Contact your Havwoods consultant on 1300 428 966.

### Product Details

Product Code	HW240404
Product Range	Simplista
Construction	Mixed Species MDF
Pattern	Castellated Pattern
Finish	Primed
Profile	PAR (Planed All Round)
Edge Profile	Square Edge
Backing	PVC Backed
Thickness	9mm
Width	1220mm
Length	2440mm
Panel Size	2.9768m <sup>2</sup>
Grade	Prime
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

### Technical Criteria

Origin	Asia
Sustainability	Havwoods timber is sourced from sustainably managed forests that also adhere to local illegal logging legislation.
Formaldehyde Emission	P2 – (CARB)
Pentachlorophenol Emission	NPD
Reaction to Fire Certification	NPD
Thermal Conductivity	NPD

^ Please note that this is a smoked/fumed product. This reactive process will typically generate a wider range of colour variation in the product.

\* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

\*\* This product may require on-site sanding prior to applying a suitable finish

# Temperature of top-face must never be allowed to exceed 27°C. Under Floor Heating UFH protocol to control temperature conditions is recommended.

‡ Pack lengths will either be 1950mm or 2400mm dependent upon stock availability.

**Installation and Warranty:** All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

© This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in the sheet are intended only as illustrations. No rights can be derived from them.



Havwoods Australia, 6 Spitfire Place,  
Rutherford, NSW 2320

1300 428 966  
info@havwoods.com.au  
www.havwoods.com.au