

# Technical Data Sheet

Version 1.0



HW240301

**M3**

Simplista



## Specification

Pattern	Panel
Construction	Milled
Top Layer Specie	MDF
Surface Process	N/A
Finish	Unfinished
Connection System	PAR
Edge Profile	Square Edge
Backing	N/A
Wear Layer Thickness	N/A
Total Thickness	6mm
Width	1200mm
Length	2400mm
Pack Size	TBC
Grade	Prime

### Key:

^ Please note that this is a smoked/ fumed product. This reactive process will typically generate a wider range of colour variation in the product.

\*\* This product may require on-site sanding prior to applying a suitable finish

‡ Pack lengths will vary between the specified minimum and maximum lengths depending upon stock availability.

\* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

# Temperature of top-face must never be allowed to exceed 27°C. UFH protocol to control temperature conditions is recommended.



# HAVWOODS

## For More Information Contact Our Experienced Team:

Tel: +44 (0)1524 737 000 | Fax: +44 (0)1524 737 001  
Email: [info@havwoods.com](mailto:info@havwoods.com)

Comprehensive maintenance instructions and materials are available from Havwoods for all floors.



This technical data sheet was written by Havwoods International. At the time of writing and publication, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this document are intended only as illustrations. No rights can be derived from them.

