




# Technical Data Sheet

Version 1.0

## HRC4006 Spring Vertical



### Specification

|                      |                                       |
|----------------------|---------------------------------------|
| Pattern              | Plank                                 |
| Construction         | Solid                                 |
| Top Layer Specie     | European Oak ( <i>Quercus robur</i> ) |
| Surface Process      | Sanded                                |
| Finish               | Oiled                                 |
| Connection System    | PAR                                   |
| Edge Profile         | Square Edge                           |
| Backing              | N/A                                   |
| Wear Layer Thickness | N/A                                   |
| Total Thickness      | 4mm                                   |
| Width                | 100mm                                 |
| Length               | 300-1200mm                            |
| Pack Size            | TBC                                   |
| Grade                | Rustic                                |

#### Key:

\*\* This product may require on-site sanding prior to applying a suitable finish

\* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

## Installation Methods

|                |                    |
|----------------|--------------------|
| Fully Bonded   | Yes* (recommended) |
| Nailed/Screwed | Yes*               |

All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

## Grading Criteria

|                  |             |
|------------------|-------------|
| Sound Knots      | Unlimited   |
| Broken Knots     | Unlimited   |
| Filled Defects   | Allowed     |
| Heart /Pith      | Allowed     |
| Sapwood          | Not allowed |
| End Checks       | Allowed     |
| Insect damage    | Allowed     |
| Filler           | None        |
| Colour variation | Allowed     |
| Small cracks     | Allowed     |
| Inner bark       | Not allowed |
| Modullary Rays   | Allowed     |

**N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. To allow for unavoidable variations in the material characteristics, 3% of materials may vary from the stated range.**

## Technical Criteria

|                                 |                     |
|---------------------------------|---------------------|
| Origin                          | Europe              |
| Janka Hardness Rating           | 1.120 lbf (4,980N)  |
| Formaldehyde Emissions          | BDL (EN 12149)      |
| Reaction to Fire Classification | Class E (EN13501-1) |



# HAVWOODS

## For More Information Contact Our Experienced Team:

Tel: +44 (0)1524 737 000 | Fax: +44 (0)1524 737 001  
Email: [info@havwoods.com](mailto:info@havwoods.com)

Comprehensive maintenance instructions and materials are available from Havwoods for all floors.



This technical data sheet was written by Havwoods International. At the time of writing and publication, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this document are intended only as illustrations. No rights can be derived from them.

