



The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. Due to the size of this photograph, it does not provide any indication of grading. Please refer to our separate grading rules. No rights can be derived from them.

Installation Methods

Glue Assist Installation	Yes*
Nailed	Yes (Secret Nail Recommended)
Screw / Staple	Yes

Product Information

- Endless opportunities across a multitude of applications
- Premium quality composition that is Cradle to Cradle® certified
- Impact Resistant
- Anti Bacterial Certified and Food Safe
- 4 of Havwoods most popular on-trend colours
- Registered and Embossed Timber Touch Technology
- Ready-to-use and requires no additional finishing on-site
- 10mm Clicwall Panel includes moisture resistant core

NB: The product grading criteria is an approximation only. Please ask for details. Contact your Havwoods consultant on 1300 428 966.

Product Details

Product Code	HW32104
Product Range	RealGrain Clicwall
Construction	Multi-Layer Melamine faced MR MDF Fibreboard
Design	Impregnated Decorative Paper with Oak Finish
Pattern	Registered and Embossed Timber Touch Technology
Surface Texture	Brushed
Finish	Matt & Low Reflective
Profile	Patented Uniclic Click System
Edge Profile	Square Edge
Top Layer	Timbertouch Finish (Double Sided)
Core	Moisture Resistant MDF
Thickness	10mm
Width	600mm
Length	2785mm
Pack Size	1.671m ²
Grade	Prime
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

Technical Criteria

Origin	Belgium
Sustainability	Cradle to Cradle®
Formaldehyde content (mg/100 g dry)	(E1) ≤8 (EN120)
Pentachlorophenol Emission	EN13986 (Chp 5.18) <5ppm
Reaction to Fire Certification	NPD
Thermal Conductivity	λ 0.10 W/mK EN13986 (Table 11)



^ Please note that this is a smoked/fumed product. This reactive process will typically generate a wider range of colour variation in the product.

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

** This product may require on-site sanding prior to applying a suitable finish

Temperature of top-face must never be allowed to exceed 27°C. Under Floor Heating UFH protocol to control temperature conditions is recommended.

‡ Pack lengths will either be 1950mm or 2400mm dependent upon stock availability.

Installation and Warranty: All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

© This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in the sheet are intended only as illustrations. No rights can be derived from them.



Havwoods Australia, 6 Spitfire Place,
Rutherford, NSW 2320
1300 428 966
info@havwoods.com.au
www.havwoods.com.au