



The photographs used in this sheet are intended only as illustrations, colours shown are only as accurate as the printing process or device screen will allow. Due to the size of this photograph, it does not provide any indication of grading. Please refer to our separate grading rules. No rights can be derived from them.

### Product Details

Product Code	HW33026
Product Range	PurePanel
Construction	Solid Veneer
Species	European Oak Veneer (Quercus spp.)
Pattern	Mix Match Quarter Sawn Veneered Sheet
Process	Brushed & Stained
Finish	Matt Lacquered
Profile	PAR (Planned All Round)
Edge Profile	Square Edge
Top Layer	0.6mm European Oak (Quercus spp.)
Backing	High Pressure Laminate (HPL)
Thickness	1mm
Width	1220mm
Length	3050mm
Pack Size	3.78m <sup>2</sup>
Grade	Prime
Maintenance	Comprehensive maintenance instructions and materials are available from Havwoods for all floors.

### Installation Methods

Fully Bonded	Yes* (recommended)
Nailed	No

### Grading Criteria

- Endless opportunities across a multitude of applications
- Premium quality, European timber veneer that is PEFC certified
- Wide selection of Havwoods most popular on-trend colours
- Mix-match production technique ensures each panel is consistent in colour and quality
- Ready-to-use and require no additional finishing on-site
- Matching PureEdge trim available for a complete and fully sealed edge detail.

**NB:** The product grading criteria is an approximation only. Please ask for details. Contact your Havwoods consultant on 1300 428 966.

### Technical Criteria

Origin	Belgium
Sustainability	PEFC® Certified (PEFC/16-37-1417)
Formaldehyde Emission	E1 (EN 717-1)
Pentachlorophenol Emission	PCP Free
Reaction to Fire Certification	Dfl-s1-d0
Thermal Conductivity	NPD



<sup>^</sup> Please note that this is a smoked/fumed product. This reactive process will typically generate a wider range of colour variation in the product.

<sup>\*</sup> Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

<sup>\*\*</sup> This product may require on-site sanding prior to applying a suitable finish

<sup>#</sup> Temperature of top-face must never be allowed to exceed 27°C. Under Floor Heating UFH protocol to control temperature conditions is recommended.

<sup>‡</sup> Pack lengths will either be 1950mm or 2400mm dependent upon stock availability.

**Installation and Warranty:** All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

© This technical data sheet was written by Havwoods International. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in the sheet are intended only as illustrations. No rights can be derived from them.



Havwoods Australia, 6 Spitfire Place,  
Rutherford, NSW 2320  
1300 428 966  
info@havwoods.com.au  
www.havwoods.com.au