



Technical Data Sheet

Version 1.1

HW231911RAB

Rosewood Flat Sheet

Elegante



Specification

Pattern	Flat sheet
Construction	Composite MDF reconsituted veneer with hardwood balancer reverse
Top Layer Specie	Ayous (Triplochiton scleroxylon)
Finish	Unfinished
Connection System	PAR
Edge Profile	Square edge
Backing	MDF
Wear Layer Thickness	0.6mm
Total Thickness	20mm
Width	1220mm
Length	3020mm
Pack Size	TBC
Grade	Prime



The mark of responsible forestry

Key

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

Installation Methods

Fully Bonded	Yes*
Nailed/Screwed	Yes*

All Havwoods floor must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

Grading Criteria

Typically, prime grade has few, if any knots, and these will be of minimal size. There will also be a minimal amount of sapwood and filler, if any at all. Where filler is used its colour is selected to complement the wood rather than to match it exactly and the colour of the filler may vary from batch to batch. There will be a relatively small amount of colour variation in the timber itself.

N.B. The product grading criteria is inspected at each mill visually and should be taken as an approximation only. To allow for unavoidable variations in the material characteristics, 3% of materials may vary from the stated range.

Technical Criteria

Origin	Europe
Certification	FSC® Certified (FSC-C009500)
Janka Hardness Rating	430 lbf (1,910 N)



HAVWOODS

For More Information Contact Our Experienced Team:

Tel: +44 (0)1524 737 000 | Fax: +44 (0)1524 737 001
Email: info@havwoods.com

Comprehensive maintenance instructions and materials are available from Havwoods for all floors.



This technical data sheet was written by Havwoods International. At the time of writing and publication, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this document are intended only as illustrations. No rights can be derived from them.

