



Stripping, Scrubbing, Polishing



Mighty
w/ Telescoping
Handle

Mighty

Machine operators will appreciate the performance, versatility and value in the Hawk Mighty. The 1.0 HP TEFC AC motor and XHD gears deliver huge power in a small and manageable machine. The Mighty is ideal for use in tight spaces, restrooms, edging and stairs.

The TH model with telescoping handle fits every operator's height and store in tight spaces.

Power

- 1.0 HP, 56C frame, dual capacitor, AC motor
- 115-230V, 50/60 Hz power
- 50 ft. 14-3 SJT 2-piece power cord with molded plug for rigid handle models. Telescoping 13" and 15" use standard 5" cord

Drive System

- Triple-planetary severe-duty 11:1 helical-cut industrial gears, case hardened with steel coupler
- Gears drive brushes and pads at 165 RPM

Engineered Design

- All steel construction with welded, powder-coated frame
- Telescoping handle (TH models) adjusts from 36" to 48"
- 13" and 15" steel brush covers have full wraparound bumper
- One piece powder-coated, heavy duty steel handle with 6-position pin lock
- Comfortable vinyl dipped foam grips
- Thumb-operated safety switch. Negative pressure on/off switch.
- Dual steel operating triggers
- 1" x 5" non-marking ball bearing wheels

Safety Features

- Quiet 64 dB operation. Meets GS42 standard.
- Built with UL Listed components



Specifications

Model	MIGHTY13	MIGHTY 13-TH	MIGHTY15	MIGHTY15-TH
Part Number	F60-13	F60-13TH	F60-15	F60-15TH
Handle	Rigid	Telescoping	Rigid	Telescoping
Size	13"	13"	15"	15"
Pad Size	12"	12"	14"	14"
Telescoping Handle	No	Yes	No	Yes
Pad Speed	165 RPM	165 RPM	165 RPM	165 RPM
Amp Draw	4.9 Amp	4.9 Amp	6 Amp	6 Amp
Weight	87 lbs.	87 lbs.	88 lbs.	88 lbs.

All Models

Motor	1.0 HP, 56 frame, dual capacitor AC motor
Power Source	115-230V, 50/60 Hz power
Power Cord	50 ft. 14-3 SJT power cord w/molded plug
Driver System	Triple-planetary XHD 11:1 helical-cut industrial gears
dB Rating	64 dB - Meets GS42 standard



Works in
Tight Spaces



Telescoping Handle
Adjusts from 36" to 48"



Optional 2.5-Gallon
Solution Tank



Handle with 6-Position
Pin Lock

Subject to Change Without Notice