



Stripping, Scrubbing, Carpet Care

The Hawk 2-Speed floor machine is rough and versatile. Change between low and high speed as the job requires. Powered by a 1.5 HP DC rectified motor.

Choose the HD for standard scrubbing and stripping at 175/320 RPM. The XHD model uses 11:1 helical cut gear set for more challenging work including carpet care and natural stone maintenance. Both models have a toggle speed switch at the top of the handle. XHD models can be weighted for greater performance.

Power

- 1.5 HP, 66 frame, DC rectified 2-speed motor. 115V, 60 Hz power.
- 50 ft. 14-3 STO industrial cord w/molded plug
- **HD** uses triple-planetary HD 10:1 helical-cut commercial gears. Drives brushes and pads at 175/320 RPM.
- **XHD** (Extra Heavy Duty) planetary 11:1 helical-cut industrial gears, case hardened with steel coupler. 165/300 RPM pad speed.

Engineered Design

- All steel construction with welded, powder-coated frame
- One piece, chromed heavy duty steel handle with variable position lock and vinyl-dipped foam grips
- Powder-coated steel brush covers with full wraparound bumpers
- Dual steel operating triggers. Negative pressure on/off switch.
- Thumb-operated safety switch. 1" x 5" non-marking wheels.
- Optional frame weights (XHD only)

Safety Features

- Quiet 60dB (HD 2-Speed) and 66 dB (XHD 2-Speed) operation. Meets GS 42 Standard. UL / CUL listed.



Hi/Lo Speed Motor Switch on Handle



Easy Transport with 1" x 5" Non-Marking Ball-Bearing Wheels



Brush Covers in 7 Stock Colors Plus Chrome



DX Model Includes Pad Driver, Solution Tank & Splash Guard



Specifications HD 2-Speed

Specifications XHD 2-Speed

Model	HP1513-2S	HP1515-2S	HP1517-2S	HP1520-2S	HP1513-2S-XHD	HP1515-2S-XHD	HP1517-2S-XHD	HP1520-2S-XHD
Part #	F03-13-01	F03-15-01	F03-17-01	F03-20-01	F04-13-01	F04-15-01	F04-17-01	F04-20-01
Machine Size	13 inch	15 inch	17 inch	20 inch	13 inch	15 inch	17 inch	20 inch
Pad Size	12 inch	14 inch	16 inch	19 inch	12 inch	14 inch	16 inch	19 inch
Pad Speed	175/320 RPM	175/320 RPM	175/320 RPM	175/320 RPM	165/300 RPM	165/300 RPM	165/300 RPM	165/300 RPM
Amp Draw	7.8/8.2 Amp	8.1/8.5 Amp	8.5/9.1 Amp	9.2/9.5 Amp	7.8/8.2 Amp	8.1/8.5 Amp	8.5/9.1 Amp	9.2/9.5 Amp
Weight	87 lbs	91 lbs	94 lbs	97 lbs	87 lbs	90 lbs	94 lbs	99 lbs

ALL HD 2-Speed Sizes

ALL XHD 2-Speed Sizes

Motor	1.5 HP, 66 frame, DC rectified 2-speed motor	1.5 HP, 66 frame, DC rectified 2-speed motor
Drive System	Triple-planetary 10:1 helical-cut commercial	Triple-planetary XHD 11:1 helical-cut industrial gears
Power Source	115-230V, 60 Hz (50 Hz optional)	115-230V, 60 Hz (50 Hz optional)
Power Cord	50 ft. 14-3 STO industrial w/molded plug	50 ft. 14-3 STO industrial w/molded plug
dB Rating	60dB (175) - 69dB (320) - Meets GS42 standard	69dB(165) - 72dB (300) - Meets GS42 standard

Subject to Change Without Notice