



Stripping, Sanding, Carpet Care, Resurfacing



The Brute is built for high productivity in the harshest jobs like concrete resurfacing, natural stone polishing, and wood screening and sanding. We fit the powerful 1.5 HP 180 frame TEFC (Totally Enclosed Fan Cooled) AC motor with 11:1 gears and industrial grade steel coupler. You will power your Brute without blowing breakers and reducing down time.

The 100% steel construction is accented with three exterior decorations:

- **Brute** - chrome motor and brush cover
- **TE-CP** - chrome motor with powder coated brush cover
- **TE** - powder-coated motor cover (black) and brush cover

Power

- 1.5 HP, 180 frame, TEFC dual capacitor AC motor
- 115-230V, 60 Hz (50 Hz optional)
- 50 ft. 12-3 SJTOW industrial power cord with molded plug

Drive System

- Triple-planetary XHD 11:1 helical-cut industrial gears, case hardened with steel coupler, driving brushes at 165 RPM

Engineered Design

- All steel welded construction. Steel brush covers with full wrap around bumper.
- One piece chrome, heavy duty steel handle w/variable position lock
- Dual steel operating triggers with negative pressure on/off switch. Thumb-operated safety switch. Comfortable vinyl-dipped foam grips.
- 1" x 5" non-marking ball bearing wheels
- Optional 4 gallon solution tank. Optional frame weights.

Safety Features

- Quiet 66 dB operation. Meets GS42 standard.
- UL/CUL listed



Brute

Specifications				
Machine Size	13"	15"	17"	20"
Model	-	HP1515-180 Brute	HP1517-180 Brute	HP1520-180 Brute
Part #	-	F35-CP	F37-CP	F40-CP
Motor / Brush Cover	-	Chrome/Chrome	Chrome/Chrome	Chrome/Chrome
Model	HP1513-180 TE	HP1515-180 TE	HP1517-180 TE	HP1520-180 TE
Part #	F33-01-B	F35-01-B	F37-01-B	F40-01-B
Motor Cover	Black	Black	Black	Black
Brush Cover	Powder-Coated	Powder-Coated	Powder-Coated	Powder-Coated
Model	HP1513-180 TECP	HP1515-180 TECP	HP1517-180 TECP	HP1520-180 TECP
Part #	F33-01-C	-	F37-01-C	F40-01-C
Motor Cover	Chrome	-	Chrome	Chrome
Brush Cover	Powder-Coated	-	Powder-Coated	Powder-Coated
Pad Speed	165 RPM	165 RPM	165 RPM	165 RPM
Amp Draw	7.2 Amp	7.5 Amp	7.9 Amp	8.4 Amp
Weight	113 lbs.	117 lbs.	123 lbs.	125 lbs
All Sizes				
Motor	1.5 HP, 180 frame, TEFC dual capacitor AC motor			
Power	115-230V, 60 Hz power			
Power Cord	50 ft. 12-3 SJTOW industrial power cord w/molded plug			
Drive System	Triple-planetary XHD 11:1 helical-cut industrial gears			
dB Rating	66 dB - Meets GS42 standard			



Optional Dust Pickup System with Vacuum Connection



Add the 25 lb. Custom "U" Weights for Fast Results



7 Private Brand Colors Plus Chrome



Power for Optional Drivers & Tools

Subject to Change Without Notice