



Glide Sanding with Active Dust Control



The Glide Sanding Star makes wood floor maintenance faster and easier. Designed to be nimble for scuffing, blending and sanding on all types of finished wood, bare wood, VCT and coated floors.

We combine the Glide “floating-head” Wheels Down frame design with the Hawk Mighty 1.0 HP DC motor, and mount our six quart, triple-filter vacuum on the powder-coated steel handle carriage. The Sanding Star uses XHD 11:1 industrial gears to spin floor sanding drivers at 165 RPM. A twist-lock plug securely connects the machine to its 100 ft. (12-3) industrial power cord.

The HAWK 360 Dust Pickup System™ collects airborne dust and debris internally at the floor level with its proprietary 360 degree duct system. Floor preparation debris control is made safe and simple.

Power

- Powerful 1.0 HP TEFC dual capacitor motor
- 115-230V 50/60 Hz AC power
- 100 ft. 2-pc. (12-3) SJTOW power cord with twist-lock connection
- XHD 11:1 helical-cut case hardened gears with steel coupler spins sanding drivers at 165 RPM

Engineered Design

- Exclusive WD™ detachable handle-carriage design with 5-position pin-set handle lock
- HAWK 360 Dust Pickup System™ makes sanding cleaner
- Includes handle-mounted, 6 quart dual-stage tank vacuum with triple filtration
- 2" x 8" non-marking ball bearing wheels
- Welded, powder-coated handle with vinyl-dipped foam grips
- Dual steel operating triggers with negative pressure on/off switch
- Includes 20 lb. weight and 360 degree dust ring

Safety Features

- Quiet 66 dB operation. Meets GS42 standard.



Specifications

Model	Sanding Star 17"	Sanding Star 17" w/ Vacuum	Sanding Star 20"	Sanding Star 20" w/ Vacuum
Part #	F95-17-01	F95-17-01S	F95-20-01	F95-20-01S
Machine Size	17"	17"	20"	20"
Pad Size	16"	19"	16"	19"
Pad Speed	165 RPM	165 RPM	165 RPM	165 RPM
Gear Box	11:1	11:1	11:1	11:1
Amp Draw	6.7 Amp	6.7 Amp	7.1 Amp	7.1 Amp
Weight	137 lbs.	147 lbs.	139 lbs.	149 lbs.

All Models

Motor	1.0 HP, 56 frame dual capacitor powder-coated AC motor
Power	115V/230V, 50-60 Hz power
Power Cord	100 ft. 2-piece (12-3) SJTOW w/ twist-lock connection
dB Rating	66 dB Meets GS42 standard


Subject to Change Without Notice



360 Degree Duct in Brush Apron Directs Debris to Vacuum Port



Includes Handle Mounted 6 Quart Tank Vacuum



5 Position Pin Lock Handle



Two-Piece Twist Lock 100 ft. Power Cord