



Dry Stripping, Scrubbing, Stripping

The TigerHawk 2014 and 2814 with revolutionary WD™ wheels down “Floating Head” technology are the most productive orbitals on the market. With over 0.79 pounds per square inch of pressure moving at over 1740 RPM, you power through finish removal without the use of chemicals. Scrub, strip, or sand floors effortlessly with less noise and fatigue.

Our large 180 frame 1.5 HP TEFC motor is connected to a solid steel drive plate and balanced via easy access eccentric driver. 12 vibration isolators combined with Hawk exclusive handle-carriage mounting system prevents any vibration to be felt by the operator. The handle removes easily for transport and storage. Includes 4 caster steel transport dolly and drip tray.

Power

- 1.5 HP, 180 frame, TEFC dual capacitor AC motor
- 115-230V, 60 Hz power
- 50 ft. 2-pc. 12-3 SJTOW yellow industrial power cord with twist-lock plug
- Eccentric balanced design drives pads at 1740 RPM

Engineered Design

- Dual vibration isolation system
- Heavy-duty powder-coated steel handle with 5-position pin lock
- The WD™ handle is easy to remove for transport and storage
- The heavy duty motor guard protects the motor from impact damage
- Thumb-operated safety switch. Dual steel operating triggers.
- Comfortable vinyl-dipped foam handle grip
- 2" x 8" non-marking ball bearing wheels
- Optional active Vacuum System includes 6 quart tank vacuum, dust skirt and hardware (#TH1001).
- Optional Osprey Sprayer System includes motor-mounted sprayer pump, 4 gallon solution tank and hardware (#TH1010).
- Includes transport cart and drip tray

Safety Features

- Quiet 60 dB operation. Meets GS42 standard.
- UL/CUL listed



TigerHawk 2014

TigerHawk 2814



Specifications

Model Number	TH-2014	TH-2814
Part Number	F98-TH2014	F98-TH2814
Pad Size	20" x 14"	28" x 14"
Pad Speed	1740 RPM	1740 RPM
Amp Draw	7.1 Amp	7.8 Amp
Weight	250 lbs.	305 lbs.
Pad Pressure	0.89 lbs/in ²	0.79 lbs/in ²

All Models

Motor	1.5 HP, 180 frame, TEFC dual capacitor AC motor
Power Source	115-230V, 60 Hz power
Power Cord	50 ft. 2-pc. 12-3 SJTOW yellow industrial power cord w/twist-lock plug
Drive System	Eccentric balanced orbital drive
Vibration Isolators	(6) primary, (8) secondary isolaters
dB Rating	60 dB - Meets GS42 standard

Subject to Change Without Notice



Steel Frame with Rear Vacuum Port



Works Along Baseboards and Into Corners



Two-Part Twist Lock Connects Machine to 50 ft. Power Cord



Includes Transport Cart and Drip Tray