



## Burnishing & Refinishing

The Hawk High-Speed Burnisher with AC motor is a balanced force of polishing power. The models are built with a durable 1.5 HP TEFC (Totally Enclosed Fan Cooled) motor that requires little maintenance. The enclosure protects the inner working of the motor from dust and moisture, running cleaner than traditional motors. The AC motor runs at lower amp draw than most DC motors. Hawk AC burnishers are the perfect addition to any Green Cleaning program.

### Power

- 1.5 HP, 56C frame, TEFC dual capacitor AC motor
- 115-230V, 60 Hz power
- 50 ft., 14-3 STO industrial power cord with molded plug

### Drive System

- Multi V-Belt drives pads at 1000 RPM

### Engineering Design

- 13", 15", 17" and 20" standard models are built with powder coated steel brush cover with full wraparound bumper
- 17" and 20" Dust Control models add a dust ring and filter
- Welded steel frame.
- One-piece chrome handle with variable position positive handle lock
- Comfortable vinyl-dipped foam handle grips
- Thumb-operated safety switch.
- Negative pressure on/off switch
- Dual steel operating triggers
- 1" x 5" non-marking wheels
- Includes flexible pad holder with pad centering clamp

### Safety Features

- Quiet operation - 58 dB (Standard), 53 dB (Dust Control). Meets GS42 standard.
- Built with UL listed components



High Speed Burnisher  
with AC Motor  
and Dust Control

High Speed Burnisher  
with AC Motor



## Specifications

| Machine        | 13" Standard  | 15" Standard | 17" Standard | 17" Dust Control | 20" Standard | 20" Dust Control |
|----------------|---|--------------|--------------|------------------|--------------|------------------|
| Pad Size       | 13"   | 15"          | 17"          | 16"              | 20"          | 19"              |
| Model #        | HP1513-1000   | HP1515-1000  | HP1517-1000  | HP1517-1000DC    | HP1520-1000  | HP1520-1000DC    |
| Part #         | F1000-13TE  | F1000-15TE   | F1000-17TE   | F1000-20TEDC     | F1000-17TE   | F1000-20TEDC     |
| Speed          | 1000 RPM  | 1000 RPM     | 1000 RPM     | 1000 RPM         | 1000 RPM     | 1000 RPM         |
| Amp Draw       | 10.0 Amp  | 11.2 Amp     | 12.4 Amp     | 11.6 Amp         | 13.5 Amp     | 12.4 Amp         |
| Motor          | 1.5 HP, 56C frame, TEFC dual capacitor AC motor                               |              |              |                  |              |                  |
| Power          | 115-230V, 60 Hz power. 50 ft. 14-3 STO industrial power cord with molded plug |              |              |                  |              |                  |
| Drive          | Multi-V belt drive  |              |              |                  |              |                  |
| dB Rating      | 58 dB   | 58 dB        | 58 dB        | 53 dB            | 58 dB        | 53dB             |
| Machine Weight | 84 lbs.   | 86 lbs.      | 88 lbs.      | 88 lbs.          | 90 lbs.      | 90 lbs.          |

Subject to Change Without Notice