

HAWK Titan 29 & Titan 55

Commercial Wet/Dry Tank Vacuums





Includes: Wet/Dry Tool Kit #HPVA002

15' Flexible Vacuum Hose **#HPVT1060**

Large Area Vacuum Cleaning

The Hawk Titan 29 and Titan 55 wet/dry tank vacuums are built for years of trouble-free service. Ideal for large volume recovery of liquids and solid wastes. Safely moves heavy loads up to 400 lbs. on large rear wheels and industrial front casters. The corrosion-resistant tank is easy to rinse out through the 13" top entry hole. Drain liquids and debris collections from the rear-mounted quick-drop drain valve.

Power

- 2 HP, 2-stage heavy duty bypass motor. (230V Option).
- 2-piece commercial, 35 ft. (14-3) SJT easy-wrap power cord

Engineered Design

- Corrosion-resistant roto-molded tank is easy to clean
- Quick-drop drain valves 1.5" (T29) and 3" (T55)
- V29-V Large 5" rear wheels and strong 3" front casters
- V55-V Large 6" rear wheels and strong 4" front casters
- Powder-coated steel handle and carriage
- An automatic liquid shut-off prevents motor flooding
- Includes wet/dry tool kit (#HPVA002)
- Includes 15 ft. flexible vacuum hose (#HPVT1060)
- Includes one acid and mildew resistant, non-pleated washable synthetic cloth dust bag (#HPVA4040) and mounting ring (#VA2018)

Safety Features

- Quiet operation 68 dB. Meets GS42 requirements
- Quick drop drain hose prevents need for lifting
- UL / CUL approved components for safe performance

SPECIFICATIONS		
Model #	Titan 29	Titan 55
Part #	V29-V	V55-V
Capacity	29 gallon	55 gallon
Wet Pick Up	22 gallons	48 gallons
Dry Pick Up	2 bushel (18.6 gal)	4 bushel (37.2 gal)
Motor	2 HP DC, 2-Stage	2 HP DC, 2-Stage
Power	115V, 50/60 Hz	115V, 50/60 Hz
Amperes	10.7	10.7
Power Cord	35 ft., 2 Part, 16/3	35 ft., 2 Part, 16/3
Water Lift	117 inch	117 inch
Air Flow	112 CFM	112 CFM
2 Wheels - Rear	8 inch	10 inch
2 Casters - Front	4 inch	5 inch
Weight	80 lbs	94 lbs
Drain Valve	1.5 inch	3 inch
Dimensions (HxDxW)	40" x 33.5" x 20.5"	45" x 38" x 25.5"
Sound Levels	68 dB	68 dB





Tank Vacuum



Quick-Drop Drain Valves - 1.5" (V29) and 3" (V55)



Wheels, Casters & Molded Tank are Mounted on Strong Steel Frame