

Phone: 802-874-0123 Fax: 703-991-8770

Email: sales@tsitouch.com

tsitouch.com

NEC Infrared Touch Screen Solutions



NEC

Infrared Interactive Solution

The TSItouch solution is Infrared (IR) based, allowing for a high accuracy interactive experience. The usage of IR technology allows for virtually any input to be detected (pen/stylus, user's fingers, palms, gloved fingers). The TSItouch overlay is a full steel chassis integrated with tempered cover glass, which increases durability and optical clarity, while protecting the display.



Multi-Touch Screen

True multi-touch support for all major operating systems. 6, 10, 12, or 32 simultaneous touch point options are available



Ultra-Fast Response Time

Allows for split second reactions between touch point and screen. Rapid and smooth touch response



Superior Design

Full steel chassis combined with tempered glass provides additional protection to the LCD panel



Branding Free

Branding/logo free, not to divert attention from your brand and messaging



24/7 Commercial Grade Display

Commercial grade display with around the clock functionality



Easy Integration Unrivaled simplicity

makes installation easier and faster



HID Compliant


Maximum compatibly with numerous operating systems, plug-and-play





Customizable

Custom colors silk screening, and logos available

Solution Sizes Available







Specification	40"	48"	55″
Display Compatible	P404, V404	P484, V484	P554, V554
Part Number	TSI40NN10TACRZZ	TSI48NN10R6CRZZ	TSI55NN10R6CRZZ
Protective Glass	1/8" Anti-Reflective Cover Glass		
Touch Technology	IR		
Viewing Angle	178x178 degrees		
Touch Points	6 Point (10 Point Available)		
Response Time	16ms		
Touch Accuracy	+/- 2mm (Over 99% Area)		
Interface	Type A USB		
Communication	USB 2.0		
Power Supply Mode	Single USB connection (5v, 1A)		
Duty Cycle	24/7		
Audio Out / External Speaker Out	3.5mm Audio Mini Jack		
Panel Technology	SPVA	SPVA	S-IPS
Aspect Ratio	16:9		
Connectivity	HDMI 2.0 x2 (with HDCP), DVI-D (with HDCP), DisplayPort x2 (with HDCP)		
Native Resolution	1920 x 1080 (Full HD)		
Brightness	V Series: 500 nit / P Series 700 nit		
Orientation	Portrait, Landscape, Table Format		
Contrast Ratio	4000:1		1300:1
Width/Height/Depth Including Monitor	37.64" x 22.40" x 2.87"	44.09" x 25.94" x 2.99"	50.47" x 29.69" x 3.35"
Weight Without Monitor	20.50 lbs	25.79 lbs	33.51 lbs
OS Support	Windows, Google Chrome, Android, Mac, Linux		



Phone: 802-874-0123 Fax: 703-991-8770 Email: sales@tsitouch.com

tsitouch.com