

## NEC Infrared Touch Screen Solutions



### Infrared Interactive Solution

The TSi touch solution is Infrared (IR) based, allowing for a high accuracy interactive experience. The usage of IR technology allows for virtually any input to be detected (pen/stylus, user's fingers, palms, gloved fingers). The TSi touch overlay is a full steel chassis integrated with tempered cover glass, which increases durability and optical clarity, while protecting the display.



**Multi-Touch Screen**  
 True multi-touch support for all major operating systems. 6, 10, 12, or 32 simultaneous touch point options are available



**Ultra-Fast Response Time**  
 Allows for split second reactions between touch point and screen. Rapid and smooth touch response



**Superior Design**  
 Full steel chassis combined with tempered glass provides additional protection to the LCD panel



**Branding Free**  
 Branding/logo free, not to divert attention from your brand and messaging



**24/7 Commercial Grade Display**  
 Commercial grade display with around the clock functionality



**Easy Integration**  
 Unrivaled simplicity makes installation easier and faster




**HID Compliant**  
 Maximum compatibility with numerous operating systems, plug-and-play




**Customizable**  
 Custom colors silk screening, and logos available

### Solution Sizes Available


65"




75"



86"



98"



Specification	65"	75"	86"	98"
Display Compatible	C651Q	C751Q	C861Q	C981Q
Part Number	TSI65PNRHTACCZZ	TSI75PNRJTACCZZ	TSI86PNRKTACCZZ	TSI98PNFFRACCZZ
Protective Glass	3/16" Clear Tempered Cover Glass		1/4" Clear Tempered Cover Glass	
Viewing Angle	178x178 degrees			
Contrast Ratio	4000:1			
Touch Technology	Infrared			
Touch Points	10			
Response Time	16ms			
Touch Accuracy	+/- 1.5mm (Over 99% Area)			
Interface	Type A USB			
Communication	USB 2.0			
Power Supply Mode	Single USB connection (5v, 1A)			
Duty Cycle	24/7			
Panel Technology	AMVA3			
Aspect Ratio	16:9			
Native Resolution	3840x2160			
Brightness	400 nit	350 nit		
Orientation	Portrait / Landscape / Face Up / Face Down			
VESA Configuration	400 x 400mm (M6 x 4-hole)			
Width/Height/Depth Including Monitor	58.74" x 34.33" x 3.62"	67.57" x 39.17" x 4.02"	77.28" x 44.61" x 2.52"	87.84" x 50.58" x 4.67"
Weight Without Monitor	52.47 lbs	67.02 lbs	85.98 lbs	TBD
OS Support	Windows, Google Chrome, Android, Mac, Linux			