

Philips Signage Solutions D-Line Display

49" Powered by Android 450cd/m²

SignageSolutions



49BDL4051D

Say more

Smart, fast 24/7 display.

Make it stand out with a faster Philips D-Line Professional display. With Philips superb picture quality and Android SOC more powerful than ever before, capable of delivering complex content to capture your audience's attention. Specificall

Superb picture. Blazing processor speed.

- Android 7. Dedicated Android processor
- Proof of Play for Android content. Know what's playing
- Integrated dual-band WiFi
- Effortless setup. Total control.
- CMND & Control. Operate, monitor, maintain
- CMND & Create. Develop and launch your own content
- CMND & Deploy. Install and launch apps remotely
- Integrated mPCIe slot for optional 4G/LTE module

Cost-effective system solution

- FailOver. Ensure your display never goes blank
- Integrated HTML5 browser. Play and control online content
- Energy-saving automatic backlight control



Highlights

Powered by Android

Control your Philips professional display via an internet connection. The integrated Android OS (SoC) lets you install web and native Android apps directly to the display. A built-in scheduler makes it easy to launch apps and content based on time of day, or user. Auto-orientation ensures your content displays properly.

CMND & Control



Run your display network over a local (LAN) connection. CMND & Control allows you to perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

CMND & Create

Take control of your content with CMND & Create. A drag-and-drop interface makes it simple to publish your own content-whether it's a daily specials board or branded corporate information. Preloaded templates and integrated widgets ensure your stills, text, and video will be up and running in no time.

CMND & Deploy

Quickly install and launch any app-even when you're off-site and working remotely. CMND & Deploy lets you add and update your own apps, as well as apps from the Philips Professional Display App Store. Simply scan the QR code, log in to the store, and click on the app you want to install. The app is automatically downloaded and launched.

Integrated mPCIe slot

Easily connect 4G/LTE modules to your Philips professional display. The integrated mPCle slot

enables your display to communicate with other devices that share the same wireless connectivity. Invaluable if you're installing displays in locations such as banks or government buildings, where you cannot get onto the local network.

FailOver



From waiting room to meeting room, never show a blank screen. FailOver lets your Philips Professional Display switch automatically between primary and secondary inputs ensuring content keeps playing even if the primary source goes down. Simply set a list of alternate inputs to be sure your business is always on.

Specifications

Picture/Display

- Diagonal screen size: 48.5 inch / 123.2 cm
- Panel resolution: 1920x1080p Optimum resolution: 1920 x 1080 @ 60Hz
- Brightness: 450 cd/m²
- Contrast ratio (typical): 1100:1
- Dynamic contrast ratio: 500,000:1
- Aspect ratio: 16:9
- Response time (typical): 12 ms
- Pixel pitch: 0.55926 x 0.55926 mm
- · Display colors: 16.7 million
- Viewing angle (H / V): 178 / 178 degree
- Picture enhancement: 3/2 2/2 motion pull down, 3D Combfilter, Motion compens. deinterlacing, 3D MA deinterlacing, Progressive scan Operating system: Android 7.1.2
- Panel technology: IPS
- Placement: Landscape, Portrait


Connectivity

- Video input: Display Port1.2x1, DVI-I x 1, HDMI (x2)
- Video output: DisplayPort1.2x1, DVI-I x1
- Audio input: 3.5 mm jack
- Audio output: 3.5mm jack • External control: RJ45, RS232C (in/out) 2.5 mm jack,
- IR (in/out) 3.5 mm jack • Other connections: micro USB, USB 3.0, USB 2.0,
- micro SD

Supported Display Resolution

Computer formats Resolution Refresh rate 1920 x 1200 60Hz 1920×1080 60H7 1680 x 1050 60Hz 1600 x 1200 60Hz 1600 x 900 60Hz 1400 x 1050 60.75Hz 1440 x 1050 60H7 1440 x 900 60, 75Hz 1366 x 768 60Hz 1360 x 768 60Hz 1280×1024 60,67,75Hz 1280 x 720 60.70Hz 1280×800 60,75Hz

Philips 49BDL4051D Version: 1.0 Release Date: 2018/09/17



 1280×768

1024x768

1152 x 864

1152 × 900

1280 x 960

960x720

848 x 480

832 x 624

 800×600

720 x 400

640 x 480

 640×350

Video formats

Resolution

1080_D

1080i

720p

576i

576p

480p

480i

Dimensions

Convenience

DVI. RS232

Power

• Picture in picture: PIP

• Set dimensions (W x H x D):

Set dimensions in inch (W x H x D):

• Bezel width: 9.6 mm (T/L/R), 15.7 mm (B)

1097.6 x 633.9 x 45.5 mm

43.21 x 24.96 x 1.79 inch

• Product weight (lb): 32.63 lb

• Tiled Matrix: Up to 15 x 15

VESA Mount: 400 x 400 mm, M6

· Keyboard control: Hidden, Lockable

Network controllable: R|45, RS232

Screen saving functions: Pixel Shift

Standby power consumption: <0.5 W

Mains power: AC (100 ~ 240 V) , 2.5A

• Signal Loop Through: IR Loopthrough, DisplayPort,

• Product weight: 14.80 kg

60Hz, 75Hz

60, 70, 75Hz

56, 60, 72, 75Hz

60, 67, 72, 75Hz

60.70Hz

66Hz

60Hz

75Hz

60Hz

75Hz

70Hz

70Hz

Refresh rate

50. 60Hz

50, 60Hz 50, 60Hz

50Hz


50Hz

60Hz

60H7

5

PHILIPS	
E T	



© 2019 Koninklijke Philips N.V. All Rights reserved.

Version: 1.1.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 001 56731 EAN: 87 12581 75390 0 49BDL4051D/00

- Consumption (Typical): 75 W
- Consumption (On mode): 130W (max)

Operating conditions

- Temperature range (operation): 0 ~ 40 °C
- Temperature range (storage): -10 ~ 50 °C
- Altitude: 0 ~ 3000 m
- MTBF: 50,000 hour(s)
- Humidity range (operation)[RH]: 10 ~ 80% (without condensation)
- Humidity range (storage) [RH]: 0 ~ 90% (without condensation)

Sound

• Built-in speakers: 2 x 10W RMS

Accessories

- Included accessories: Remote Control, Batteries for remote control, Quick start guide, RS232 cable, AC Power Cord
- Stand: Universal Stand-L (BM05922)(Optional)
- Included Accessories: Edge Alignment Kit (1)-2pcs, Edge Alignment Kit (2)-1pcs, M2 Screw x2, M3 screw x 1, Philips logo, RS232 daisy-chain cable, SD card cover x 1, Thumb Screw x8

Multimedia Applications

- USB Playback Audio: AAC, M4A, MP3, WMA
- USB Playback Picture: BMP, JPEG, JPG, PNG
- USB Playback Video: MKV, MP4, MPEG, MPG, TS, VOB, WMV, ASF, AVI, DAT, FLV

Miscellaneous

- On-Screen Display Languages: English, French, German, Spanish, Polish, Turkish, Russian, Italian, Simplified Chinese, Traditional Chinese, Arabic, Japanese, Danish, Dutch, Finnish, Norwegian, Portuguese, Swedish
- Regulatory approvals: CE, BSMI, CB, EAC, EnergyStar 7.0, FCC, Class A, PSB, UL/cUL, CECP, FPA
- Warranty: 3 year warranty

Internal Player

- CPU: Dual-Core Cortex-A72 @2GHz, Quad-Core Cortex-A53 @ 1.5GHz, RK3399
- GPU: ARM Mali-T860 MP4
- Memory: 4GB DDR3
- Storage: 16GB EMMC
- Wifi: 2T2R, 802.11 ac/a/b/g/n, WCT07R2201

www.philips.com