



Compliant Product Line

Green Guard / LEED / California Compliant

PRODUCT NUMBER	FLAMMABILITY	APPLICATION	COMPLIANT / CERTIFIED			VOC* G/L	BENEFITS
			OTC	CA	GREENGUARD		
BULK SPRAY CONTACT CEMENTS							
HY-12NFM	N/F	Spray	•			249	<ul style="list-style-type: none"> High Heat Resistance Excellent Greenstrength Room Temperature Contactability LEED 4.4
HY-30 / HY-30G	N/F	Spray, Brush, Roll	•	•	•	0	<ul style="list-style-type: none"> Water-Base Excellent Room Temperature Contactability LEED 3.2, 4.1, 4.4 Postformable
HY-31 / HY-31G	N/F	Spray, Brush, Roll	•	•	•	53	<ul style="list-style-type: none"> Water-Base Excellent Room Temperature Contactability LEED 3.2, 4.1, 4.4 Postformable
HY-75NFM / HY-75NFMG	N/F	Spray	•			0	<ul style="list-style-type: none"> NO VOC High Solids High Heat Resistance LEED 4.4 Excellent Greenstrength Room Temperature Contactability Sprays Easily
HY-B68 / HY-B68R	F	Spray	•		•	241	<ul style="list-style-type: none"> Low VOC High Solids - Extended Mileage High Heat Resistance Excellent Bond Strength LEED 3.2, 4.4
HY-B68NF / HY-B68NFG	N/F	Spray	•		•	0	<ul style="list-style-type: none"> NO VOC High Solids High Heat Resistance LEED 4.4 Excellent Greenstrength Room Temperature Contactability Sprays Easily
HY-88 / HY-88R	F	Spray	•	•		0	<ul style="list-style-type: none"> Zero VOC High Bond Strength Long Open Time LEED 3.2, 4.4, 4.1
BULK BRUSH CONTACT CEMENTS							
HY-80NFM	N/F	Brush, Roll	•			240	<ul style="list-style-type: none"> High Heat Resistance Excellent Greenstrength & Room Temperature Contactability LEED 4.4
B68OH	F	Brush	•			217	<ul style="list-style-type: none"> Low VOC Long Open Time High Solids LEED 4.4
AEROSOL PRODUCTS							
CBA-655 General Purpose Contact Adhesive	F	Aerosol	•	•		<55% by weight	<ul style="list-style-type: none"> High Solids Good Heat Resistance Adjustable Spray Pattern LEED 4.4

*EPA Method 24

LEED Rating:

3.2 (Indoor Air Quality)

4.1 (Meets SCAQMD Air Quality Standard VOC 80g/l or less)

4.4 (No UREA-Formaldehyde Added)



CHOICE BRANDS
ADHESIVES

TO LEARN MORE ABOUT CHOICE BRANDS AND OUR PRODUCTS,
CALL 1.800.330.5566
666 REDNA TERRACE, CINCINNATI, OHIO 45215





Compliant Product Line

Green Guard / LEED / California Compliant

PRODUCT NUMBER	FLAMMABILITY	APPLICATION	COMPLIANT CERTIFIED			VOC* G/L	BENEFITS
			OTC	CA	GREENGUARD		
CANISTER PRODUCTS							
CBA-3000	F	Spray Canister	•			131	<ul style="list-style-type: none"> • Low VOC F-200 • High Heat Resistance • Fast Dry • LEED 4.4
CF-23NF	N/F	Spray Canister	•			22	<ul style="list-style-type: none"> • Low VOC • Excellent Heat Resistance • Long open time • LEED 3.2, 4.4 • Green Diamond • Excellent adhesion to a variety of substrates.
CF-88 / CF-88R	F	Spray Canister	•	•		37	<ul style="list-style-type: none"> • Low VOC • High Solids • Excellent Heat Resistance and Bond Strength • LEED 3.2, 4.4, 4.1
BULK WOOD GLUE							
HY-GG	N/A	Brush, Squeeze Bottle, Hand Roll, Glue Spreader	•	•	•	3.6	<ul style="list-style-type: none"> • Fast Setting Wood Glue • Use on Hard and Soft Wood • Easily Sanded • LEED 3.2, 4.1, 4.4
HY-GGE	N/A	Glue Spreader	•	•	•	18.1	<ul style="list-style-type: none"> • Type II Wood Glue • Exterior Grade • Hot or Cold Press • LEED 3.2, 4.1, 4.4 • RF Gluing • Fast Setting Wood Glue • Easily Sanded
XA-2600	N/A	Glue Spreader, Squeeze Bottle	•	•	•	13.1	<ul style="list-style-type: none"> • Aggressive Wet Grab • Assembly Adhesive for Cold Press Lamination or Wood Assembly • LEED 3.2, 4.1, 4.4
XA-2700	N/A	Brush, Hand Roll, Glue	•	•	•	2.23	<ul style="list-style-type: none"> • Aggressive Wet Grab • Assembly Adhesive for Cold Press Lamination or Wood Assembly • LEED 3.2, 4.1, 4.4
7709TG	N/A	Spray, Roll Coat	•	•	•	1.29	<ul style="list-style-type: none"> • Postformable • Dead Stack • Cold or Hot press • LEED 3.2, 4.1, 4.4
CBA-502	N/A	Brush, Hand Roll, Glue Spreader	•	•		10.23	<ul style="list-style-type: none"> • Excellent Wet Tack • Fast Setting • Good Moisture Resistance • LEED 3.2, 4.1, 4.4 • Hot Press • RF Gluing
CBA-531	N/A	Hand Roll, Glue Spreader	•	•		12.61	<ul style="list-style-type: none"> • Superior PVA emulsion • Difficult to bond surfaces • Excellent wet tack • LEED 3.2, 4.1, 4.4



*EPA Method 24

LEED Rating:

3.2 (Indoor Air Quality)

4.1 (Meets SCAQMD Air Quality Standard VOC 80g/l or less)

4.4 (No UREA-Formaldehyde Added)



CHOICE BRANDS
ADHESIVES