

# Medex<sup>®</sup>

## MDF

MEDFORD, OR

TECHNICAL DATA	IMPERIAL	METRIC
<b>Widths</b>	4 & 5 ft	1.22 & 1.52 m
<b>Lengths</b>	up to 18 ft	up to 5.49 m
<b>Thicknesses</b>	1/4 – 1-1/4 in	6.35 – 31.8 mm
<b>Density</b>	48 lbs/ft <sup>3</sup>	769 kg/m <sup>3</sup>
<b>Internal Bond</b>	250 psi	1.72 Nmm <sup>2</sup>
<b>Modulus of Rupture/MOR</b>	5,500 psi	37.9 Nmm <sup>2</sup>
<b>Modulus of Elasticity/MOE</b>	550,000 psi	3,792 Nmm <sup>2</sup>
<b>Hardness/MOH</b>	1,200 lbs	5,338 N
<b>Screw Holding – Face</b>	325 lbs	1,446 N
<b>Screw Holding – Edge</b>	280 lbs	1,245 N
<b>Thickness Swell</b>	3%	
<b>Linear Expansion</b>	0.25%	
<b>Moisture Content</b>	4 – 6%	
<b>Flame Spread Rating</b>	Class C (3)	
<b>Dimensional Tolerances:</b>		
Length/Width	±0.080 in	±2.0 mm
Squareness	±0.036 in/ft	±3.0 mm/m
Thickness – panel average from specified	±0.005 in	±0.125 mm
Thickness – variance from panel average	±0.005 in	±0.125 mm

Values represent averages for 3/4" thick panels. Mechanical properties are tested in accordance with ASTM D1037.

Customer-specified grades are available by request and subject to minimum order quantities.

## MEDIUM DENSITY FIBERBOARD

MDF panels with superior strength and moisture resistance made with no added formaldehyde (NAF).

## COMMON APPLICATIONS

- Cabinetry for high-moisture areas
- Furniture
- Lockers
- Retail displays
- Entry doors
- Signs
- Countertop substrate in high-moisture areas
- Wall cladding
- Millwork & trim in high-moisture areas



MDF

MEDFORD, OR

## STANDARDS & CERTIFICATIONS

Roseburg Medex MDF is tested and certified to meet or exceed the following standards and certifications.

### ANSI A208.2 – American National Standard – Medium Density Fiberboard (MDF) for Interior Applications

- ✓ Meets or exceeds ANSI A208.2 Grade 155
- ✓ Meets grade MR50 moisture resistance
- ✓ Exceeds requirements of ASTM D1037 six cycle accelerated aging test

### Formaldehyde Emissions Regulations – Third party certified (TPC-1) to meet the requirements of:

- ✓ EPA Formaldehyde Emission Regulation, TSCA Title VI\*
- ✓ Standards Council of Canada Formaldehyde Emissions Standard for Composite Wood Products – CAN/CSA 0160-16\*
- ✓ No Added Formaldehyde (NAF) Exempt - State of CA Executive Order N-20-313\*

### No Added Formaldehyde

- ✓ Scientific Certification Systems Validated (SCS-NAF-01329)\*

### Recycled Content

- ✓ Scientific Certification Systems Certified 92% pre-consumer recycled content (SCS-MC-01584)\*

### Environmental Product Declaration

- ✓ Type III Product Specific EPD Certified by UL Environment

### Forest Stewardship Council®

- ✓ Scientific Certification Systems Certified (SCS-COC/CW-00300) – FSC-C017580 FSC® Mix and FSC® Controlled Wood - AVAILABLE OPTION\*

### Eco-Certified Composite Grademark Program

- ✓ CPA ECC Sustainability Standard\*

\*Certificates and documentation available at [Roseburg.com](http://Roseburg.com)

## GREEN BUILDING SUPPORT:

For LEED® and other green building support documentation, visit [roseburg.com/product/medex](http://roseburg.com/product/medex)