

## TECHNICAL LEAFLET

### EGGER ABS EDGING, SUITABLE FOR LACQUERING



"Lacquerable edges" only differ in the surface from conventional EGGER ABS edging. Processing edges that are suitable for lacquering is simple in both continuous flow systems and processing centres. As regards processing, please consider EGGER ABS edging Processing Instructions.

It is usually not necessary to prime or sand the edging before, however, it must be free from dust and dirt. Using conventional separating agents, coolants or cleaning agents generates bonding problems in the lacquering step.

EGGER's edging are particularly suitable for lacquering, but many water-based lacquers have good bonding properties too. Coordination with the lacquer manufacturer and tests under local conditions are required with water-based 1-component lacquers.

The following combinations achieved positive results when combined with the EGGER priming film:

Lacquer manufacturer	Solvent lacquers	Water-based lacquers
<b>ADLER-Werk Lackfabrik Johann Berghofer GmbH &amp; Co KG</b> Bergwerkstr. 22 A-6130 Schwaz info@adler-lacke.com www.adler-lacke.com	■	■
<b>Akzo Nobel Wood Coatings GmbH</b> Geschäftsbereich Zweihorn Düsseldorfer Straße 96-100 40721 Hilden zweihorn@akzonobel.com www.zweihorn.com	■	■
<b>Sherwin-Williams ARTI GmbH</b> Paul-Gerhard-Str. 31 42389 Wuppertal Office@arti.de www.arti.de	■	Please note the information provided by the paint manufacturer
<b>Hesse GmbH &amp; Co.KG</b> Warendorfer Straße 21 59075 Hamm info@hesse-lignal.de www.hesse-lignal.de	■	■
<b>Jordan Lacke GmbH</b> Im Kreuz 6 D-97076 Würzburg info@jordanlacke.de www.jordanlacke.de	■	Please note the information provided by the paint manufacturer

Lacquer manufacturer	Solvent lacquers	Water-based lacquers
<b>Plantag Coatings GmbH</b> Plantagenweg 34 - 38 32758 Detmold info@plantag.de www.plantag.de	■	Please note the information provided by the paint manufacturer
<b>Remmers Baustofftechnik GmbH</b> Bernhard-Remmers-Straße 13 49624 Lönningen Info@remmers.de www.remmers.de	■	Please note the information provided by the paint manufacturer
<b>Lackfabrik Votteler GmbH &amp; Co. KG</b> Schwieberdinger Str. 97/102 D-70825 Korntal-Münchingen d.info@votteler.com www.votteler.de	■	Please note the information provided by the paint manufacturer

We recommend to clean EGGER priming film and EGGER ABS edging by sanding before lacquering. The technical data sheet "TM EGGER EURODEKOR E1 GFE" provides more information about laminated boards.

This technical leaflet has been carefully drawn up to the best of our knowledge. The information provided is based on practical experience and in-house tests and reflects our current level of knowledge. It is intended for information only and does not constitute a guarantee in terms of product properties or their suitability for specific applications. We accept no liability for any mistakes, errors in standards or printing errors. Furthermore, the continuous further development of EGGER edging as well as the amendment of standards and public documents may result in technical changes. This technical data sheet is not an instruction for use and not a legally binding document. Our General Terms and Conditions apply.