











Multiple plies of birch veneer render an aesthetically beautiful edge appearance.

Europly plus core with phenolic glue lines and decorative face veneers.

Panel thicknesses include 1/4", 1/2", 5/8", 3/4", and 1". Contact your Columbia representative for current availability.

Columbia's Europly PLUS™

panel assemblies raise the ante of quality in any furniture, millwork or cabinetry project where it can be incorporated for exceptional results.

Add the decorative veneers of your choice, and from any angle, the look is a visually striking, premium panel where the edge competes with the face for beauty. And the beauty is not skin deep, because the no added urea formaldehyde construction goes to the core.

Columbia Forest Products has provided fine decorative hardwood plywood veneer panels to North American fabricators for over 50 years.

Columbia's customers have grown to appreciate the widest product line in the industry from efficient, modern mills where exceptional service and product support are commonplace. For more information, please contact one of the regional offices listed below or visit us online at www.cfpwood.com.

| Core Properties* | | |
|--------------------------------------|------------|------------|
| Core specification | 1/2" | 3/4" |
| Core construction | 100% Birch | 100% Birch |
| Ply count (including face & back) | 11 | 15 |
| Glue type - core | Phenolic | Phenolic |
| Glue type - face/back lamination | Soy | Soy |
| Hardness (lbf) | 1,403 | 1,308 |
| Density (lbs/ft²) | 44 | 44 |
| Parallel MOE (psi) | 11,662 | 12,266 |
| Parallel MOR (psi) | 10,596 | 11,353 |
| Perpendicular MOE (psi) | 13,299,000 | 14,401,000 |
| Perpendicular MOR (psi) | 12,589 | 12,518 |
| Screw Holding - Face (lbs) | 721 | 620 |
| Screw Holding - Edge (lbs) | 511 | 442 |
| Formaldehyde Emissions (ppm) | < 0.05 | < 0.05 |
| Internal Bond (psi) | 278 | 393 |
| Water Absorption (%) | 28.3 | 25.2 |
| Thickness Swell (%) | 7.4 | 6.5 |
| Linear Expansion (%) | 0.09 | 0.06 |
| Width Expansion (%) | 0.12 | O.17 |
| Weight (lbs) 4' x 8' sheet | 57 | 85 |

Copyright © Columbia Forest Products. All Rights Reserved

Features & Benefits

- Eurostyle Edge. Europly PLUS offers a visually striking edge that designers and architects are demanding for a contemporary, natural appearance.
- > LEED®EQ 4.4 Compliant.
 Europly PLUS is a no added
 urea formaldehyde panel,
 compliant for use in LEED
 project work which calls for no
 added urea formaldehyde in
 lamination or core construction
 adhesives of interior composite
 panel products.
- > CARB Exempt and CARB
 Phase 2 Compliant.
 This product is manufactured
 to the ANSI HP-1 2009
 Hardwood Plywood Standard
 and tests below 0.05ppm for
 formaldehyde emissions and
 contains no added urea
 formaldehyde.
- > FSC®Certified. Europly Plus can be ordered FSC certified to add a chain-of-custody trace to responsibly managed forestlands and contribute credit towards the MR 7 certified wood credit in LEED project work. For more information on FSC constructions, visit the FSC page at www.cfpwood.com.
- > Columbia Offers Choice. Europly PLUS 1/2" and 3/4" constructions are typically available with short lead times. For other thicknesses, contact your Columbia sales representative.
- > Excellent Machinability.
 Europly PLUS provides
 a practically void-free
 construction to help reduce
 reject rates. Its high-density
 construction offers great
 machinability and tremendous
 screw holding capacity.

Proudly Supplied By



^{*}Test samples were constructed with rotary maple face and back. Test results for hardness can differ depending on density of decorative veneer. Wood is natural and variable to a certain extent. Test data is for informational purposes and does not represent a claim by Columbia that identical panel assemblies meet these properties in the field.