











Europly plus core with phenolic glue lines and decorative face veneers.

Panel thicknesses include 1/4", 1/2", 5/8", 3/4", and 1". Contact your Columbia representative for current availability.

Columbia's Europly PLUS™

panel assemblies raise the ante of quality in any furniture, millwork or cabinetry project where it can be incorporated for exceptional results.

Add the decorative veneers of your choice, and from any angle, the look is a visually striking, premium panel where the edge competes with the face for beauty. And the beauty is not skin deep, because the no added urea formaldehyde construction goes to the core.

Columbia Forest Products has provided fine decorative hardwood plywood veneer panels to North American fabricators for over 50 years.

Columbia's customers have grown to appreciate the widest product line in the industry from efficient, modern mills where exceptional service and product support are commonplace. For more information, please contact one of the regional offices listed below or visit us online at www.cfpwood.com.

Core Properties*		
Core specification	1/2"	3/4"
Core construction	100% Birch	100% Birch
Ply count (including face & back)	11	15
Glue type - core	Phenolic	Phenolic
Glue type - face/back lamination	Soy	Soy
Hardness (lbf)	1,403	1,308
Density (lbs/ft²)	44	44
Parallel MOE (psi)	11,662	12,266
Parallel MOR (psi)	10,596	11,353
Perpendicular MOE (psi)	13,299,000	14,401,000
Perpendicular MOR (psi)	12,589	12,518
Screw Holding - Face (lbs)	721	620
Screw Holding - Edge (lbs)	511	442
Formaldehyde Emissions (ppm)	< 0.05	< 0.05
Internal Bond (psi)	278	393
Water Absorption (%)	28.3	25.2
Thickness Swell (%)	7.4	6.5
Linear Expansion (%)	0.09	0.06
Width Expansion (%)	0.12	O.17
Weight (lbs) 4' x 8' sheet	57	85

Features & Benefits

- Eurostyle Edge. Europly PLUS offers a visually striking edge that designers and architects are demanding for a contemporary, natural appearance.
- ➤ LEED® EQ 4.4 Compliant. Europly PLUS is a no added urea formaldehyde panel, compliant for use in LEED project work which calls for no added urea formaldehyde in lamination or core construction adhesives of interior composite panel products.
- > CARB Exempt and CARB
 Phase 2 Compliant.
 This product is manufactured
 to the ANSI HP-1 2009
 Hardwood Plywood Standard
 and tests below 0.05ppm for
 formaldehyde emissions and
 contains no added urea
 formaldehyde.
- > FSC® Certified. Europly Plus can be ordered FSC certified to add a chain-of-custody trace to responsibly managed forestlands and contribute credit towards the MR 7 certified wood credit in LEED project work. For more information on FSC constructions, visit the FSC page at www.cfpwood.com.
- > Columbia Offers Choice. Europly PLUS 1/2" and 3/4" constructions are typically available with short lead times. For other thicknesses, contact your Columbia sales representative.
- ➤ Excellent Machinability. Europly PLUS provides a practically void-free construction to help reduce reject rates. Its high-density construction offers great machinability and tremendous screw holding capacity.

Copyright © Columbia Forest Products. All Rights Reserve

^{*}Test samples were constructed with rotary maple face and back. Test results for hardness can differ depending on density of decorative veneer. Wood is natural and variable to a certain extent. Test data is for informational purposes and does not represent a claim by Columbia that identical panel assemblies meet these properties in the field.

proudly supplied by



1-855-650-3265 | www.rugbyabp.com