## 45# Premium Industrial



Boise Cascade 45# Premium Industrial Particleboard. Dress it up with a variety of coatings and laminates. Boise Cascade 45# Premium Industrial Particleboard is renowned for its machining performance and edge integrity. Boise Cascade Company. The pride of the west.

## **THICKNESS RANGE**

3/8" through 1-3/16" or 9 mm through 30 mm

## **DESCRIPTION**

An engineered composite panel wood product made from 100% recycled Ponderosa pine and associated species of western wood particles formed and bonded with an interior resin.

Meets ANSI standard M-2.

## **SPECIFICATION CONFORMANCE**

The manufacturing standards shown below represent an average of all our product thicknesses. Conforms to American Society of Testing and Materials Fire Test Method E-84 (flamespread rating is Class C). Canadian Standard CAN/ULC-S102-M

MANUFACTURING STANDARDS Average	IMPERIAL	METRIC
Density	45.0 lb/ft <sup>3</sup>	0.721 g/cm <sup>3</sup>
Internal Bond	100 psi	0.689 N/mm <sup>2</sup>
Screw Holding - Face	250 lbs	1,112 N
Screw Holding - Edge	185 lbs	822.92 N
Formaldehyde, Emissions (CARB Phase 2)	< 0.09 ppm	< 0.09 ppm
Linear Expansion - Maximum	0.35%	0.35%
Water Absorption - Maximum	20.0%	20.0%
Thickness Swell - Maximum	0.035 inches	0.89 mm
Moisture Content	7%	7.0%
Sanding	100 grit	-

MANUFACTURING TOLERANCES	IMPERIAL	METRIC
Thickness Average from Target Value* *Target value 0.005 under nominal	±0.005 inches	±0.127 mm
Thickness Range (within panel) from Panel Average Value	±0.004 inches	±0.102 mm
Length and Width (within panel) from Specified Size	±0.0625 inches	±1.588 mm
Squareness (within panel) Maximum Deviation Between Diagonal Measurements	0.125 inches	3.175 mm
Straightness (within panel) Maximum Bow per 8' Length	0.0625 inches	1.588 mm

All products are available SFI® Chain-of-Custody Certified.





Boise Cascade
Particleboard

Proudly Distributed By

,

Contact Us



SEARCH
BE INSPIRED



hardwoods-inc.com

Visit Our Websites

designonesource.com

888.826.5528

info@hardwoods-inc.com