

Mirka Solutions

NORTH AMERICAN PRODUCT CATALOG



The Pioneers of Dust-Free Solutions

For more than two decades, Mirka has been at the forefront of dust-free sanding. Our patented Net structure means that no dust particle is ever more than 0.5 mm from a dust extraction hole, so it is always possible to see exactly what is happening at the sanding surface.

About US

Welcome to Mirka! We are making a continuous effort to bring you the best abrasives, tools, dust-free sanding systems, and accessories. This way, when partnering with Mirka, you can evolve your work and your business.

The following pages will show our broad range of products, from the new and innovative to the tried and true.

At Mirka, when we say we are Dedicated to the finish, we mean the results achieved by our customers. This dedication over the years has made us a world leader in sanding solutions for surface finishing and precision industries. We deliver one of the most diverse portfolios in the industry and help tackle projects from the ordinary to the extraordinary, and anything in between!

Our customers have the advantage of:

- Exceptional Support through our passionate and knowledgeable team members
- Pioneering Innovations that deliver next-generation products and processes
- Unwavering Dedication that enables a remarkable finish and inspires technicians, shop owners, creators, woodworkers and DIYers to perform better

We welcome your feedback on how we can best help you achieve your goals, whether through new products, partnerships, or other ideas.

Thanks for your interest in Mirka.

Symbols:

Industries:



Automotive Refinishing



Automotive Manufacturing



Composite



Construction/ Decoration



Glass



Industrial



Marine Industry



Transportation



Woodworking

Types of Abrasives:

































File Sheets





















Net File Sheets

Pads

Sheets

Narrow Belts

Wide Belts

Portable Belts Pump Sleeves

Mini Belts

P-Grade

Product Number Reference Guide:

Product numbers are by series, configuration and grit. The last digits of the product number are the GRIT (XXX).

EX. 9A-203-XXX = 9A-203-800 represents Abranet[®], 3" disc, P800

23-5MF-XXX = 23-5MF-320 represents Gold, 5" Multifit vacuum disc, P320

FM-611-XXX = FM-611-2500 represents Microstar*, 6" vacuum disc, P2500

For part numbers without dashes - the last two digits XX are the GRITS EX. Autonet, AE241050XX

80 = P80, 12 = P120, 15 = P150, 18 = P180, 25 = P240, 32 = P320, 41 = P400, 51 = P500, 61 = P600, 81 = P800

Table of Contents:

| 710117101710 | 3 | Sanding Sponges | 20 | DEROS RS 600X | 44 |
|---------------------|----|-----------------------------------|----|----------------------------------|----|
| Abralon® | 4 | Stryro System | 23 | DEROS + DEOS + DELTA | 45 |
| Abralon® J3 | 4 | WPF Pro | 24 | LEROS + LEROS-S | 46 |
| Abranet® | 5 | SANDING SYSTEMS | 25 | PROS CV / SGV / NV | 47 |
| Abranet® Ace | 6 | Golden Finish | 26 | Pneumatic Belt Sanders | 48 |
| Abranet® Ace HD | 6 | OSP | 27 | MR-Series Pneumatic Tools | 49 |
| Autonet® | 7 | ABRASIVE BELTS | 28 | Two-Handed Tools | 52 |
| Galaxy | 8 | Abranet® Max Belts | 29 | ESSENTIALS | 53 |
| Gold | 9 | Hiolit® JCA2A0 Belts | 29 | Paint Cups | 54 |
| Gold Film | 10 | Hiolit® XO Belts | 30 | PCS Spray Gun Adapter Versions | 55 |
| Gold ProFlex | 11 | Jepuflex Antistatic Belts | 31 | Tapes + Film | 57 |
| Goldflex Soft | 11 | Ultimax® Belts | 31 | DUST-FREE SYSTEMS | 58 |
| Gold Soft | 11 | Sica Closed Belts | 32 | Dust Extractors | 59 |
| Iridium™ | 12 | Sica Fine Stearate Belts | 32 | Modular Trolley – Pro Model | 60 |
| Iridium™ SR | 13 | Mini File Belts | 33 | Dust-Free Sanding Systems | 61 |
| Jepuflex Antistatic | 14 | Surface Conditioning Belts | 33 | Abrasive Trial Kits | 64 |
| Microstar® | 14 | Grinding Discs | 34 | Dust Extractor Accessories | 65 |
| Mirlon® | 15 | POLISH | 36 | ACCESSORIES | 66 |
| Mirlon Total® | 15 | Polarshine® | 37 | Hand Sanding Tools + Accessories | 67 |
| Ultimax® Ligno | 16 | PRO Iridium™ 1250 | 37 | Backup Pads | 68 |
| Basecut | 17 | Pro Finishing Solution | 38 | Interface Pads | 70 |
| Caratflex | 17 | Polishing Pads | 39 | Protector Pads | 71 |
| Coarse Cut | 18 | Marine Polishing Kit | 39 | Miscellaneous Accessories | 72 |
| Hiolit® XO / JCA2A0 | 18 | POWER TOOLS | 41 | GRIT COMPARISON CHART | 73 |
| Polarstar® SR | 19 | Cordless File Belt Sander (FBS-B) | 42 | INDEX | 74 |
| Q.Silver® | 19 | Cordless Tools | 43 | | |

All products shown in the catalog are P-Grade with a few exceptions. Abralon (except J3), Galaxy, Gold Film 23-6NHF 800-1500, Iridium, Mini File Belts, Q.Silver 2C-611 Series, SR discs, and Ultimax Ligno are not P-Grade.



NEW POWER TOOLS

FBS-B Cordless File Belt Sanders

The new rugged FBS-B Cordless File Belt Sanders enhance efficiency and flexibility in auto body and metalworking with their ergonomic, durable design. Ideal for cleaning seams, spot welds, and paint removal, they offer seamless maneuverability without cumbersome cords.

PAGE **42**



Mirka® DEROS RS 600X

The DEROS RS 600X Rotary Sander is an ergonomic, light, and quiet tool, designed for heavy-duty performance across a variety of materials and applications. Its powerful rotary action ensures ease of use, making it ideal for both rough tasks and general-purpose sanding.

PAGE 44



NEW DUST-FREE SYSTEM

Mirka[®] Modular Trolley - Pro Model

Maximize Productivity with the New Modular Trolley - Pro Model!

The new mobile workbench streamlines workflow by keeping tools, supplies, and a dust extractor within quick, ergonomic reach. Designed for efficiency, this sturdy, smooth-moving trolley ensures everything is exactly where you need it.

Featuring spacious soft-close drawers, a configurable tool board, a rubberized work surface, spray gun and aerosol can holders, a moveable hose arm, and versatile hooks for tools and cables, the Modular Trolley – Pro Model supports an efficient professional workflow for collision repair, finishing, and polishing.

Available ready-to-fill or as a Mirka* Dust-Free Sanding System that comes equipped with a power tool, hand sanding tool, dust extractor with hose, and more.

PAGE 60





A world leader in surface finishing, Mirka manufactures a complete range of technically superior abrasives

Mirka offers abrasives in all shapes and sizes, tailored for every sanding application, including the original net abrasives for dust-free sanding. Designed for professionals, our premium abrasives deliver superior performance, helping you to sand more efficiently and to achieve a flawless finish every time.



Abralon®

Foam Abrasive















Technical Specifications

| Grain | Silicon carbide |
|----------------|-------------------------|
| Bonding | Special Resin |
| Backing | Knitted fabric on foam |
| Coating | Special Abralon® method |
| Color | Gray |
| Attachment | Grip |
| Foam Density | 33 kg/m ² |
| Foam Thickness | 6.5 mm |
| | |

FEATURES AND BENEFITS:

- Combines benefits of abrasive cloth and non-woven products
- Constructed of fabric face, foam center and a grip backing
- Abrasive grains are bonded evenly to the fabric face
- Can be used for dry or wet sanding

Abralon[®] J3 Foam Abrasive

8M Series









| Tech | nical Specifications |
|--------------|-------------------------|
| Grain | Silicon carbide |
| Bonding | Special Resin |
| Backing | Knitted fabric on foam |
| Coating | Special Abralon® method |
| Color | Gray |
| Attachment | Grip |
| Foam Density | 62 kg/m ² |
| | |

Open cell design holds large amounts of water or solvent for lubrication and cooling

Foam Thickness 3 mm

Abralon° Foam Abrasive

| | Part Number: | Size: | Description: | 180 | 220 | 240 | 360 | 400 | 500 | 600 | 800 | 1000 | 2000 | 3000 | 4000 | AP |
|---|--------------|-------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|----|
| • | 8A-600-XXX | 11⁄4" | Grip | | | | • | | • | | | • | • | | • | |
| | 8A-203-XXX | 3" | Grip | • | | | • | | • | | | • | • | • | • | • |
| | 8A-232-XXX | 5" | Grip | • | | | • | | • | • | | • | • | • | | |
| | 8A-240-XXX | 6" | Grip | • | | | • | | • | | | • | • | • | • | |
| | 8A-241-XXX | 6" | Grip | • | | | • | | • | | | • | • | • | • | • |
| * | 8A-241-XXXRP | 6" | Grip | • | | | • | | • | | | • | • | | • | • |
| | 8A-618-XXX | 12" | Grip | • | | | • | | • | | | • | • | | | |

^{*} XXXRP = Smaller packages designed for retail sales

Abralon[°] J3 Foam Abrasive

| | Part Number: | Size: | Description: | 180 | 220 | 240 | 360 | 400 | 500 | 600 | 800 | 1000 | 2000 | 3000 | 4000 | AP |
|---|--------------|-------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|----|
| • | 8M-203-XXX | 3" | Grip | | | | | | | | | • | • | • | • | |
| | 8M-241-XXX | 6" | Grip | | | | | | | | | • | • | • | • | |
| | 8M-223-XXX | 9" | Grip | | | | • | | • | | | • | • | | • | |

DID YOU KNOW?

Some common applications for Abralon® abrasives include:

- Pre-polishing clearcoats (1000-4000)
- Surface finishing of aluminum or stainless steel
- Finishing of solid surface counter tops
- Sanding of sealers and primers (180-500)
- Removing mold marks and flash from plastic parts
- · Finishing glass surfaces



Abranet°

Net Abrasive

9A Series 😂 📾











Technical Specifications

| 1001 | inical Specifications |
|------------|-----------------------|
| Grain | Aluminum oxide |
| Bonding | Resin over resin |
| Backing | Polyamide net |
| Coating | Closed |
| Color | Maroon |
| Attachment | Grip |



- Net abrasives are a key component for dust-free sanding
- Removal of dust particles eliminates loading and pilling problems
- Woven mesh backing works with hook and loop attachment
- Designed for dry sanding by machine or by hand
- Available in discs, sheets, and rolls

| Abranet® | Net Abrasive | P | | | | | | | | | | | | | | | |
|----------|--------------|-----------------|--------------------|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|----|
| | Part Number: | Size: | Description: | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 320 | 400 | 500 | 600 | 800 | 1000 | AP |
| • | 9A-600-XXX | 11⁄4" | Grip | • | | • | • | • | | • | • | • | | | | | |
| | 9A-203-XXX | 3" | Grip | • | • | • | • | • | • | • | • | • | | • | | | • |
| | 9A-232-XXX | 5" | Grip | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| | 9A-232-XXXRP | 5" | Grip | • | • | • | • | • | • | | • | • | | • | | | • |
| | 9A-241-XXX | 6" | Grip | • | • | • | • | • | • | • | • | • | | • | • | • | • |
| | 9A-241-XXXRP | 6" | Grip | • | • | • | • | • | • | | • | • | | • | | | • |
| | 9A-252-XXX | 8" | Grip | • | | • | | • | | • | • | • | | • | • | | |
| | 9A-223-XXX | 9" | Grip | • | • | • | • | • | | • | | | | | | | |
| | 9A-223-XXXRP | 9" | Grip | • | • | • | • | • | | • | | | | | | | |
| | 9A-262-XXX | 11" | Grip | • | | • | | • | | • | • | • | | | | | |
| # | 9A-219-XXX | 4" x 6" x 6" | Grip | • | | • | • | • | | • | | | | | | | |
| # | 9A-219-XXXRP | 4" x 6" x 6" | Grip | • | | • | • | • | | • | | | | | | | |
| a | 9A-570-XXX | 2¾" x 10 yds. | Grip | • | • | • | | • | | • | • | • | | | | | |
| | 9A-149-XXX | 2¾" x 5" | Grip | • | | • | • | • | • | • | • | • | | • | | | • |
| | 9A-150-XXX | 2¾" x 8" | Grip | • | | • | • | • | • | • | • | • | | | | | • |
| | 9A-150-XXXRP | 2¾" x 8" | Grip | • | • | • | • | • | • | | • | • | | • | | | • |
| | 9A-151-XXX | 2¾" x 16½" | Grip | • | • | • | • | • | | • | • | • | | | | | • |
| | 9A-129-XXX | 3" x 4" | Grip | • | | • | • | • | • | • | • | • | | | | | |
| | 9A-129-XXXRP | 3" x 4" | Grip | • | | • | • | • | • | | • | • | | | | | |
| | 9A-175-XXXRP | 3" x 9" | Grip | • | | • | | • | | • | | | | | | | |
| | 9A-178-XXX | 3" x 5" | Grip | • | • | • | • | • | | • | • | • | • | • | | | |
| | 9A-178-XXXRP | 3" x 5" | Grip | • | | • | • | • | • | | • | • | | | | | |
| Q | 9A-593-XXX | 3.67" x 82' | Grip | | | | | | | | • | • | | • | | | |
| | 9A-110-XXX | 41/2" x 10 yds. | Grip | • | • | • | | • | | • | • | • | | | | | |
| | 9A-125-XXX | 4½" x 25 yds. | Grip | • | | • | | • | | • | • | • | | | | | |
| | 9A-555-XXX | 4½" x 8.2' | Grip, Roll | • | | • | | • | | • | | | | | | | |
| | 9N-232-400B | 5" | Grip, Non-Stearate | | | | | | | | | • | | | | | |
| | 9L-232-400 | 5" | Grip, Liner | | | | | | | | | • | | | | | |

Abranet® Ace

Net Abrasive

AC Series











| Technical | Specifications |
|-----------|----------------|
|-----------|----------------|

| 1001 | inical specifications |
|------------|------------------------|
| Grain | Ceramic/Ceramic coated |
| Bonding | Resin over resin |
| Backing | Polyamide net |
| Coating | Closed |
| Color | Light Maroon |
| Attachment | Grip |

FEATURES AND BENEFITS:

- Developed to achieve outstanding results on challenging surface conditioning and repair applications
- Well-designed for metal applications
- Removal of dust particles eliminates loading and pilling problems
- Improved woven mesh backing offers increased strength and edge wear
- Net abrasives are a key component for dust-free sanding

Abranet® Ace HD

Net Abrasive

AH Series 😂 🋗











| ieci | rechnical specifications | | | | | | | | | |
|------------|--------------------------|--|--|--|--|--|--|--|--|--|
| Grain | Ceramic | | | | | | | | | |
| Bonding | Resin over resin | | | | | | | | | |
| Backing | Polyamide net | | | | | | | | | |
| Coating | Closed | | | | | | | | | |
| Color | Brown | | | | | | | | | |
| Attachment | Grip | | | | | | | | | |

- Ceramic grains allow for maximum cutting speed and consistent performance across a variety of surfaces and substrates
- Coarse grit range makes this ideal for aggressive stock removal
- Features exceptional resistance to edge wear and clogging
- Net abrasives are a key component for dust-free sanding

| Abranet [®] Ace | Net Abrasive | P |
|--------------------------|--------------|---|
| | | |

| Part Number: | Size: | Description: | 40 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 320 | 400 | 500 | 600 | 800 | 1000 |
|--------------|---------|--------------|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| AC-129-XXX | 3" x 4" | Grip | | | • | | • | • | • | | • | • | • | | • | | |
| AC-178-XXX | 3" x 5" | Grip | | | • | • | • | • | • | | • | • | • | | | | |
| AC-203-XXX | 3" | Grip | | | • | | | | • | • | | • | • | • | • | • | |
| AC-232-XXX | 5" | Grip | | | • | • | • | • | • | • | • | • | • | • | • | • | • |
| AC-241-XXX | 6" | Grip | | | • | • | • | • | • | • | • | • | • | • | • | • | • |
| AC-223-XXX | 9" | Grip | | | • | • | • | • | • | • | • | • | • | | | | • |

| Abranet® Ace HD | Net Abrasive | P |
|-----------------|--------------|---|
| | | |

| - | | Part Number: | Size: | Description: | 40 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 320 | 400 | 500 | 600 | 800 | AP |
|---|---|--------------|---------------|--------------|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| * | | AH-219-XXXRP | 4" x 6" x 6" | Grip | • | • | • | | • | | | | | | | | | | |
| | | AH-232-XXX | 5" | Grip | • | • | • | | • | | | | | | | | | | |
| * | | AH-232-XXXRP | 5" | Grip | • | | • | | | | | | | | | | | | |
| | | AH-241-XXX | 6" | Grip | • | • | • | | • | | | | | | | | | | |
| * | | AH-241-XXXRP | 6" | Grip | • | • | • | | • | | | | | | | | | | |
| | | AH-252-XXX | 8" | Grip | • | • | • | | | | | | | | | | | | |
| | | AH-223-XXX | 9" | Grip | • | • | • | | • | | | | | | | | | | |
| * | | AH-223-XXXRP | 9" | Grip | • | • | • | | • | | | | | | | | | | |
| | 0 | AH-570-XXX | 2¾" x 10 yds. | Grip | • | • | • | | | | | | | | | | | | |

^{*} XXXRP = Smaller packages designed for retail sales

Autonet®

Net Abrasive








| specifications |
|----------------|
| 5 |

| | • |
|------------|------------------|
| Grain | Aluminum oxide |
| Bonding | Resin over resin |
| Backing | Polyamide net |
| Coating | Closed |
| Color | Gray |
| Attachment | Grip |

FEATURES AND BENEFITS:

- Excellent initial aggressivity
- Long life-span compared to paper-backed discs
- Eliminates clogging and pilling
- Developed specifically for the automotive repair industry
- Rolls have perforations every 2¾" making it simple to get the desired length
- Net abrasives are a key component for dust-free sanding



| 1 | Autone | e t ° Net Abras | sive P | | | | | | | | | | | | | | | | |
|---|----------|------------------------|---------------|-----------------|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| | | Part Number: | Size: | Description: | 40 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 320 | 400 | 500 | 600 | 800 | 1000 |
| | | AE-203-XXX | 3" | Grip | | | • | | • | • | • | | • | • | • | | • | • | |
| | | AE232050XX | 5" | Grip | | | • | | • | • | • | | • | • | • | • | • | • | |
| | | AE241050XX | 6" | Grip | | | • | | • | • | • | | • | • | • | • | • | • | |
| * | a | AE-570-XXX | 2¾" x 11 yds. | Grip, Perf Roll | | | • | | • | • | • | | • | • | • | | • | | |

^{*} Perforated every 2¾"

For Autonet® part numbers without dashes - the last two digits represent the grit: 80 = P80, 12 = P120, 15 = P150, 18 = P180, 25 = P240, 32 = P320, 41 = P400, 51 = P500, 61 = P600, 81 = P800



DID YOU KNOW?

Keeping Autonet's sanding surface free from dust ensures that it maintains its impressive cutting power for much longer, reducing the need for frequent abrasive changes and ultimately resulting in fewer abrasives used per job.

A Mirka dust extractor is the most efficient way to do this, but also simply clearing away accumulated paint dust and filler residue helps keep abrasive waste to a minimum.



Galaxy

Film Abrasive


FY Series











Technical Specifications

| Grain | Ceramic/Aluminum oxide |
|------------|------------------------|
| Bonding | Low VOC resin system |
| Backing | Polyester film |
| Coating | Semi-open |
| Color | Blueish |
| Attachment | Grip and PSA |

FEATURES AND BENEFITS:

- Self-Sharpening grains continue cutting from edge-to-edge
- New, sharp grains form as you sand
- Lasting sharpness means a long life and a fast cut
- Clog resistant coating repels dust to keep grains free to cut
- Scratch pattern of finer grits polishes out easily
- Higher grits can be used to polish with Polarshine® compounds

| Galaxy Film Abrasive | Nultifit Multifit hole pattern available in 3", 5", and 6" discs. |
|----------------------|--|
|----------------------|--|

| | Part Number: | Size: | Description: | 40 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 320 | 400 | 500 | 600 | 800 | 1000 | 1200 | 1500 | 2000 |
|-----|--------------|------------|---------------------------|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|
| | FY-608-XXX | 3" | No-Hole, Grip | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| | FY-612-XXX | 5" | No-Hole, Grip | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| | FY-622-XXX | 6" | No-Hole, Grip | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| | FY-680-XXX | 9" | 24-Hole, Grip | | | • | | • | | • | • | • | • | • | • | | | | | | |
| | FY-3MF-XXX | 3" | Multifit, Grip | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| | FY-5MF-XXX | 5" | Multifit, Grip | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| | FY-6MF-XXX | 6" | Multifit, Grip | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| 56 | FY-5PF-XXX | 5" | No-Hole, Linkroll, PSA | | | • | • | • | • | • | • | • | • | • | • | • | • | • | | | |
| 5 | FY-6PF-XXX | 6" | No-Hole, Linkroll, PSA | | | • | • | • | • | • | • | • | • | • | • | • | • | • | | | |
| | FY-631-XXX | 8" | No-Hole, Grip | • | • | • | • | • | • | • | • | • | • | • | | | | | | | |
| * 🔾 | FY-570-XXX | 2¾" x 33½' | Multifit, Grip, Perf Roll | • | • | • | • | • | • | • | • | • | • | • | | | | | | | |

^{*} Perforated every 23/4"

DID YOU KNOW?









9956-MF 6" Multifit Protector Pad

Optimized for superior dust extraction, the Mirka* Multifit Backup Pad is specifically designed for use with 6" Galaxy Multifit discs. It's ideal for use during primer sanding in collision repair and marine applications.

The backing pad comes with a custom Multifit Pad Saver, which acts as a protective layer between the backing pad and the Galaxy disc, preventing wear and tear during continuous, aggressive sanding (also sold separately).

Gold

Paper Abrasive

23 Series













- Designed for both finishing and heavy stock removal
- Aluminum oxide grain delivers a fast, long lasting cut
- High strength resin bonding provides superior grain support
- Special stearate coating is used to maximize resistance to clogging and loading
- Semi-open coat produces an even, consistent scratch pattern



| Tech | Technical Specifications | | | | | | | | | | | | |
|---------------------------------|---------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|
| Grain | Aluminum oxide | | | | | | | | | | | | |
| Bonding | Resin over resin | | | | | | | | | | | | |
| Backing | D-weight / C-weight paper | | | | | | | | | | | | |
| Coating | Semi-open | | | | | | | | | | | | |
| Color | Gold | | | | | | | | | | | | |
| Attachment Grip, PSA, and Plain | | | | | | | | | | | | | |

| Gold | Paper Abrasive P | Mul | tifit Multifit hole p | attern | avai | labl | e in 5 | 5", an | d 6" c | discs. | | | | | | | | | |
|------|------------------|---------------|------------------------------|--------|------|------|--------|--------|--------|--------|-----|-------|-----|-----|-----|-----|-----|-----|-----|
| | Part Number: | Size: | Description: | 36 | 40 | 60 | 80 | 100 | 120 | 150 | 180 | 220 2 | 240 | 280 | 320 | 400 | 500 | 600 | 800 |
| | 23-170-XXX | 2¾" x 17½" | No-Hole, Plain | • | • | • | • | • | • | • | • | • | | | | | | | |
| | 23-308-XXX | 31/2" | No-Hole, PSA | | | | • | | | • | | • | | | | | | | |
| | 23-314-XXX | 5" | No-Hole, PSA, Linkroll | | | | • | • | • | • | • | • | • | | • | • | • | • | • |
| | 23-320-XXX | 5" | 8-Hole, PSA | | | | • | • | • | • | | • | | | • | | | | |
| | 23-321-XXX | 5" | 5-Hole, PSA | | | • | • | • | • | • | • | • | • | | • | • | | | |
| | 23-332-XXX | 5" | No-Hole, PSA | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| | 23-341-XXX | 6" | No-Hole, PSA | • | • | • | • | | | | | | | | | | | • | • |
| | 23-341-XXXRP | 6" | No-Hole, PSA | • | • | | • | | • | | • | • | | | • | • | | | |
| 66 | 23-342-XXX | 6" | No-Hole, PSA, Linkroll | | | | • | • | • | • | • | • | • | • | • | • | • | | |
| | 23-352-XXX | 8" | No-Hole, PSA | • | • | | • | • | • | • | • | • | | | • | • | | | |
| | 23-352-XXXRP | 8" | No-Hole, PSA | • | • | | • | | | | | | | | | | | | |
| | 23-364-XXX | 2¾" x 16½" | No-Hole, PSA | • | • | • | • | | • | | | | | | | | | | |
| | 23-364-XXXRP | 2¾" x 16½" | No-Hole, PSA | • | • | | • | • | • | | | | | | | | | | |
| | 23-379-XXX | 6" | No-Hole, PSA, Autobox | | | | • | • | • | • | • | • | | | • | • | | | |
| | 23-388-XXX | 5" | No-Hole, PSA, Autobox | | | | • | • | • | • | • | • | • | | • | • | | | |
| | 23-5MF-XXX | 5" | Multifit, Grip | | • | • | • | • | • | • | • | • | • | | • | • | • | • | • |
| 0_ | 23-573-XXX | 4½" x 10 yds. | PSA, Autokut | | | | • | • | • | • | • | • | | | • | • | | | |
| 0 | 23-574-XXX | 2¾" x 20 yds. | PSA, Autokut | | | | • | • | | | | | | | | | | | |
| 0 | 23-584-XXX | 2¾" x 40 yds. | PSA, Autokut | | | | | | • | • | • | • | • | | • | • | | • | |
| | 23-6MF-XXX | 6" | Multifit, Grip | | • | • | • | • | • | • | • | • | • | | • | • | | • | • |
| • | 23-608-XXX | 3" | No-Hole, Grip | | | | • | | • | • | • | • | • | | • | • | • | • | • |
| | 23-612-XXX | 5" | No-Hole, Grip | • | • | • | • | • | • | • | • | • | • | | • | • | • | • | • |
| | 23-622-XXX | 6" | No-Hole, Grip | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| | 23-631-XXX | 8" | No-Hole, Grip | • | | | • | | | | • | | | | | | | | |
| • | 23-632-XXX | 8" | 9-Hole, Grip | | | | | | | | • | | | | • | | | | |
| • | 23-634-XXX | 3" | 6-Hole, Grip | | | | • | | | | | • | | | • | • | | • | • |
| :::: | 23-635-XXX | 2¾" x 8" | 8-Hole, Grip | | | | • | | • | • | • | • | | | • | • | | | |
| | 23-648-XXX | 9" | 27-Hole, Grip | | | | • | • | • | • | • | | • | | | | | | |
| | 23-648-XXXRP | 9" | 27-Hole, Grip | | | | • | • | • | • | • | | • | | | | | | |
| | 23-663-XXX | 2¾" x 16½" | No-Hole, Grip | • | • | | • | | | | | | | | | | | | |
| :::: | 23-688-XXX | 3" x 5" | 8-Hole, Grip | | | | • | • | • | • | • | • | • | | • | | | | |
| | XS-23-641-XXX | 3" x 4" | Grip | | | | • | • | • | • | • | • | • | | • | • | | | |

















| | JY 11 15 16 |
|------------|----------------------|
| Tech | nical Specifications |
| Grain | Aluminum oxide |
| Bonding | Low VOC resin system |
| Backing | Polyester Film |
| Coating | Semi-open |
| Color | White |
| Attachment | Grip and PSA |

FEATURES AND BENEFITS:

- Designed for fine finishing
- Aluminum oxide grain delivers a fast and long lasting cut
- High strength resin bonding provides superior grain support
- Special stearate coating is used to maximize resistance to loading
- Semi-open coat produces an even, consistent scratch pattern

| G | iold Film | Film Abrasive | P | Multifit | Multifit ho | le pattern | availa | ble in | 5", ar | ıd 6" c | liscs. | | | | | | |
|---|-----------|---------------|-------|----------------|-------------|------------|--------|--------|--------|---------|--------|-----|-----|------|------|------|------|
| | | Part Number: | Size: | Description: | 120 150 | 180 220 | 240 | 280 | 320 | 400 | 500 | 600 | 800 | 1000 | 1200 | 1500 | 2000 |
| | | 23-3NHF-XXX | 3" | No-Hole, Grip | | | | | | | | • | | • | • | • | • |
| | | 23-5MFF-XXX | 5" | Multifit, Grip | | | | | | | | • | • | • | • | • | • |
| | | 23-5NHF-XXX | 5" | No-Hole, Grip | | | | | | | | • | • | • | • | • | • |
| | | 23-6MFF-XXX | 6" | Multifit, Grip | | | | | | | | | • | • | • | • | • |
| * | | 23-6NHF-XXX | 6" | No-Hole, Grip | | | | | | | | | • | • | • | • | • |

^{* 23-6}NHF-XXX, 800-1500 grits are not P-Graded

DID YOU KNOW?

Mirka's abrasive product line is full of Gold! Great, reliable products that are continually updated to keep pace with today's technology – like the new Multifit line that fits any dust-free tool.

Here's a favorite:

Goldflex Soft is the perfect combination of a cut sheet and a sanding sponge. It sands the surface as flat as a sheet but also provides the flexibility to round contours like a sanding sponge. It's excellent for softening the edges prior to top coat adhesion.



Gold ProFlex

Paper Abrasive

23 Series 😂













Technical Specifications

| Grain | Aluminum oxide |
|------------|-------------------------------------|
| Bonding | Resin over resin |
| Backing | P80-P180 C-paper, P220-P800 B-paper |
| Coating | Semi-open |
| Color | Gold |
| Attachment | Plain |

FEATURES AND BENEFITS:

- Designed for hand sanding applications
- Aluminum oxide grain provides a good cut and an excellent scratch pattern
- Flexible, latex-impregnated backing provides superior conformity in profile sanding
- Anti-slip coating on the back side provides a solid grip and feel during sanding

Goldflex Soft

Paper Abrasive

23 Series











Technical Specifications

| | <u> </u> |
|------------|----------------------------|
| Grain | Aluminum oxide |
| Bonding | Resin over resin |
| Backing | A-latex paper with PE foam |
| Coating | Semi-open |
| Color | Gold |
| Attachment | Plain |

FEATURES AND BENEFITS:

- Designed for hand sanding applications
- A-weight, latex impregnated paper backing with PE foam is highly flexible and ideal for profile sanding
- Produces a high quality finish
- Durable, aluminum oxide grain delivers a long lasting, smooth cut
- Bulk roll is perforated to allow easy sheet dispensing from box

Gold Proflex Paper Abrasive

| | Part Number: | Size: | Description: | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 280 | 320 | 400 | 500 | 600 | 800 | 1000 | 1200 |
|---|--------------|----------|--------------|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|
| | 23-104-XXX | 9" x 11" | Plain | • | • | • | • | • | • | • | | • | • | • | • | • | | |
| * | 23-104-XXXRP | 9" x 11" | Plain | • | • | • | • | • | • | • | | • | • | • | | | | |

^{*} XXXRP = Smaller packages designed for retail sales

Goldflex Soft Paper Abrasive

| | Part Number: | Size: | Description: | 80 | 100 | 120 | 150 | 180 | 220 2 | 40 280 | 320 | 400 | 500 | 600 | 800 | 1000 | 1200 | 1500 |
|---|--------------|----------|--------------|----|-----|-----|-----|-----|-------|--------|-----|-----|-----|-----|-----|------|------|------|
| | 23-145-XXX | 4½" x 5" | Plain | | | | • | • | • | • | • | • | • | • | • | • | | |
| * | 23-145-XXXRP | 4½" x 5" | Plain | • | | • | • | | (| • | • | | | | | | | |

^{*} XXXRP = Smaller packages designed for retail sales

Gold Soft

Paper Abrasive

23 Series









FEATURES AND BENEFITS:

- Designed for final sanding of e-coats, primers, sealers and panel blends
- Durable, aluminum oxide grain delivers a long lasting, smooth cut
- A special stearate coating is used to resist clogging and loading
- 6" 15-hole discs can be used with or without vacuum



| Technical | Specifications |
|-----------|----------------|
| مبيلا | ainum avida |

| Grain | Aluminum oxide |
|------------|----------------------|
| Bonding | Resin over resin |
| Backing | C-paper with PE-foam |
| Coating | Semi-open |
| Color | Gold |
| Attachment | Grip |



Paper Abrasive



| Part Number: | Size: | Description: | 80 | 100 | 120 1 | 150 | 180 | 220 | 240 | 280 | 320 | 400 | 500 | 600 | 800 | 1000 | 1200 | 1500 |
|--------------|-------|---------------|----|-----|--------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|
| 23-645-XXX | 6" | 15-Hole, Grip | | | | | | | | | • | | • | | • | | | |



Iridium™

Paper Abrasive


24 Series











Technical Specifications

| | <u> </u> |
|------------|--------------------------|
| Grain | Ceramic / Aluminum oxide |
| Bonding | Low VOC resin system |
| Backing | Latex C-paper |
| Coating | Semi-open |
| Color | Gray |
| Attachment | Grip and PSA |

- Fast sanding and consistent scratch pattern saves you time and money
- Consistent quality and non-stick coating repels dust and provides a long disc life
- Effective multihole pattern delivers outstanding performance without clogging
- Premium paper backing offers remarkable flexibility and grain adhesion

| I | ridium [™] | Paper Abrasive | | | | | | | | | | | | | | | | | |
|----|---------------------|----------------|---------------|--------------------------|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| | | Part Number: | Size: | Description: | 40 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 320 | 400 | 500 | 600 | 800 | 1000 |
| | | 24-101-XXX | 9" x 11" | No-Hole, Plain | | | • | | • | | • | | • | • | | | | | |
| | 56 | 24-314-XXX | 5" | PSA, Linkroll | | | • | | • | • | • | • | | • | • | | • | • | • |
| | 56 | 24-342-XXX | 6" | PSA, Linkroll | | | • | | • | • | • | • | • | • | • | | • | • | • |
| | | 24-35M-XXX | 3" x 5" | 54-Hole, Grip | | • | • | | • | • | • | | • | • | • | | | | |
| | ((0))((0)) | 24-38P-XXX | 2¾" x 16" | 140-Hole, Perf, Grip | | • | • | | • | • | • | | • | • | • | | | | |
| | | 24-3MH-XXX | 3" | Multi-Hole, Grip | | | • | | • | • | • | • | • | • | • | • | • | | |
| * | 0_ | 24-570-XXX | 2¾" x 33½' | 20-Hole, Grip, Perf Roll | | | • | | • | • | • | • | • | • | • | | • | | |
| | 0 | 24-573-XXX | 4½" x 10 yds. | PSA, Roll | | | • | | • | • | • | • | | • | • | | | | |
| | 0_ | 24-574-XXX | 2¾" x 20 yds. | PSA, Roll | | | • | | | | | | | | | | | | |
| | 0 | 24-584-XXX | 2¾" x 40 yds. | PSA, Roll | | | | | • | • | • | • | • | • | • | | | | |
| | | 24-5MH-XXX | 5" | Multi-Hole, Grip | • | • | • | | • | • | • | • | • | • | • | • | • | • | • |
| ** | | 24-5MH-XXXRP | 5" | Multi-Hole, Grip | | | • | | • | | • | | • | • | | | | | |
| | | 24-5NH-XXX | 5" | No-Hole, Grip | • | • | • | • | • | • | • | • | • | • | • | | • | • | • |
| | | 24-620-XXX | 4" x 6" x 6" | 7-Hole, Grip | | | • | | • | | • | | • | | | | | | |
| | | 24-641-XXX | 3" x 4" | 36- Hole, Grip | | | • | • | • | • | • | • | • | • | • | | | | |
| | | 24-6MH-XXX | 6" | Multi-Hole, Grip | • | • | • | | • | • | • | • | • | • | • | • | • | • | • |
| | | 24-6NH-XXX | 6" | No-Hole, Grip | • | • | • | | • | • | • | • | • | • | • | • | • | • | • |
| | | 24-8MH-XXX | 8" | Multi-Hole, Grip | • | | • | | • | • | • | • | • | • | • | • | • | • | |
| | | 24-680-XXX | 9" | 24-Hole, Grip | • | • | • | • | • | • | • | • | • | • | | | | | |
| | | 24-9CU-XXX | 9" | 9H, Grip, 25/Pkg | • | • | • | | | | | | | | | | | | |

^{*} Perforated every 2¾" ** XXXRP = Smaller packages designed for retail sales

Iridium[™] **SR** Film Abrasive

24 Series 🔓















3 micron

PSA

5 micron 7 micron

| lec | lechnical Specifications | | | | | | |
|---------|--------------------------|--|--|--|--|--|--|
| Grain | Silicon Carbide | | | | | | |
| Bonding | Slurry | | | | | | |
| Backing | Film, 3 mil | | | | | | |
| Coating | Closed | | | | | | |
| Color | Green, Gray, Purple | | | | | | |

FEATURES AND BENEFITS:

Attachment

- Perfect size for denibbing
- Keeps repair as small as possible
- Efficient defect removal
- First step in undetectable repairs
- Smooth film backing
- Ideal for OEM fine finishing
- Easy peel-and-stick attachment
- Consistent on topcoat as well as composites



Iridium[™] SR Film Abrasive

| | Part Number: | Size: | Description: | 3μ | 5μ | 7μ |
|---|--------------|-------|--------------|----|----|----|
| • | 24-220-XXX | .87" | PSA | • | • | • |
| | 24-301-XXX | 11/4" | PSA rosette | • | • | • |
| | 24-309-XXX | 11/4" | PSA | | • | • |
| | 24-340-XXX | 11/4" | PSA | • | • | • |
| * | 24-689-5U | 11⁄4" | Grip rosette | | • | |
| | | | | | | |



For a Flawless Spot Repair

MUS-AUTKIT – This professional spot repair kit is designed to achieve a flawless final finish in auto manufacturing and refinishing. Enjoy the convenience of cordless tools plus premium abrasives and polishing compounds—everything you need in a deluxe wide-mouth carry bag. Transform spot repair into a seamless process with this all-in-one kit!

- Cordless Sander
- Iridium[™] SR Abrasive
- Polishing Pads
- Microfiber Cloths
- Cordless Polisher
- Polishing Compound
- Damper Bottles
- Deluxe Carry Bag

Jepuflex Antistatic

Paper Abrasive

44 Series









Technical Specifications

| Grain | Aluminum/Silicon carbide |
|------------|----------------------------|
| Bonding | Resin over resin |
| Backing | Antistatic T-paper/F-paper |
| Coating | Closed |
| Color | Maroon |
| Attachment | Grip |

FEATURES AND BENEFITS:

- Strong, reliable, antistatic paper
- Full resin bonding and aluminum oxide grain guarantee durability
- Silicon carbide grain used in the coarsest grit
- Perfect for sanding of hard wood such as beech, birch, and oak
- Multi-purpose works well on metal, plastic, and top coat

Microstar[®]

Film Abrasive

FM Series









Technical Specifications

| | Teermean Speemean on S | | | | | | | | |
|------------|------------------------|--|--|--|--|--|--|--|--|
| Grain | Aluminum oxide | | | | | | | | |
| Bonding | Low VOC resin system | | | | | | | | |
| Backing | Polyester film | | | | | | | | |
| Coating | Semi-open | | | | | | | | |
| Color | White | | | | | | | | |
| Attachment | Grip | | | | | | | | |

FEATURES AND BENEFITS:

- Ideal for removal of runs, dust nibs and excess orange peel from topcoat finishes before repainting or buffing
- Resists loading for longer disc life
- Ideal for sanding fresh or soft clearcoat
- Leaves an even scratch pattern, which buffs out quickly on all types of automotive paints
- Film-backed discs have full resin bonded aluminum oxide grain

| Jepuflex Antistatic | Paper Abrasive | P |
|---------------------|----------------|---|
| | | |

| | Part Number: | Size: | Description: | 40 | 50 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 320 | 360 | 400 | 500 |
|---|--------------|----------|--------------|----|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 0 | 44-325-XXX | 3" x 75' | Grip | • | | • | • | • | • | • | • | • | | | | | |
| 0 | 44-625-XXX | 6" x 75' | Grip | • | | • | • | • | • | • | • | • | | | | | |

| Microstar® | Film Abrasive | P |
|------------|---------------|---|
| | | |

| Part Number: | Size: | Description: | 220 | 240 | 320 | 400 | 500 | 600 | 800 | 1000 | 1200 | 1500 | 2000 | 2500 |
|--------------|-------|--------------|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|
| FM-608-XXX | 3" | Grip | | | | | | | • | • | • | • | • | |
| FM-612-XXX | 5" | Grip | | | | | | | • | • | • | • | • | • |
| FM-622-XXX | 6" | Grip | | | | | | | • | • | • | • | • | • |
| FM-611-XXX | 6" | 15-Hole Grip | | | | | | | • | • | • | • | • | • |

DID YOU KNOW?

Microstar abrasives are effective in both wet and dry sanding. For best results when sanding clearcoat and topcoat finishes, it is best to use an interface pad to prevent cutting through on the edges.

For a longer life, wipe the Microstar disc with a microfiber cloth after making a few sanding passes.



Mirlon[®] Non-Woven Abrasive

18 Series











Technical Specifications

| | • |
|---------|--|
| Grain | Aluminum oxide (VF), Silicon carbide (UF) |
| Bonding | Resin |
| Backing | Non-Woven |
| Coating | Three dimensional |
| Color | Maroon (VF), Gray (UF) |

FEATURES AND BENEFITS:

- Three-dimensional structure made with cut fiber strands coated with resin and abrasive
- Consistent coating of aluminum oxide (VF) and silicon carbide (UF) abrasive grains provide more uniform scratch pattern
- Very flexible, ideal for use on contoured surfaces

Mirlon Total® Non-Woven Abrasive 18 Series

Technical Specifications

| Grain | Aluminum oxide (VF), Silicon carbide (XF, UF, MF) |
|---------|--|
| Bonding | Resin |
| Backing | Non-Woven |
| Coating | Three Dimensional Total Coating |
| Color | Red (VF), Black (XF), Gray (UF), Gold (MF) |

- Open design is thinner and more flexible than traditional non-woven pads
- Three-dimensional structure made with cut fiber strands coated with resin and abrasive
- Consistent coating of aluminum oxide (VF 360) and silicon carbide (XF 800, UF 1500, MF 2500) abrasive grains provide uniform, dense
- Very flexible, ideal for use on contoured surfaces

| | Mirlon° | Non-Woven Abrasive | P | | | | | | |
|---|---------|--------------------|---------------|----------|--------|-----|-----|------|------|
| | | Part Number: | Size: | Coating: | Color: | 360 | 800 | 1500 | 2500 |
| | | 18-241-447 | 6" | VF | Maroon | • | | | |
| | | 18-241-448 | 6" | UF | Gray | | | • | |
| | | 18-111-447 | 6" x 9" | VF | Maroon | • | | | |
| * | | 18-111-447RP | 6" x 9" | VF | Maroon | • | | | |
| | | 18-111-448 | 6" x 9" | UF | Gray | | | • | |
| * | | 18-111-448RP | 6" x 9" | UF | Gray | | | • | |
| | 0_ | 18-573-447 | 4½" x 11 yds. | VF | Maroon | • | | | |
| | 0_ | 18-573-448 | 4½" x 11 yds. | UF | Gray | | | • | |

| Mirlon T | Total Non-Woven | Abrasive P | | | | | | |
|----------|------------------------|-------------------|--|--------|-----|-----|------|------|
| | Part Number: | Size: | Coating: | Color: | 360 | 800 | 1500 | 2500 |
| | 18-118-446 | 4½" x 9" | XF | Black | | • | | |
| | 18-118-447 | 4½" x 9" | VF | Red | • | | | |
| * | 18-118-447RP | 4½" x 9" | VF | Red | • | | | |
| | 18-118-448 | 4½" x 9" | UF | Gray | | | • | |
| * | 18-118-448RP | 4½" x 9" | UF | Gray | | | • | |
| | 18-118-449 | 4½" x 9" | SF/MF | Gold | | | | • |
| * | 18-118-449RP | 4½" x 9" | SF/MF | Gold | | | | • |
| * | 18-118-APRP | 4½" x 9" | VF/Red, UF/Gray, SF/Gold, 3 sheets, 1 ea | | • | | • | • |
| | 18-241-XXX | 6" | VF (360) Red, XF (800) Black | | • | • | | |
| 0_ | 18-573-373 | 4½" x 11 yds. | VF | Red | • | | | |
| 0 | 18-573-943 | 4½" x 11 yds. | UF | Gray | | | • | |

^{*} XXXRP = Smaller packages designed for retail sales



Ultimax° Ligno

Paper Abrasive

UL Series 🗀





Technical Specifications

| Grain | Ceramic/Aluminum oxide |
|------------|-----------------------------------|
| Bonding | Low VOC resin system |
| Backing | Latex paper, D-paper/C-paper |
| Coating | Semi-open with Selective Coating® |
| Color | Red |
| Attachment | Grip, PSA, Plain |

FEATURES AND BENEFITS:

- An all-new abrasive for dust-free woodworking
- Unique hourglass shape increases sanding effectiveness and dust extraction
- Multifit universal hole patterns work with any tool and grip backing pad
- Dust-free sanding keeps the abrasive grain clean and cutting at all times
- Better air flow reduces heat during sanding
- Sustainable, energy-saving production process

Multifit Multifit hole pattern available in 5" and 6" discs, $3" \times 4"$ and $3" \times 5"$ sheets. **Ultimax® Ligno** Paper Abrasive

| | Part Number: | Size: | Description: | 40 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 320 | 400 | 500 | 600 | 800 | 1000 |
|----|--------------|-----------|------------------------|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| | UL-332-XXX | 5" | PSA | • | • | • | • | • | • | • | • | • | • | • | | | | |
| | UL-341-XXX | 6" | PSA | • | • | • | • | • | • | • | • | • | • | • | | | | |
| | UL-5MF-XXX | 5" | Multifit, Grip | • | • | • | • | • | • | • | • | • | • | • | | | | |
| | UL-6MF-XXX | 6" | Multifit, Grip | • | • | • | • | • | • | • | • | • | • | • | | | | |
| | UL-6B8-XXX | 3" x 4" | Multifit, Grip | • | • | • | • | • | • | • | • | • | • | • | | | | |
| | UL-6BK-XXX | 3" x 5" | Multifit, Grip | • | • | • | • | • | • | • | • | • | • | • | | | | |
| 0_ | UL-127-XXX | 4.5" x 5" | Perf-Soft, Roll, Plain | | | | | | • | • | • | • | • | • | | | | |

DID YOU KNOW?

Ultimax® Ligno – Selected out of 64 different designs, the hourglass pattern proved to perform the best. Each segment has four sharp corners and two angled surfaces for optimal cutting performance. The segmented surface increases WOODWORKING MASTERPIECE sanding pressure on each abrasive grain and creates channels for dust to flow away from the work.





Basecut

Paper Abrasive

20 Series









| Technical Specifications | | | | | | | | |
|---|------------------|--|--|--|--|--|--|--|
| Grain | Aluminum oxide | | | | | | | |
| Bonding | Resin over resin | | | | | | | |
| Backing P40-P80 D-paper, P100-P800 C-paper | | | | | | | | |
| Coating | Semi-open | | | | | | | |
| Color White | | | | | | | | |
| Attachment Grip, PSA and Plain | | | | | | | | |

FEATURES AND BENEFITS:

- Economical and efficient
- Dependable over a long lifespan
- Useful for a variety of applications
- High initial aggressive cut

Caratflex

Paper Abrasive

02 Series





| recnnical Specifications | | | | | | | |
|--------------------------|-------------------------------------|--|--|--|--|--|--|
| Grain | Silicon carbide | | | | | | |
| Bonding | Resin over resin, Progressive Bond® | | | | | | |
| Backing | P80 - P320 B-paper, P400 A-paper | | | | | | |
| Coating | Semi-open | | | | | | |
| Color | Gray | | | | | | |
| Attachment | Grip, PSA and Plain | | | | | | |
| | | | | | | | |

- Designed for hand sanding of wood, sealers, paint and lacquers
- The latex impregnated paper backing is highly flexible and ideal for profile sanding
- An advanced stearate coating is used to resist loading
- Resin bonding improves grain adherence and product life
- Silicon carbide grain delivers an exceptionally sharp, smooth cut

| Basecut | Paper Abrasive | P | | | | | | | | | | | | | | | | |
|---------|----------------|------------|-------------------------|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| | Part Number: | Size: | Description: | 40 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 320 | 360 | 400 | 500 | 600 | 800 |
| | 20-101-XXX | 9" x 11" | No-Hole, Plain | • | • | • | • | • | • | • | • | | • | | • | | | |
| 56 | 20-314-XXX | 5" | No-Hole, PSA, Linkroll | | | • | • | • | • | • | • | • | • | | • | • | | |
| | 20-332-XXX | 5" | No-Hole, PSA with Liner | | | | | | | | | | | | | | • | |
| | 20-341-XXX | 6" | No-Hole, PSA with Liner | • | | | | | | | | | | | | | | |
| 56 | 20-342-XXX | 6" | No-Hole, PSA, Linkroll | | | • | • | • | • | • | • | | • | | • | • | | |
| | 20-364-XXX | 2¾" x 16½" | No-Hole, PSA | • | | • | | | | | | | | | | | | |
| | 20-352-XXX | 8" | No-Hole, PSA with Liner | • | | • | | | | | | | | | | | | |
| 0_ | 20-573-XXX | 4½" x 30' | No-Hole, PSA | | | | • | • | | | • | | | | | | | |
| 0 | 20-580-XXX | 2¾" x 75' | No-Hole, PSA | | | • | | • | • | • | • | | • | | • | | | |
| | 20-612-XXX | 5" | No-Hole, Grip | | | • | • | • | • | • | • | | • | | • | • | • | • |
| | 20-622-XXX | 6" | No-Hole, Grip | • | | • | • | • | • | • | • | | • | | • | • | • | • |

| Carat | flex Paper Abra | asive P | | | | | | | | | | | | | | | | | | |
|-------|------------------------|-----------|---------------|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|-----|--------|
| | Part Number: | Size: | Description: | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 280 | 320 | 360 | 400 | 500 | 600 | 800 | 1000 | 120 | 0 1500 |
| | 02-101-XXX | 9" x 11" | Plain | • | • | • | • | • | • | • | | • | | • | | | | | | |
| | 02-124-XXX | 4½" x 11" | Plain | | | | | • | | | | | | | | | | | | |
| 5 | 02-314-XXX | 5" | PSA, Linkroll | | | • | • | • | • | | | • | | | | | | | | |
| | 02-612-XXX | 5" | Grip | | | | | • | • | | | • | | | | | | | | |

Coarse Cut Paper Abrasive

40 Series



Technical Specifications

| Grain | Aluminum oxide |
|------------|-------------------------------------|
| Bonding | Resin over resin, Progressive Bond® |
| Backing | Specially reinforced F-paper |
| Coating | Semi-open |
| Color | Maroon |
| Attachment | Grip and PSA |

FEATURES AND BENEFITS:

- Coarse grades are aggressive and fast cutting as well as long lasting
- Specially reinforced paper exclusive to Mirka provides superior grain support
- Semi-open coat produces a consistent scratch pattern, while resisting loading

Hiolit® XO / JCA2A0

Paper Abrasive

XO (51) / JCA2A0 (5B)









Technical Specifications

| Grain | Aluminum oxide |
|------------|---|
| Bonding | Resin over resin |
| Backing | Polyester cloth (51 Series) J-weight cotton cloth (5B Series) |
| Coating | Closed |
| Color | Maroon |
| Attachment | PSA |

FEATURES AND BENEFITS:

- JCA2A0 option is highly adaptable to contoured surfaces
- Removes stock quickly, while producing a high-quality surface finish
- The durable aluminum oxide grain delivers an exceptionally long lasting cut

Coarse Cut Paper Abrasive

| | Part Number: | Size: | Description: | 36 | 40 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 280 | 320 | 400 | 500 | 600 | 800 |
|---|--------------|------------|--------------|----|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| • | 40-608-XXX | 3" | Grip | | • | | | | | | | | | | | | | | |
| | 40-612-XXX | 5" | Grip | • | • | • | • | • | • | | | | | | | | | | |
| | 40-332-XXX | 5" | PSA | • | • | • | • | • | • | | | | | | | | | | |
| | 40-614-XXX | 5" | 5-Hole, Grip | | • | • | • | | • | • | | | | | | | | | |
| | 40-622-XXX | 6" | Grip | • | • | • | • | | | | | | | | | | | | |
| | 40-341-XXX | 6" | PSA | • | • | • | • | | • | | | | | | | | | | |
| | 40-624-XXX | 6" | 6-Hole, Grip | • | • | • | • | | | | | | | | | | | | |
| | 40-631-XXX | 8" | Grip | • | • | • | • | • | | | | | | | | | | | |
| | 40-352-XXX | 8" | PSA | • | • | • | • | • | • | • | | | | | | | | | |
| | 40-632-XXX | 8" | 9-Hole, Grip | | • | | • | | | • | | | | | | | | | |
| | 40-663-XXX | 2¾" x 16½" | Grip | • | • | | • | | | | | | | | | | | | |
| | 40-364-XXX | 2¾" x 16½" | PSA | • | • | • | • | • | | • | | | | | | | | | |

| Hiolit® XO | /JCA2A0 | Paper Abrasive | F |
|------------|---------|----------------|---|
| | | | |

| | Part Number: | Size: | Description: | 40 | 50 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 320 | 360 | 400 | 500 |
|---|--------------|-------|--------------|----|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| • | 51-332-XXX | 5" | PSA | • | | | | | | | | | | | | | |
| 6 | 5B-332-XXX | 5" | PSA | | | • | • | • | • | • | • | • | | | | | |

Polarstar[®] SR

Film Abrasive

3 micron (eqv. to P5000) 5 micron (eqv. to P3000) 7 micron (eqv. to P2500)

SR Series 😂







| Technical Specifications | | | | | | | |
|---------------------------------|--|--|--|--|--|--|--|
| Grain | Aluminum oxide | | | | | | |
| Bonding | Resin over resin | | | | | | |
| Backing | Polyester film | | | | | | |
| Coating | Defined mono-layer coating technology | | | | | | |
| Color | Pale yellow (3A), Mint green (5A), Lilac (7A) | | | | | | |
| Attachment | Water-resistant PSA | | | | | | |

FEATURES AND BENEFITS:

- Designed for spot repair of clearcoats
- Ideal for nib sanding to remove dirt or imperfections
- Excellent durability
- Suitable for wet sanding



Blue

Grip and PSA

Paper Abrasive

FEATURES AND BENEFITS:

Color

Attachment

Q.Silver[®]

- Outstanding performance in automotive, hard wood, and composites
- Flexible, strong, latex paper backing
- High heat endurance
- Tight grain distribution provides a more consistent scratch pattern
- Extra hard grain material

Polarstar[®] SR Film Abrasive

| | Part Number: | Packaging: | Size: | Description: | 240 | 320 | 400 | 500 | 600 | 800 | 1000 | 1200 | 1500 | 3μ | 5μ | 7μ |
|---|--------------|------------|-------|--------------|-----|-----|-----|-----|-----|-----|------|------|------|----|----|----|
| * | SR-301-XXX | 100/box | 11⁄4" | PSA | | | | | | | | | | | • | • |
| * | SR-340-XXX | 500/box | 11⁄4" | PSA | | | | | | | | | | | • | • |

| Q.Silver [°] | Paper Abrasive | P | | | | | | | | | | | | | | | | |
|-----------------------|----------------|---------------|---------------|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|
| | Part Number: | Size: | Description: | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 320 | 400 | 500 | 600 | 800 | 1000 | 1200 | 1500 |
| | 2A-332-XXX | 5" | PSA | | | 1 | | | | • | • | | | | | | | |
| | 2B-608-XXX | 3" | Grip | • | | | | • | | | | | | | | | | |
| | 2B-612-XXX | 5" | Grip | • | | • | • | • | • | • | • | • | • | | | | | |
| | 2B-332-XXX | 5" | PSA | • | • | • | • | • | • | • | • | • | • | | | | | |
| | 2B-614-XXX | 5" | 5-Hole, Grip | • | • | • | • | • | • | | • | • | | | | | | |
| | 2B-342-XXX | 6" | Linkroll, PSA | • | | • | • | • | • | • | • | • | | | | | | |
| | 2B-622-XXX | 6" | Grip | • | | • | • | • | • | • | • | • | • | | | | | |
| | 2B-611-XXX | 6" | 15-Hole, Grip | • | • | • | • | • | • | • | • | • | • | | | | | |
| | 2B-663-XXX | 2¾" x 16½" | Grip | • | | | | • | • | | | | | | | | | |
| 0 | 2B-574-XXX | 2¾" x 20 yds. | PSA | • | | | | | | | | | | | | | | |
| 0 | 2B-584-XXX | 2¾" x 40 yds. | PSA | | | • | • | • | • | | • | • | | | | | | |
| | 2C-608-XXX | 3" | Grip | | | | | | | | | | | • | • | • | • | • |
| | 2C-332-XXX | 5" | PSA | | | | | | | | | | | • | | | | |
| | 2C-612-XXX | 5" | Grip | | | | | | | | | | | • | • | • | • | • |
| | 2C-341-XXX | 6" | PSA | | | | | | | | | | | • | • | | | |
| • | 2C-611-XXX | 6" | 15-Hole, Grip | | | | | | | | | | | • | • | • | • | • |
| | 2C-622-XXX | 6" | Grip | | | | | | | | | | | • | • | • | • | • |

^{* 2}C-611-XXX are not P-Graded

Sanding Sponges

Foam Abrasive

1351 Series 😂 😂 🛗 🔔 😂











FEATURES AND BENEFITS:

- Fine silicon carbide grit
- Versatile, flexible sanding sponge
- Use wet or dry, wash and reuse

| Techni | cal Specifications |
|------------------|---------------------------|
| Grain | Silicon carbide |
| Bonding | Syntheic adhesive |
| Backing | Colored polyurethane foam |
| Density | 24 kgm ⁻³ |
| Tear Strength | 125 Nm ⁻¹ |
| Tensile Strength | 87 kPa |

| Part Number: | Packaging: | Size: | Color: | Description: | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 280 | 320 | 400 | 600 |
|--------------|------------|---------------------|--------|--------------|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 1351-XXX | 10/Box | 4.75" x 3.75" x .5" | Black | 2-sided | | | • | • | • | • | • | | | | |
| 1351-XXXB | 100/Box | 4.75" x 3.75" x .5" | Black | 2-sided | | | • | | • | • | • | | | | |

1353 Series 😂 😭 🕮











- Hard foam core keeps its shape
- Four surfaces coated with grains
- Suitable for sanding 90-degree angles
- Waterproof



| Techni | Technical Specifications | | | | | | | | |
|------------------|---------------------------|--|--|--|--|--|--|--|--|
| Grain | Aluminum oxide | | | | | | | | |
| Bonding | Synthetic adhesive | | | | | | | | |
| Backing | Colored polyurethane foam | | | | | | | | |
| Density | 24 kgm ⁻³ | | | | | | | | |
| Tear Strength | 125 Nm ⁻¹ | | | | | | | | |
| Tensile Strength | 87 kPa | | | | | | | | |

| Part Number: | Packaging: | Size: | Color: | Description: | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 280 | 320 | 400 | 600 |
|--------------|------------|-----------------|--------|--------------|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 1353-XXX | 10/Box | 4" x 2.75" x 1" | Brown | 4-sided | • | | • | | • | • | • | | | | |
| 1353-XXXB | 100/Box | 4" x 2.75" x 1" | Brown | 4-sided | | | • | | • | • | • | | | | |

Sanding Sponges

Foam Abrasive



1355 Series 😂 😂 🛗 🔔 😂











P

FEATURES AND BENEFITS:

- Use for wood, paint, metal, fiberglass, coatings, and composites
- Fine grits for profiled and rounded surfaces
- Both dry and wet sanding
- Wash and reuse



| Techni | cai specifications |
|------------------|---------------------------|
| Grain | Aluminum oxide |
| Bonding | Syntheic adhesive |
| Backing | Colored polyurethane foam |
| Density | 24 kgm ⁻³ |
| Tear Strength | 125 Nm ⁻¹ |
| Tensile Strength | 87 kPa |

| Part N | lumber: | Packaging: | Size: | Color: | Description: | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 280 | 320 | 400 | 600 |
|--------|---------|------------|----------------------|--------|--------------|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 135 | 5-XXX | 20/Box | 4.5" x 5.5" x .1875" | White | 1-sided | • | | • | | • | • | • | | • | • | |
| 1355 | S-XXXB | 250/Box | 4.5" x 5.5" x .1875" | White | 1-sided | • | | • | • | • | • | • | | • | | |

1356 Series 😂 😂 🔠 🔔 😂











- Soft, flexible, low-density foam
- Two sides coated with fine-grit abrasive
- Long lasting performance
- Color-coded by grit



| rechni | cai specifications |
|------------------|---------------------------|
| Grain | Aluminum oxide |
| Bonding | Synthetic adhesive |
| Backing | Colored polyurethane foam |
| Density | 24 kgm ⁻³ |
| Tear Strength | 125 Nm ⁻¹ |
| Tensile Strength | 87 kPa |

| Part Number: | Packaging: | Size: | Description: | 100 Purple | 150 Blue | 180 Red | 220 Green | 280 Clear | 320 Brown |
|--------------|------------|---------------|--------------|---------------|-------------|------------|--------------|--------------|--------------|
| 1356-XXXB | 250/Box | 4" × 5" × .5" | 2-sided | • | • | • | • | • | • |

Sanding Sponges


Foam Abrasive





Technical Specifications

| | <u> </u> |
|------------------|---------------------------|
| Grain | Aluminum oxide |
| Backing | Colored polyurethane foam |
| Density | 24 kgm ⁻³ |
| Tear Strength | 125 Nm ⁻¹ |
| Tensile Strength | 87 kPa |
| Attachment | Grip |



MGS345 Series 100 150 180 220 280 320

Technical Specifications

| Grain | Aluminum oxide |
|------------------|---------------------------|
| Backing | Colored polyurethane foam |
| Density | 85 kgm ⁻³ |
| Tear Strength | 370 Nm ⁻¹ |
| Tensile Strength | 290 kPa |
| Attachment | Grip |

FEATURES AND BENEFITS:

- For use with power tools
- Color coded by grit
- Suitable for jobs from stock removal to polishing
- Ideal for profiles, edges, and small corrections
- Use wet or dry, wash and reuse

| Part Number: | Packaging: | Size: | Description: | 36 Clear | 60 Clear | 80 Clear | 100 Purple | 150 Blue | 180 Red | 220 Green | 280 Clear | 320 Brown |
|--------------|------------|---------------|-----------------------------|-------------|-------------|-------------|---------------|-------------|------------|--------------|--------------|--------------|
| MGS34-XXXB | 100/Box | 3" x 4" x .5" | 1-Sided, Grip, Low Density | | • | • | • | • | • | • | • | • |
| MGS3410-XXXB | 100/Box | 3" x 4" x .4" | 1-Sided, Grip, High Density | • | • | • | • | • | • | • | • | • |
| MGS345-XXXB | 100/Box | 3" x 4" x .2" | 1-Sided, Grip, High Density | • | • | • | • | • | • | • | • | • |

Grits lower than 100 are the same color as 280 grit

DID YOU KNOW?

Let the sander do the work with MGS34 Series 3"x 4" sponges that fit on a 3x4 orbital sander with grip attachment. These versatile sponges can be used by hand or machine to upgrade results anywhere hand sanding had previously been needed.



Styro System

Paper Abrasive








FEATURES AND BENEFITS:

- Great for smoothing out textured walls, ceilings and foam panels
- Drastically reduce setup and cleanup time
- Large holes on pads and abrasives improve dust extraction capacity
- 9" diameter random orbital sander works quickly over large areas
- Iridium's non-stick coating resists clogs for long disc life
- Light, ergonomic LEROS is available in two lengths: 57" and 35"



| Part Number: | Product Name: | 40 | 60 | 80 |
|--------------|---|----|----|----|
| MIW9564411 | Backing Pad 9" Grip Styro for Mirka LEROS | | | |
| MIW9535611 | Interface 9" Styro for Mirka LEROS | | | |
| 24-9CU-XXX | IRIDIUM 9" Grip 9H Styro, 25/Pkg | • | • | • |

Recommended Power Tools


| MIW95020BAUS | LEROS 950XCV 9"/5mm Wall Sander w/Bag, 57" length |
|--------------|---|
| MIW95021BAUS | LEROS-S 950XCV 9"/5mm Wall Sander w/Bag, 35" length |
| DE-1230-AFC | Mirka Dust Extractor 1230 HEPA AFC 120V |





DID YOU KNOW?

"Best dust extraction I've ever seen—there's no Styrofoam on the floor." This comment came from a customer who used the Styro System to smooth out a 'popcorn' textured ceiling. The large holes on the pads and abrasives allow the Mirka® Dust Extractor to overcome static cling and make quick work of interior and exterior sanding.



WPF Pro

Paper Abrasive

21 Series











Technical Specifications

| Grain | Silicon carbide |
|------------|----------------------|
| Bonding | Resin over resin |
| Backing | C-weight latex paper |
| Coating | Closed |
| Color | Black |
| Attachment | Plain |

FEATURES AND BENEFITS:

- C-weight latex paper for excellent flexibility
- Highly polishable scratch pattern for a fine surface finish
- Suited for paint removal, putty and wood sanding, plus primer and topcoat sanding


WPF Pro Paper Abrasive


> Part Number: Size: Attach: 60 80 100 120 150 180 220 240 280 320 360 400 500 600 800 1000 1200 1500 2000 2500 3000 **21-101-PXXX** 9" x 11" Plain

21-140-PXXX 5½" x 9" Plain

DID YOU KNOW?

For an especially smooth sanding pattern, use the highly flexible WPF Pro with a sanding block to apply even pressure and keep the abrasive flush to the surface. We recommend the Mirka 121-002 Dual-Density Hand Sanding Block. Soft on one side and firm on the other, they can be used wet or dry and can be easily cut to customize their size and shape.







Golden Finish Sanding System



Golden Finish 😂

The Mirka Golden Finish kit is a quick and easy solution for perfecting

It features number and color coded products for an efficient polishing process, suitable for both light and dark surfaces.

FEATURES AND BENEFITS:

- Complete Post-Paint Finishing System
- Improved consistency and less re-work
- Less time required for the repair area
- Systematic approach with numeric codes
- Two step sanding system / Two step polishing system
- Standardized post-paint / polishing process
- Ideal for both small and large repairs
- Grip attachment

| Part Number: | Description: | Process Steps: | | | | |
|----------------------|--------------------------------------|--|--|--|--|--|
| OS-241-GF1 | 6" Grip (Film) | Step 1: Sanding/Leveling surfaces | | | | |
| OS-241-GF2 | 6" Grip (Foam) | Step 2: Sanding/Conditioning scratches | | | | |
| PC20-1L MPADLWY-6 | Polarshine® 20 6" Lambswool Pad | Step 1: Polishing | | | | |
| FC5-1L MPADBF-6W | Polarshine® VF5 6" Black Foam Pad | Step 2: Polishing | | | | |
| M-9915G | Microfiber Cloth | Finish/Clean surface | | | | |

STEP 1



OS-241-GF1 Golden Finish Step 1

6" Grip Film



PC20-1L Polarshine® 20



MPADLWY-6

6" Lambswool Pad



OS-241-GF2

Golden Finish Step 2 6" Grip Foam





FC5-1L

Polarshine® VF5



MPADBF-6W

6" Black Foam Pad



M-9915G Microfiber Cloth

TECH TIP ____

The Golden Finish Process - your best friend when it comes to small and medium size post-paint refinishing, removing nibs, drips and orange peel from the car's surface.







Optimized Surface Preparation System





Mirka's groundbreaking 'Optimized Surface Preparation' system maximizes performance at every stage of the vehicle repair process. Gathering the best ideas from Mirka's years of experience, we streamlined and perfected the entire process to bring you the optimal system.

Surface preparation has never been so simple, fast, and cost effective, with a premium quality result that is repeatable, time and time again!

FEATURES AND BENEFITS:

- Complete system for auto body repair applications
- Easy for all operators to use
- Combines three industry SOPs in one process
- Improved consistency and less re-work
- Simple to standardize process across all facilities
- Less time required for the repair
- Improved shop environment
- Less technician exposure to dust
- Reduced labor cost of clean-up and maintenance
- Rolls are perforated every 2¾"



| Te | Technical Specifications | | | | | | |
|----------------------|--------------------------|--|--|--|--|--|--|
| Grain Blended | | | | | | | |
| Bonding | Resin | | | | | | |
| Backing | Polyamide Net | | | | | | |
| Coating | Closed | | | | | | |
| Color | Brown, Gray, Yellow | | | | | | |
| Attachment | Grip | | | | | | |

| | | Part Number: | Description: | Process Steps: | | | | | |
|--------------|-----|--------------|-------------------------------|--------------------------------------|--|--|--|--|--|
| | | OS-203-001 | 3" Grip | | | | | | |
| _ | | OS-241-001 | 6" Grip | Daint name of book filling and disco | | | | | |
| OSP | | OS-150-001 | 2¾" x 7¾", Grip | Paint removal, body filler sanding | | | | | |
| | * 🔔 | OS-570-001 | 2¾" x 11 yds. Grip, Perf Roll | | | | | | |
| | • | OS-203-002 | 3" Grip | | | | | | |
| 2 | | OS-241-002 | 6" Grip | Dody fillor/along conding | | | | | |
| OSP | | OS-150-002 | 2¾" x 7¾", Grip | Body filler/glaze sanding | | | | | |
| | * 🔔 | OS-570-002 | 2¾" x 11 yds. Grip, Perf Roll | | | | | | |
| | • | OS-203-003 | 3" Grip | | | | | | |
| M | | OS-241-003 | 6" Grip | Divine | | | | | |
| OSP | | OS-150-003 | 2¾" x 7¾", Grip | Primer prep | | | | | |
| | * 🔔 | OS-570-003 | 2¾" x 11 yds. Grip, Perf Roll | | | | | | |
| 4 | | OS-127-004 | 4½" x 5", Plain | | | | | | |
| OSP 4 | | OS-241-004 | 6" Grip | Drimor finishing | | | | | |
| 0 | • | OS-734-004 | 3" 6-Hole, Grip | Primer finishing | | | | | |
| | | OS-711-004 | 6" 15-Hole, Grip | | | | | | |

^{*} Perforated every 23/4"

Use OSP with Mirka® Dry Guide Coat to Ensure the Perfect Finish!




9193500111 (Black)



9193600111 (White)

Dry Guide Coat is a great tool to guide the operator through the sanding process and to achieve a perfect result.

With its excellent covering properties, the powder makes all imperfections and scratches visible. The unique applicator leaves an even powder coating, and its flexible edges make it easy to use even on contoured areas.



Abranet® Max











| Technical : | Specifications |
|--------------------|----------------|
|--------------------|----------------|

| Grain | Aluminum Oxide |
|---------|------------------|
| Bonding | Resin over Resin |
| Backing | Net |
| Coating | Closed |
| Color | Brown |
| Joint | T (Standard) |

FEATURES AND BENEFITS:

- Tough aluminum oxide grain gives a high cut rate on harder wood types and materials
- Extremely long lifetime compared to conventional abrasive belts
- The symmetric net structure enables an efficient cut and stock removal
- Resists clogging on resinous wood types or soft materials
- Keeps sanded surface cooler to avoid burning
- Lower pressure required when sanding due to its net structure

Hiolit® JCA2A0

5B Series







Technical Specifications

| Grain | Aluminum Oxide | | | | |
|---|------------------|--|--|--|--|
| Bonding | Resin over Resin | | | | |
| Backing Flexible J-weight cotton cloth | | | | | |
| Coating | Semi-Open | | | | |
| Color | Maroon | | | | |
| Joint | T,TT | | | | |
| | | | | | |

FEATURES AND BENEFITS:

- Flexible properties and high quality sanding results make it ideal for metal and wood workshops
- Durability and excellent edge wear resistance make it ideal for sanding profiles and seams
- Ideal for aggressive sanding where flexibility is needed

Abranet® Max P

| Part Number: | Size: | Type: | Custom Order? | 40 | 50 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 320 |
|----------------------|--|----------|----------------------|----|----|----|-----|-----|-----|-----|-----|-----|-----|
| AB-2.5-14-XXXT | 2.5 x 14" | Portable | _ | | | • | • | • | • | • | | | |
| AB-3-18-XXXT | 3 x 18" | Portable | _ | | | • | • | • | • | • | | | |
| AB-3-21-XXXT | 3 x 21" | Portable | _ | | | • | • | • | • | • | | | |
| AB-3-24-XXXT | 3 x 24" | Portable | _ | | | • | • | • | • | • | | | |
| AB-4-24-XXXT | 4 x 24" | Portable | _ | | | • | • | • | • | • | | | |
| AB-WIDTH-LENGTH-GRIT | W: 0.25" - 12" L: 6" - 400" | Narrow | Yes | | | • | • | • | • | • | • | • | |

Hiolit[®] JCA2A0



| W |) | Part Number: | Size: | Type: | Custom Order? | 40 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 320 |
|---|---|----------------------|---|-------------|----------------------|----|----|----|-----|-----|-----|-----|-----|-----|-----|
| _ | | 5B-WIDTH-LENGTH-GRIT | W: 0.25" - 11" L: 6" - 400" | Narrow | Yes | | | • | • | • | • | • | • | | |
| | | 5B-WIDTH-LENGTH-GRIT | W: 7", 8", 9" L: 10.5" - 26.3" | Pump Sleeve | Yes | | | • | • | • | • | • | • | | |



Hiolit[®] XO

57 Series









Technical Specifications

| Grain | Blue fired Aluminum Oxide |
|---------|--|
| Bonding | Resin over Resin |
| Backing | Polyester cloth: P36-P80 X-weight cotton cloth: P100-P220 |
| Coating | Semi-open |
| Color | Maroon |
| Joint | T, TS, TT |

FEATURES AND BENEFITS:

- Excellent wear resistance and durability
- Designed for sanding operations where large amounts of material need to be removed
- Suitable for aggressive sanding
- Produces high quality results on challenging materials

Hiolit® XO

| Part | Number: | Size: | Type: | Custom Order? | 36 | 40 | 50 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 |
|----------|--------------|--|----------|---------------|----|----|----|----|----|-----|-----|-----|-----|-----|-----|
| 57-2.5 | 5-14-XXXT | 2.5 x 14 | Portable | Yes | | | | • | • | • | • | | | | |
| 57-3 | -18-XXXT | 3 x 18 | Portable | Yes | | • | | | • | | | | | | |
| 57-3 | -21-XXXT | 3 x 21 | Portable | Yes | | • | • | • | • | • | • | • | | | |
| 57-3 | -24-XXXT | 3 x 24 | Portable | Yes | | • | • | • | • | • | • | • | | | |
| 57-4 | -24-XXXT | 4 x 24 | Portable | Yes | • | • | • | • | • | • | • | • | | | |
| 57-WIDTH | -LENGTH-GRIT | W: 0.25" - 12" L: 6" - 400" | Narrow | Yes | • | • | • | • | • | • | • | • | • | • | |
| 57-WIDTH | -LENGTH-GRIT | W: 13-56" L: 32" - 400" | Wide | Yes | • | • | • | • | • | • | • | • | • | • | |

DID YOU KNOW?

Mirka's belt abrasives are the perfect companion to your belt sanding machines. They stand up to your toughest production sanding applications. The large sanding area gets the job done fast whether it's hardwood, metal, or plastic.

- Standard and Custom Lengths
- Net, Cloth, and Paper
- Anti-Static Option



Jepuflex Antistatic











Technical Specifications

| Grain | Aluminum Oxide / Silicon carbide |
|---------|----------------------------------|
| Bonding | Resin over Resin |
| Backing | Antistatic T-Paper / F-Paper |
| Coating | Closed |
| Color | Maroon |
| Joint | A, T, TS, TT |

FEATURES AND BENEFITS:


- Strong, reliable, antistatic paper
- Full resin bonding and aluminum oxide grain guarantee durability
- Silicon carbide grain used in the coarsest grit
- Perfect for sanding of hard wood such as beech, birch, and oak
- Multi-purpose works well on metal, plastic, and lacquer

Ultimax® Belts

UC Series







| recillical Specifications | | | | | | | | |
|---------------------------|--------------------------------|--|--|--|--|--|--|--|
| Grain | Aluminum Oxide | | | | | | | |
| Bonding | Resin over Resin | | | | | | | |
| Backing | Antistatic T-paper/F-paper | | | | | | | |
| Coating | Closed with Selective Coating® | | | | | | | |
| Color | Brown | | | | | | | |
| Joint | B -Joint | | | | | | | |

FEATURES AND BENEFITS:

- Selective Coating® Technology prevents clogging
- Aggressive performance with cool sanding surface
- Long life and excellent edge wear resistance
- Reduced material usage per job

Jepuflex Antistatic



| Part Number: | Size: | Type: | Custom Order? | 40 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 320 | 400 |
|----------------------|--|--------|---------------|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|
| 44-WIDTH-LENGTH-GRIT | W: 13" - 56" L: 32" - 400" | Wide | Yes | | | • | • | • | • | • | • | • | • | • |
| 44-WIDTH-LENGTH-GRIT | W: 0.25" - 12" L: 6" - 400" | Narrow | Yes | | | • | • | • | • | • | • | • | • | • |

Ultimax



| | Part Number: | Size: | Type: | Custom Order? | 40 | 50 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 320 |
|---|---------------------|--|--------|---------------|----|----|----|-----|-----|-----|-----|-----|-----|-----|
| U | C-WIDTH-LENGTH-GRIT | W: 13-56" L: 32" - 400" | Wide | Yes | | | • | • | • | • | • | • | • | • |
| U | C-WIDTH-LENGTH-GRIT | W: 0.25" - 12" L: 6" - 400" | Narrow | Yes | | | • | • | • | • | • | • | • | • |



DID YOU KNOW?

Belt Joint Types

T-Joint (Standard joint up to 12" wide)

T-Joint is the original standard tape joint for cloth belts, used on narrow and portable belts. Normally slightly thicker than the abrasive, it requires thin tape to prevent chatter marks.

TS-Joint (Standard joint 13" wide and above)

A TS-joint is similar to a T-joint but the connecting ends are cut in a sine wave shape to avoid the hinge effect. This joint type is most suitable for belts in medium grit sizes.

B-Joint (Standard on Mirka® Ultimax belts)

B-joint is an overlapping joint with compensation on the sanding side. This means that the joint area is free of abrasive material, which allows the paper to overlap without adding thickness to the area.

Sica Closed

04 Series







Technical Specifications

| | • |
|---------|-------------------------------|
| Grain | Silicon Carbide |
| Bonding | Resin over Resin / Antistatic |
| Backing | Antistatic F-Paper |
| Coating | Closed |
| Color | Black |
| Joint | A, T, TS, TT |

FEATURES AND BENEFITS:

- The antistatic treatment reduces dust loading to keep machines and work piece cleaner
- Fine scratch pattern produces a quality final result after surface treatment
- Designed for sanding of hardwood and MDF
- Well suited to use after Jepuflex to achieve a better finish

Sica Fine Stearate

05 Series







FEATURES AND BENEFITS:

- Full stearate coating for minimal dust load
- Can reduce topcoat use
- Variety of belt styles

Sica Closed P

| Part Number: | Size: | Type: | Custom Order? | 36 | 40 | 50 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 |
|----------------------|---|--------|---------------|----|----|----|----|----|-----|-----|-----|-----|-----|-----|
| 04-WIDTH-LENGTH-GRIT | W: 13" - 56" L: 32" - 400" | Wide | Yes | | | | | • | • | • | • | • | • | |
| 04-WIDTH-LENGTH-GRIT | W: 0.25" - 12" L: 6 " - 400" | Narrow | Yes | | | | | • | • | • | • | • | • | |

Sica Fine Stearate



DID YOU KNOW?

Belt Joint Types (continued)

A-Joint (Custom joint - available by request)

A-joint is an overlapping joint without interruption in the abrasive coating. Used for paper belts, it produces a uniform belt thickness and results in even sanding without chatter marks.

TT-Joint (Custom joint - available by request)

TT is a special joint for cloth belts with the tape applied to the sanding side, making it suitable for profile sanding with a sanding pad.



Mini File Belts

66 Series (-XXX)









| Technical Specifications | | | | | | | |
|--------------------------|------------------|--|--|--|--|--|--|
| Grain | Ceramic blend | | | | | | |
| Bonding | Resin over resin | | | | | | |
| Backing | Y Polyester | | | | | | |
| Coating | Semi-open | | | | | | |
| Color | Red | | | | | | |

FEATURES AND BENEFITS:

- Improved ceramic blended self-sharpening grains
- Designed for high alloy steel and super alloys
- Subtle breakdown of ceramic grain produces much sharper edges which allows for lower temperature contact area and extended life
- Optimum stock removal

Surface Conditioning Belts

66 Series (-CG and -MM)









| Technical Specifications | | | | | | | |
|---------------------------------|-----------------------|--|--|--|--|--|--|
| Grain | Aluminum oxide | | | | | | |
| Bonding | Resin over resin | | | | | | |
| Backing | Non-woven nylon fiber | | | | | | |
| Coating | Closed | | | | | | |
| Color | CG: Gold, MM: Maroon | | | | | | |

FEATURES AND BENEFITS:

- Robust aluminum oxide grains
- Strong, durable nylon backing
- Optimum stock removal
- Non-woven abrasive

| Part Number: | Size: | Description: | 36 | 50 | 60 | 80 | 100 | COARSE | MEDIUM |
|--------------|-------------|--|----|----|----|----|-----|--------|--------|
| 66-1218-CG | .5" x 18" | Mini File Belt Non-Woven, Coarse, 10/Box | | | | | | • | |
| 66-1218-MM | .5" x 18" | Mini File Belt Non-Woven, Medium, 10/Box | | | | | | | • |
| 66-3813-CG | .375" x 13" | Mini File Belt Non-Woven, Coarse, 10/Box | | | | | | • | |
| 66-3813-MM | .375" x 13" | Mini File Belt Non-Woven, Medium, 10/Box | | | | | | | • |



DID YOU KNOW?

Pair Mirka® Mini File Belts with Mirka's File Belt Sanders to tackle tough sanding applications in automotive refinishing and metal processing. The cordless FBS-B and the pneumatic PBS models excel in seam and spot weld grinding and in paint removal. The tools are user-friendly, ergonomic, and powerful, yet still light and comfortable to hold.

The control of sanding speed is also a big factor when using Mirka's mini belts. Running the tool at a lower speed actually gets the job done faster and also increases the life of the belt.

GRINDING DISCS

Cutoff Wheels





| Part Number: | Size: | Thickness: | Color |
|--------------|-------|------------|---------|
| MS-0110 | 3" | 1/32" | Royal |
| MS-0150 | 3" | 1/16" | Royal |
| MS-0316 | 3" | 3/16" | Premium |

FEATURES AND BENEFITS:

- Fast cutting wheels for use when cutting autobody sheet metal, ferrous and non-ferrous metals, fiberglass, plastics and composite materials
- 3 in. diameter with 3/8" center hole
- Rated to 24,000 rpm

Trim-Kut°







| Part Number: | Size: | 24 | 36 | 60 | 80 |
|--------------|-------|----|----|----|----|
| 63-300-XXX | 3" | • | • | • | |
| 63-500-XXX | 5" | • | • | | |

FEATURES AND BENEFITS:

- Plastic backing resists breaking and cracking
- Can be trimmed to the 1" core
- Color coded for easy grit identification
- Can be used in grinders and high speed drills with quick change mandrels and adapters
- Suitable for use on metal, wood, fiberglass and composite materials

Resin Fiber Discs






| Size: | 24 | 36 | 50 | 60 |
|-------|----|----|----|--|
| 5" | • | • | • | |
| 7" | • | | | |
| | | | | Size: 24 36 50 5" • • • 7" • * * |

- Ceramic Resin Fiber Discs contain 100% SG ceramic grain with a top coat that resists loading and aids in cooling
- Great for metal grinding applications that provides maximum productivity at reduced cost
- Long-life and maximum performance on stainless steel and other alloys

GRINDING DISCS

Mini Strip Away Discs





| Part Number: | Size: | |
|--------------|-------|----------------|
| 66-300-CS | 3" | Orange, 10/Box |
| 66-400-CS | 4" | Orange, 5/Box |

FEATURES AND BENEFITS:

- Open design for fast and cool cutting action
- Cleans welds and removes paint, rust, and coatings without profiling or gouging the metal beneath

MRFD Mini Ceramic Ultra X, Type R





| Part Number: | Size: | 24 | 36 | 50 | 60 | 80 | 100 | 120 |
|--------------|-------|----|----|----|----|----|-----|-----|
| 66-201-XXX | 2" | • | • | • | • | • | | |
| 66-301-XXX | 3" | • | • | • | • | • | | |

FEATURES AND BENEFITS:

- Manufactured with a high quality grain and finer crystalline structure which helps produce an improved self-sharpening effect
- Improved ceramic grain performance with higher stock removal rates for metal applications
- Lower grinding temperature rates produce less friction and heat
- Excellent cost/performance ratios

Surface Prep Discs







| Part Number: | Size: | Grit: |
|--------------|-------|--------|
| 67-200-MM | 2" | Medium |
| 67-200-CG | 2" | Coarse |
| 67-300-MM | 3" | Medium |
| 67-300-CG | 3" | Coarse |

FEATURES AND BENEFITS:

- Stripping Discs are made from tough, synthetic fibers impregnated with abrasive grit that offer fast cutting action, without damaging metal surfaces
- Ideal for deburring metal, and removing rust, paint or scale while providing a safer alternative to wire bristle tools
- The open design quickly cleans surfaces without damage and provides fast cutting action with virtually no heat build-up

Holder, Type R Grinding Discs





| Part Number: | Size: | |
|--------------|-------|---------------------------------------|
| 65-002 | 2" | Holder, Type "R" Grinding Disc, 1/Pkg |
| 65-003 | 3" | Holder, Type "R" Grinding Disc, 1/Pkg |

FEATURES AND BENEFITS:

- Locking disc holder
- R-type screw attachment
- Allows quick change of mini discs
- Medium density precision cast rubber backing



Polarshi

POLARSHINE® POLISHING AND FINISHING COMPOUNDS

Polarshine® E3









PE3-1L 1 Liter

FEATURES AND BENEFITS:

- Removes scratches from glass surfaces
- Use on standard window glass and hardened glass
- One-Step polishing process
- Silicone-Free

Polarshine[®] 3



| Part Number: | Size: |
|--------------|---------|
| FC3-1L | 1 Liter |

FEATURES AND BENEFITS:

- Antistatic carnauba wax finishing compound
- Removes minor paint imperfections and fills fine scratches
- Durable, deep, rich shine
- Protects from UV rays, heat, rain, and contaminants
- Works on original paint and repainted surfaces

Polarshine[®] 5



| Part Number: | Size: |
|--------------|---------|
| FC5-1L | 1 Liter |
| | |

FEATURES AND BENEFITS:

- High gloss finish without swirl and fine sanding marks
- A medium-fine polish for cleaning and refreshing surfaces
- Suitable for hologram removal
- Silicone-free
- Part of Golden Finish System

Polarshine® 8





| Part Number: | Size: | |
|--------------|---------|--|
| PC8-1L | 1 Liter | |

FEATURES AND BENEFITS:

- Designed for single-step polishing in AOEM/Tier1 applications
- Permanently removes deep swirl marks while producing a high gloss finish
- Keeps surface temperature low when polishing
- Suitable for use on all paint systems
- Silicone-free

Polarshine® 10

Part Number:

PC10-025L

PC10-1L

PC10-5L



Size:

250 ml

1 Liter

5 Liters









FEATURES AND BENEFITS:

- The ultimate single-compound polishing system
- Medium-Coarse polishing compound buffs and polishes simply by changing pads
- Removes sanding scratches without fillers
- Suitable for all paint systems including scratch-resistant clear coats
- Water-based and silicone-free

Polarshine® 12





| Part Number: | Size: |
|--------------|----------------|
| PC12-1L | 1 Liter |
| PC12-5L | 5 Liters |
| PCB12-1 | Black, 1 Liter |
| | |

FEATURES AND BENEFITS:

- One-Step polishing compound
- Water-Based and silicone-free
- Removes scratches from P2000 or finer
- Perfect balance of haze and hologram versus speed of cut

PRO Iridium™ 1250



| Part Number: | Size: |
|--------------|---------|
| PC1250-1L | 1 Liter |
| | |

FEATURES AND BENEFITS:

- One-Step polishing
- Fast, easy defect removal
- Used in vehicle manufacturing
- Resistance to slinging makes cleanup easy
- Part of the Pro Finishing Solution

Polarshine[®] 15

Part Number:

PC15-1L



Size:

1 Liter









FEATURES AND BENEFITS:

- A medium coarse polishing compound for removal of P1200 and finer sanding scratches
- For oxidized surfaces and water mark removal on refinish coatings
- Also suitable for removal and leveling of fine orange peel
- Silicone-free

Polarshine[®] 20



| Part Number: | Size: | |
|--------------|---------|--|
| PC20-1L | 1 Liter | |



FEATURES AND BENEFITS:


- Medium-Coarse polishing compound for scratch removal
- Optimized for fresh and soft clear coats
- Water-soluble
- Excellent cut and leaves a very high gloss surface
- Part of Golden Finish system

Polarshine® 35











FEATURES AND BENEFITS:

- An aggressive polishing compound for removal of P800 and finer sanding scratches, or for heavily oxidized surfaces.
- Can also be used for removal of fine orange peel
- Ideal for gelcoats, refinish coatings and composites
- Silicone-free

Polarshine® 45










Part Number: Size: PC45-025L 250 ml PC45-1L 1 Liter PC45-2.8L 2.8 Liters PC45-17L 17 Liters

FEATURES AND BENEFITS:

- Coarse polishing compound for production or restoration processes
- Suitable for hard surfaces and coatings; ideal for gel coat and high gloss lacquers
- Quickly and permanently removes scratches from Mirka P600 abrasives
- Removes heavy oxidation and restores color and shine
- Leaves a deep gloss finish one step polishing for light colors!

PRO FINISHING SOLUTION



The **Pro Finishing Solution** was created especially for the demanding work of Automotive Manufacturing. The system combines several Mirka products:

Our cordless spot repair sanders and Mirka Iridium™ SR discs sand out the imperfections. The sanded area is then polished with Pro Iridium™ 1250 polishing compound plus Mirka cordless polishing tools and polishing pads.

The compound was developed especially for the Pro Finishing solution. Normally, polishing when removing surface defects is a two-step process: one compound to remove the sanding scratch marks and a second to restore gloss. With Mirka Pro Iridium™ 1250, you get the best of both worlds—you only need to polish once, while still getting a perfect result.

FEATURES AND BENEFITS:

- Professional system for fast, easy defect removal
- Keeps surface cool during sanding and polishing
- Consistent, hologram-free finish

STEP 1

STEP 2



Finessing Damper



Cordless Angled Sander



Iridium[™]SR **Abrasives** (page 12)



Cordless Rotary Polisher (page 41)



Yellow Waffle **Polishing Pad** (page 39)



Burgundy Waffle Polishing Pad (page 39)



Pro Iridium[™] 1250 compound (above)

(page 66)

(page 41)

















POLISHING

LIGHT CUTTING

MEDIUM CUTTING

AGGRESSIVE



BLACK FOAM PAD

- For fine polishing and finessing of paint surfaces
- Produces a high gloss finish
- Suitable for use with most polishing systems
- Easy, grip fastening
- Washable

| | Part Number: | Description: |
|---|---------------|--------------------------|
| | MPADBF-3.25 | 3¼" dia. x 1⁄8" |
| * | MPADBF-3.25RP | 31/4" dia. x 7/8", 2/Pkg |
| | MPADBF-6F | 6" x 1", Flat |
| | MPADBF-6W | 6" x 1", Waffle |
| | MPADBF-8 | 8" dia. x 11⁄4" |

^{*} RP = Smaller packages designed for retail sales



LAMBS WOOL POLISHING PAD

- For medium coarse polishing
- Suitable for dry use
- Easy, grip fastening
- The best choice for a perfect finish
- Washable

| | Part Number: | Description: |
|---|--------------|----------------|
| | MPADLW-3 | 3" x ¾" |
| * | MPADLW-3RP | 3" x ¾", 2/Pkg |
| | MPADLW-6 | 6" x ¾" |
| | MPADLW-7 | 7" × ¾" |
| | MPADLW-7.5 | 7½" x ¾" |

^{*} RP = Smaller packages designed for retail sales



FELT PAD

- Designed for glass polishing applications
- Felt pad construction has good balance and stability during polishing
- Designed to be used in combination with Polarshine® E3

| Part Number: | Description: |
|--------------|-----------------------------|
| MPADFP-5 | 5" x ¼", Felt Polishing Pad |



WHITE FOAM PAD

- Medium density pad, for less aggressive polishing
- Especially designed for medium coarse polishing
- Easy, grip attachment
- Suitable for most paintwork
- Washable

| Part Number: | Description: |
|--------------|--------------|
| MPADWF-8 | 8" x 11/4" |

MARINE POLISHING KIT



Achieve a Perfect Finish in Marine Applications

Take the guesswork out of marine surface care with this professional polishing kit. Featuring premium abrasives and compounds tailored for superior performance, it delivers exceptional results with minimal effort.

- Mirka® Galaxy abrasives for 5" or 6" tools
- · Polarshine® water-based polishing compounds
- · Twisted wool polishing pads
- · Microfiber cleaning cloth

MUS-MP5KIT (5") and MUS-MP6KIT (6")



ORANGE FOAM PAD

- For aggressive cutting and polishing
- High density, fine textured
- Suitable for most polishing systems
- Easy, grip fastening
- Washable

| Part Number: | Description: | | | | |
|--------------|-----------------------|--|--|--|--|
| MPADOF-3.25 | 31⁄4" dia. x 7⁄8" CCS | | | | |
| MPADOF-6W | 6" dia. x 1" Waffle | | | | |
| MPADOF-8 | 8" dia. x 1¼" Dimple | | | | |



BURGUNDY FOAM PAD

- Suitable for hard and medium hard coatings
- Fast cut with good gloss
- Provides stable polishing process
- Washable

| Part Number: | Description: |
|---------------|--------------|
| MPADMF-3.25WB | 3¼" dia. x1" |

QUICK DISCONNECT PADS & ADAPTER



- Adapter fits rotary polishers with 5/8" thread
- Attach or remove pads in seconds
- Secure, perfectly balanced connection to polisher
- Large, double-sided pads

| Part Number: | Description: |
|--------------|---|
| MPAD-QD | Quick Disconnect Pad Adapter |
| MPADBF-8QD | 8" Quick Disconnect Waffle - Black |
| MPADWF-8QD | 8" Quick Disconnect Waffle - White |
| MPADOF-8QD | 8" Quick Disconnect Waffle - Orange |
| MPADTW-8QD | 8" x 1" Quick Disconnect - Twisted wool |



YELLOW FOAM PAD

- For aggressive cutting and polishing
- Waffle face keeps surface cool during polishing
- High density, fine textured
- Suitable for most polishing systems
- Easy grip fastening
- Washable

| Part Number: | Description: |
|---------------|-------------------------|
| MPADYF-3.25W | 3¼" x 1", Waffle |
| MPADYF-3.25WB | 3¼" x 1", Waffle, 20/pk |
| MPADYF-6W | 6" x 1", Waffle |
| MPADYF-8W | 8" x 11/4", Waffle |



YELLOW TWISTED ACRYLIC WOOL PAD

- For medium duty polishing
- Soft edges for easy polishing
- Easy grip fastening
- Washable
- The best choice for a perfect finish

| Part Number: | Description: | | | | | |
|-----------------|--------------|--|--|--|--|--|
| MPADTWY-7.5 | 7½" x 1" | | | | | |
| MPADTWY-7.5-1.5 | 7½" x 1½" | | | | | |



TWISTED WOOL PAD

- For fast cutting, coarse polishing
- Soft edges for easy polishing
- Washable

| Part Number: | Description: |
|----------------|------------------------------------|
| MPADTW-3 | 3" dia., Grip |
| MPADTW-6 | 6" dia. x 1", Grip |
| MPADTW-7.5 | 7½" dia. x 1", Grip |
| MPADTW-7.5-1.5 | 7½" dia. 1½", Grip |
| MPADDS-8 | 8" dia. x 1", Double-Sided, Thread |



YELLOW LAMBS WOOL POLISHING PAD

- Made of premium wool fibers
- For demanding use
- Use with Polarshine® 35, 15, 10 and 8
- Easy, grip fastening
- Suitable for polishing all kinds of paint works

| Part Number: | Description: | | | | | |
|--------------|---------------|--|--|--|--|--|
| MPADLWY-3 | 3" dia. x 1" | | | | | |
| MPADLWY-5.25 | 5 ¼"dia. x ¾" | | | | | |
| MPADLWY-6 | 6" dia. x 1" | | | | | |
| MPADLWY-7 | 7" dia. x ¾" | | | | | |






Cordless File Belt Sanders (FBS-B)





This high-performance, ergonomic cordless sander is designed for durability and ease of use. Without the restrictions of a cord, it allows users access to hard-to-reach areas. Ideal for cleaning welding seams, spot welds, removing paint, and performing vehicle body repairs. Available with two belt size options. Use with Mirka® Mini File Belts and Surface Conditioning Belts. Complete kit comes with two 5.0 Ah batteries and a charger compatible with the existing platform.





FEATURES AND BENEFITS:

- Operating light illuminates work surface
- Powerful, long-life, brushless electric motor
- Stepless trigger button adjusts through seven speeds

| Part Number | Model Number | Belt Size | Weight | Speed | Noise | Voltage | Vib m/s² |
|--------------|----------------------------|-----------|---------|------------|-------|----------|------------------------|
| MBB1002100US | FBS-B 10 US (with battery) | 3%" x 13" | 1.5 lbs | 2200-17000 | 80 dB | max 12 V | 3.125 m/s ² |
| MBB1302100US | FBS-B 13 US (with battery) | ½" x 18" | 1.6 lbs | 2200-17000 | 80 dB | max 12 V | 3.125 m/s ² |
| MBB1000100 | FBS-B 10 (without battery) | | | | | | |
| MBB1300100 | FBS-B 13 (without battery) | | | | | | |

RECOMMENDED ACCESSORIES

| Part Number: | Size: | Description: |
|--------------|------------|---|
| 66-1218-CG | ½" x 18" | Mini File Belt Non-Woven, Coarse, 10/Box |
| 66-1218-MM | ½" x 18" | Mini File Belt Non-Woven, Medium, 10/Box |
| 66-3813-CG | 3/8" x 13" | Mini File Belt Non-Woven, Coarse, 10/Box |
| 66-3813-MM | 3/8" x 13" | Mini File Belt Non-Woven, Medium, 10/Box |
| BPA10850 | | Intelligent battery 11.1 V, 5.0 Ah |
| BCA108 | | Battery Charger BCA 108 max 12V w/o power cord US |
| BCA108PC | | Power Cord 2.0m for Battery Charger BCA 108 US |



Cordless Tools



Mirka cordless tools are light, ergonomic, and optimized for efficiency and portability, allowing freedom of movement without hoses or cables. Incredibly nimble, they are quiet, small, and low maintenance thanks to the brushless motor.

To minimize downtime, cordless tools come with two batteries and a charger so one can be recharging while the other is in use. Sanders and polishers come with two 2.5 Ah 11.1V Li-ion batteries. The ANGOS grinder comes with two 5.0 Ah batteries.

For a comprehensive cordless system, combine Mirka cordless sanders, polishers, and grinders with our spot repair abrasives, polishing compounds, and grinding discs.

CORDLESS SANDERS





AOS130-B

AROS150-B

| Part Number | Model Number | Size | Orbit | RPM | Pad Face | Weight | Watts | Noise | Vib m/s ² |
|--------------|------------------------------|-------|-------|---------------|------------|---------|----------|-------|----------------------|
| AOS130-B | AOS-B 130 | 11⁄4" | 3 mm | 4,000 - 8,000 | PSA + Grip | 1.3 lbs | max 12 V | 61 dB | 2.5 |
| AROS150-B | AROS-B 150 | 11/4" | 5 mm | 4,000 - 8,000 | PSA + Grip | 1.3 lbs | max 12 V | 61 dB | 1.9 |
| AOS130-B-NV | AOS-B 130 (without battery) | | | | | | | | |
| AROS150-B-NV | AROS-B 150 (without battery) | | | | | | | | |

CORDLESS POLISHERS





ARP300-B

AROP312-B

| Part Number | Model Number | Size | Orbit | RPM | Pad Face | Weight | Watts | Noise | Vib m/s ² |
|-------------|---------------------|------|-------|---------------|----------|---------|----------|-------|----------------------|
| ARP300-B | ARP-B 300 | 3" | 0 mm | 1,500 - 2,200 | Grip | 1.9 lbs | max 12 V | 57 dB | 1.8 |
| AROP312-B | AROP-B 312 | 3" | 12 mm | 4,000 - 7,000 | Grip | 2 lbs | max 12 V | 60 dB | 4.3 |

AROP312-B-NV AROP-B 312 (without battery)

CORDLESS GRINDER



| Part Number | Model | Max Pad Size | Collet Size | Weight | Max Speed | Noise | Voltage | Vib m/s² |
|--------------|--------------------|--------------|-------------|----------|------------|-------|----------|----------------------|
| ARG-B-200 | ANGOS ARG-B 200 US | 2" | 1/4" | 1.96 lbs | 20,000/min | 66 dB | 10.8 VDC | 2.5 m/s ² |
| 89911003WBUS | (without battery) | | | | | | | |



DEROS RS 600X





Introducing the Mirka® DEROS RS 600X, a powerful, light, and quiet heavy-duty rotary sander

The Mirka® DEROS RS 600X is made for heavy-duty, coarse sanding applications. Despite its robust attributes, this tool maintains a surprising level of smoothness during operation, offering a quiet and easily maneuverable solution for tackling rough materials.



MRS60011CAUS

FEATURES AND BENEFITS:

- Powerful + lightweight
- Low noise + minimal vibration
- Easy-to-use, ergonomic design
- Multiple dust extraction points
- LED indicator for RPM
- Momentary switch

| Part Number | Model Number | Size | Orbit | RPM | Pad Face | Weight | Watts | Noise | Vib m/s² |
|--------------|------------------------|------|-------|-------------|------------------|--------|-------|-------|----------|
| MRS60011CAUS | RS 600X | 6" | 0 | 700 - 2,500 | Multi-Hole, Grip | 4 lbs | 750 | 68 dB | 1.3 |
| MRS6001100US | RS 600X (without case) | | | | | | | | |

Modes of Operation -

The DEROS RS 600X offers a range of modes and functions to enhance user control. The multi-purpose LED light indicates the current mode.

- Ramp-Up Mode
- Gradually increases speed to a selected setting as load is applied
- Starting at a lower speed reduces the risk of damaging the workpiece
- Normal Mode
- Operates at a constant speed set by the user without automatic adjustments
- Standby Mode
- · A low power state will not operate until reactivated
- · Lock Mode
- Tool stays running no need to hold the button



DEROS + DEOS





DEOS and DEROS feature a high-efficiency brushless motor, with plenty of power to get the job done quickly. Their closed construction prevents dust from entering the motor to make it low maintenance and ultra-reliable. Plus, they are vacuum-ready and their power cords are removable and interchangeable.

DEROS

Electric Random Orbital + Orbital Sanders









MID3502011US

MID55020CAUS

MID62520CAUS

MID65020CAUS

| Part Number | Model Number | Size | Orbit | RPM | Pad Face | Weight | Watts | Noise | Vib m/s² |
|--------------|------------------------------|------|--------|----------------|------------------|---------|-------|-------|----------|
| MID3502011US | 350XCV | 3" | 5 mm | 4,000 - 10,000 | Multi-Hole, Grip | 1.8 lbs | 250 | 67 dB | 3.3 |
| MID55020CAUS | 550XCV | 5" | 5 mm | 4,000 - 10,000 | Multi-Hole, Grip | 2.2 lbs | 350 | 71 dB | 3.2 |
| MID55020US | 550XCV (without case) | | | | | | | | |
| MID62520CAUS | 625XCV | 6" | 2.5 mm | 4,000 - 10,000 | Multi-Hole, Grip | 2.3 lbs | 350 | 71 dB | 2.4 |
| MID65020CAUS | 650XCV | 6" | 5 mm | 4,000 - 10,000 | Multi-Hole, Grip | 2.3 lbs | 350 | 71 dB | 3.4 |
| MID65020US | 650XCV (without case) | | | | | | | | |

DEOS

Electric Orbital Sanders









MID3430201US

MID3530201US

MID3830201US

MID6630201US - Delta

| Part Number | Model Number | Size | Orbit | RPM | Pad Face | Weight | Watts | Noise | Vib m/s² |
|--------------|--------------|--------------|-------|----------------|------------------|----------|-------|-------|----------|
| MID3430201US | 343XCV | 3" x 4" | 3 mm | 5,000 - 10,000 | Multi-Hole, Grip | 2.15 lbs | 250 | 70 dB | 3.3 m/s2 |
| MID3530201US | 353XCV | 3" x 5" | 3 mm | 5,000 - 10,000 | Multi-Hole, Grip | 2.1 lbs | 250 | 69 dB | 2.6 |
| MID3830201US | 383XCV | 3" x 8" | 3 mm | 5,000 - 10,000 | Multi-Hole, Grip | 2.2 lbs | 250 | 71 dB | 2.6 |
| MID6630201US | 663XCV | 4" x 6" x 6" | 3 mm | 5,000 - 10,000 | Multi-Hole, Grip | 2.1 lbs | 250 | 68 dB | 2.6 |

All Mirka® Electric Power Tools Features:

- 1" I.D. hose threaded vacuum fitting
- Brushless DC motor technology
- Twice the power of pneumatic tools, yet lighter
- Quick connect fitting for the dust extraction hose
- Digitally controlled with variable speeds
- Pair with 'NET' abrasives for a dust-free experience
- Bluetooth connectivity pairs with myMirka App
- On/Off Switch on all models



DEROS EDGE PROTECTORS

The Edge Protector for Mirka® DEROS is a clever accessory that attaches to the tool to prolong the life of the backing pad. Simply clip on the DEROS to protect the edge of the backing pad when sanding corners and edges. Using the Edge Protector also stops the backing pad from damaging adjacent surfaces.



Not only is the Mirka^{*} LEROS the lightest, most compact and most advanced random orbital wall and ceiling sander, it enables perfect surface finishing results and a safe, clean working environment. Its dust-free efficiency dramatically reduces prep and cleanup time.

Plus, the award-winning LEROS is lightweight, putting less strain on operators' arms and shoulders. The large sanding head with 180° swivel helps to get the job done quickly. The long arm can sand ceilings without the need to climb ladders. The shorter arm of the LEROS-S is perfect for fitting into small spaces.



FEATURES AND BENEFITS:

- Lightweight weighs approximately seven pounds
- Flexible sanding head swivels to any angle
- 5 mm random orbital movement provides better surface finish
- Full force system no need to press
- Dual suction points provides efficient dust extraction
- Two lengths available LEROS (57") + LEROS-S (35")

| Part Number | Model | Length | Weight | Pad Size | Max Speed | Noise | Power | Vibration | Orbit | Flexibility |
|--------------|----------------|--------|---------|----------|-----------|-------|-------|------------------------|--------|-------------|
| MIW95020BAUS | LEROS 950XCV | 57" | 7.7 lbs | 9" | 8,000 rpm | 73 dB | 350 W | < 2.5 m/s ² | 5.0 mm | 180° |
| MIW95021BAUS | LEROS-S 950XCV | 35" | 7 lbs | 9" | 8,000 rpm | 73 dB | 350 W | $< 2.5 \text{ m/s}^2$ | 5.0 mm | 140° |

Dust-Free Systems

Mirka® LEROS Complete System MIW950-DE1230AFC-4



Mirka® LEROS-S Complete System MIW951-DE1230AFC-4



Each system includes LEROS plus:

| DE-1230-AFC | Dust Extractor |
|-------------|-------------------------------|
| MIN6519411 | Hose 1" x 13' |
| MIE6515911 | Sleeve for Hose & Cable 11.5' |
| MIW-EXT | Extension Shaft |
| MIW-BAG | LEROS Carrying Bag |

RECOMMENDED ACCESSORIES



Mirka® LEROS Extension Shaft



MIW-BAG Mirka^a LEROS Carrying Bag (included with tool)



MIE6515911 Sleeve for Hose and Cable 11.5'

| MIW-EXT | Extension Shaft 19.685" |
|------------|---|
| MIW-BAG | Carry Bag for Mirka* LEROS |
| MIW9514312 | Backing Pad 9" 25H Grip Mirka* LEROS + 8 screws |
| 9199 | Interface Pad 9" 25H for Mirka* LEROS |
| 82S6001001 | Net Interface 9" with Spacer, for Mirlon products |
| 9999 | Pad Saver 9" 25H for Mirka LEROS |

PNEUMATIC TOOLS

PROS Pneumatic Random Orbital Sanders

Mirka PROS pneumatic random orbital sanders are constructed from high quality materials that deliver long term durability, ensuring you will enjoy outstanding performance from your sander long into the future. Optimized ergonomics make it comfortable for long operating periods and allow for two handed use. Choose from Central Vacuum (CV), Self-Generating Vacuum (SGV), and Non-Vacuum (NV) models.







CV: Central Vacuum

SGV: Self-Generating Vacuum

NV: Non-Vacuum

CV: Central Vacuum

| Part Number | Model Number | Size | Orbit | RPM | Pad Face | Weight | HP | SCFM | Noise | Vib m/s² |
|-------------|--------------|------|-------|--------|------------------|--------|------|------|-------|----------|
| MRP-550CV | 550CV | 5" | 5 mm | 12,000 | Multi-Hole, Grip | 2 lbs | 0.28 | 17 | 74 dB | 2.4 |
| MRP-580CV | 580CV | 5" | 8 mm | 12,000 | Multi-Hole, Grip | 2 lbs | 0.28 | 17 | 74 dB | 3.8 |
| MRP-650CV | 650CV | 6" | 5 mm | 12,000 | Multi-Hole, Grip | 2 lbs | 0.28 | 17 | 75 dB | 3.2 |
| MRP-680CV | 680CV | 6" | 8 mm | 12,000 | Multi-Hole, Grip | 2 lbs | 0.28 | 17 | 76 dB | 3.4 |

SGV: Self-Generating Vacuum

| Part Number | Model Number | Size | Orbit | RPM | Pad Face | Weight | HP | SCFM | Noise | Vib m/s ² |
|-------------|---------------------|------|-------|--------|------------------|--------|------|------|-------|----------------------|
| MRP-550SGV | 550DB | 5" | 5 mm | 12,000 | Multi-Hole, Grip | 2 lbs | 0.28 | 17 | 81 dB | 2.8 |
| MRP-650SGV | 650DB | 6" | 5 mm | 12,000 | Multi-Hole, Grip | 2 lbs | 0.28 | 17 | 78 dB | 3.0 |

NV: Non-Vacuum

| Part Number | Model Number | Size | Orbit | RPM | Pad Face | Weight | HP | SCFM | Noise | Vib m/s² |
|-------------|--------------|------|--------|--------|----------|--------|------|------|-------|----------|
| MRP-525NV | 525NV | 5" | 2.5 mm | 12,000 | PSA | 2 lbs | 0.28 | 17 | 74 dB | 2.4 |
| MRP-550NV | 550NV | 5" | 5 mm | 12,000 | PSA | 2 lbs | 0.28 | 17 | 74 dB | 2.4 |
| MRP-580NV | 580NV | 5" | 8 mm | 12,000 | PSA | 2 lbs | 0.28 | 17 | 74 dB | 3.8 |
| MRP-650NV | 650NV | 6" | 5 mm | 12,000 | PSA | 2 lbs | 0.28 | 17 | 74 dB | 3.2 |
| MRP-680NV | 680NV | 6" | 8 mm | 12,000 | PSA | 2 lbs | 0.28 | 17 | 75 dB | 3.4 |




DID YOU KNOW?

PROS tools make sanding and polishing...

Easy: The PROS includes an air inlet extension to make connecting to air source easy.

Comfortable: PROS tools have an ergonomic design that allows one or two hand operation.

Safe: PROS have a locking feature to prevent accidental tool running while changing pads.



PNEUMATIC TOOLS

Pneumatic Belt Sanders

The Mirka PBS-10330 and the Mirka PBS-13457 are user-friendly and ergonomic tools that are powerful yet quiet to use. Comfortable to hold with a cushioned rubber grip, the grinding speed is easy to set with a top-mounted selector.

Tension mechanisms make the belts easy to change without tools in just a matter of seconds, and the arm angle of the tools are quickly adjusted with a key that is stored right in the handle.

FEATURES AND BENEFITS:

- Safety cover throws debris away from operator
- Accessible tension mechanism easy-to-change belts
- Speed regulator on top of tool effortless adjustment
- Hex key stores in the handle at hand for quick angle adjustment
- Easily reset angle get into hard-to-reach places quickly
- Rubber-coated handle doesn't get cold comfortable to hold
- Low noise level preferred belt sander for daily use
- Competitive pricing affordable addition to tech's toolkit





PBS-10330

PBS-13457

| Part Number | Model Number | Belt Size | Weight | Speed | Noise | Watts | Air Consumption | Vib m/s² |
|-------------|--------------|-----------|----------|------------|---------|-------|--------------------|-----------------------|
| PBS-10330 | 10NV | .4" x 13" | 1.79 lbs | 17,000/min | 85.7 dB | 417.6 | 610 l/min | 1.88 m/s ² |
| PBS-13457 | 13NV | .5" x 18" | 2 lbs | 20,000/min | 85 dB | 522 | 800 l/min | 1.04 m/s ² |

DID YOU KNOW?

The Mirka PBS-10330 and the Mirka PBS-13457 are user-friendly and ergonomic tools that are powerful yet quiet to use. Comfortable to hold with a cushioned rubber grip, the grinding speed is easy to set with a top-mounted selector.

Tension mechanisms make the belts easy to change in just a matter of seconds, and the arm angle of the tools are quickly adjusted with a key that is stored right in the handle.



MR-SERIES ROUND PNEUMATIC SANDERS

MR-Series Pneumatic Tools

Mirka's MR-Series Pneumatic Sanders are constructed of precision molded composites for strength and durability. This construction also reduces weight and sound for increased operator comfort. Moisture-resistant composite rotors and premium counterweight bearings ensure superior reliability.

The sanders' orbital motion leaves the surface easy to polish. Select from a wide range of sizes to accommodate square or round abrasives and dust-removal systems (CS, SGV, and NV).



CV: Central Vacuum



NV: Non-Vacuum



SGV: Self-Generating Vacuum

CV: Central Vacuum

| Part Number | Size | Orbit | RPM | Pad Face | Weight | HP | SCFM | Noise | Vib m/s ² |
|-------------|------|-------|--------|-------------|---------|------|------|-------|----------------------|
| MR-350CV | 3" | 5 mm | 12,000 | 6-Hole Grip | 1.17lbs | 0.28 | 17 | 80 dB | - |

NV: Non-Vacuum

| Part Number | Size | Orbit | RPM | Pad Face | Weight | HP | SCFM | Noise | Vib m/s ² |
|-------------|------|--------|--------|----------|----------|------|------|-------|----------------------|
| MR-3 | 3" | 2.5 mm | 12,000 | Grip | 1.12 lbs | 0.28 | 17 | 76 dB | 3.04 |
| MR-350 | 3" | 5 mm | 12,000 | PSA | 1.12 lbs | 0.28 | 17 | 80 dB | 2 |
| MR-5 | 5" | 5 mm | 12,000 | Grip | 1.7 lbs | 0.28 | 17 | 80 dB | 2.6 |
| MR-508 | 5" | 8 mm | 12,000 | PSA | 1.7 lbs | 0.28 | 17 | 74 dB | 3.5 |
| MR-525 | 5" | 2.5 mm | 12,000 | PSA | 1.7 lbs | 0.28 | 17 | 80 dB | 2.1 |
| MR-6 | 6" | 5 mm | 12,000 | PSA | 1.74 lbs | 0.28 | 17 | 79 dB | 3.7 |
| MR-608 | 6" | 8 mm | 12,000 | PSA | 2 lbs | 0.28 | 17 | 75 dB | 3.5 |
| MR-625 | 6" | 2.5 mm | 12,000 | PSA | 1.87 lbs | 0.28 | 17 | 83 dB | 3.3 |

SGV: Self-Generating Vacuum

| Part Number | Size | Orbit | RPM | Pad Face | Weight | НР | SCFM | Noise | Vib m/s ² |
|-------------|------|--------|--------|-----------------|----------|------|------|-------|----------------------|
| MR-3SGV | 3" | 2.5 mm | 12,000 | 6-Hole Grip | 1.3 lbs | 0.28 | 17 | 84 dB | 2.6 |
| MR-5SGV | 5" | 5 mm | 12,000 | Multi-Hole Grip | 1.85 lbs | 0.28 | 17 | 85 dB | 2.5 |
| MR-508SGV | 5" | 8 mm | 12,000 | Multi-Hole Grip | 1.85 lbs | 0.28 | 17 | 91 dB | 3.3 |
| MR-6SGV | 6" | 5 mm | 12,000 | Multi-Hole Grip | 1.94 lbs | 0.28 | 17 | 83 dB | 2 |
| MR-608SGV | 6" | 8 mm | 12,000 | Multi-Hole Grip | 2.2 lbs | 0.28 | 17 | 82 dB | 3.3 |

MR-SERIES SQUARE PNEUMATIC SANDERS

MR-Series Pneumatic Tools







NV: Non-Vacuum



SGV: Self-Generating Vacuum

CV: Central Vacuum

| Part Number | Model Number | Size | Orbit | RPM | Pad Face | Weight | HP | SCFM | Noise | Vib m/s ² |
|-------------|---------------------|---------|-------|--------|-----------------|--------|------|------|-------|----------------------|
| MR-38CV-1 | OS 383CV | 3" x 8" | 3 mm | 10,000 | Multi-Hole Grip | 2.1lbs | 0.24 | 16 | 75 dB | 3.3 |

NV: Non-Vacuum

| Part Number | Model Number | Size | Orbit | RPM | Pad Face | Weight | HP | SCFM | Noise | Vib m/s ² |
|-------------|---------------------|---------|-------|--------|----------|---------|------|------|-------|----------------------|
| MR-34 | _ | 3" x 4" | 3 mm | 10,000 | Grip | 1.5 lbs | 0.24 | 16 | 76 dB | 2.6 |

SGV: Self-Generating Vacuum

| Part Number | Model Number | Size | Orbit | RPM | Pad Face | Weight | HP | SCFM | Noise | Vib m/s ² |
|-------------|---------------------|---------|-------|--------|-----------------|---------|------|---------|-------|----------------------|
| MR-34DB | OS 343DB | 3" x 4" | 3 mm | 10,000 | Multi-Hole Grip | 1.6 lbs | 0.24 | 16 | 81 dB | 2.02 |
| MR-35SGV | OS 353DB | 3" x 5" | 3 mm | 10,000 | Multi-Hole Grip | 1.8 lbs | 0.24 | 16 | 84 dB | 2.3 |
| MR-38SGV | OS 383DB | 3" x 8" | 3 mm | 10,000 | Multi-Hole Grip | 2.1 lbs | 0.24 | a 16 17 | 85 dB | 2.8 |

DID YOU KNOW?

The MR-38CV-1, also known as a power block, is a great tool for block sanding. It straightens and flattens like a traditional hand block but leaves behind a scratch pattern like a 5" or 6" dual action sander, which doesn't require a great amount of effort to refine straight line scratches. This sander does it all with effortless guidance.



MR-Series Pneumatic Tools

1.25" MR-SERIES NON-VACUUM PNEUMATIC SANDERS

Precision-molded composite construction gives Mirka's MR-Series of 1.25" Round Pneumatic Sanders strength, durability, and reduced weight. The sanders' orbital motion makes spot repair and minor surface finishing easy to polish out.







MROS125



MROS150

| Part Number | Model Number | Size | Orbit | RPM | Pad Face | Weight | НР | SCFM | Noise | Vib m/s² |
|-------------|--------------|-------|-------|-------|----------|----------|------|------|-------|----------|
| MAOS130 | AOS 130NV | 11⁄4" | 3 mm | 8,500 | PSA | 1.32 lbs | 0.48 | 18 | 75 dB | 2.22 |
| MROS150 | ROS 150NV | 11/4" | 5 mm | 8,000 | PSA | 1.08 lbs | 0.15 | 15 | 71 dB | 2.33 |

3" MR-SERIES PNEUMATIC POLISHERS

Pneumatic Polishers make quick work of removing scratches when paired with wool or foam polishing pads. MR-Series polishers have reduced weight and sound for increased operator comfort.



MRAP-30



MR-30

| Part Number | Model Number | Size | Orbit | RPM | Pad Face | Weight | Watts | HP | SCFM | Noise | Vib m/s² |
|-------------|---------------------|------|-------|-------|----------|----------|-------|------|------|-------|----------|
| MRAP-30 | AP 300NV | 3" | 0 mm | 3,200 | Grip | 1.45 lbs | 298 | - | - | 76 dB | 1.34 |
| MR-30 | RP 300NV | 3" | 0 mm | 3,000 | Grip | 1.2 lbs | - | 0.28 | 17 | 81 dB | 1.4 |



BPA10825

Intelligent Battery max 12 V 2.5Ah

BPA10850 Intelligent Battery max 12 V 5.0Ah

Replacement batteries can be found on page 73.

DID YOU KNOW?

With Bluetooth and the myMirka® dashboard, you can easily monitor battery health status and available capacity. The Mirka* intelligent Li-ion battery allows a precise capacity measurement based on a coulomb counter.

It is possible to monitor individual cell voltage and, together with the coulomb counter, prolong the usage time. The firmware in the battery is upgradeable via the Bluetooth connection to the sander/polisher.

The **BPA10825** battery has 3 cells and charging time is approximately 45 minutes. The **BPA10850** battery has 6 cells and charging time is approximately 90 minutes.

PNEUMATIC TOOLS

Two-Handed Pneumatic Tools

The second handle adds stability and control while reducing operator fatigue - it can be removed when not needed. The large orbit allows you to cover a wide area in less time with aggressive sanding and polishing.

Constructed of precision-molded, moisture-resistant composites for strength and durability. A storage hanger and backing pad are included.







SGV: Self-Generating Vacuum



NV: Non-Vacuum



MROP: Random Orbital Polisher

TWO-HANDED POLISHERS

NV: Non-Vacuum

| Part Number | Model Number | Size | Orbit | RPM | Pad Face | Weight | HP | SCFM | Noise | Vib m/s ² |
|-------------|-------------------|------|-------|--------|----------|---------|------|------|-------|----------------------|
| MROP-312TH | ROP2 312NV | 3" | 12 mm | 10,000 | Grip | 2.6 lbs | 0.37 | 19 | 80 dB | 5.9 |
| MROP-512TH | ROP2 512NV | 5" | 12 mm | 10,000 | PSA | 2.7 lbs | 0.46 | 21 | 81 dB | 5.8 |

TWO-HANDED SANDERS

NV: Non-Vacuum

| Part Number | Model Number | Size | Orbit | RPM | Pad Face | Weight | HP | SCFM | Noise | Vib m/s² |
|-------------|--------------|------|-------|--------|----------|---------|------|------|-------|----------|
| MR-510TH | _ | 5" | 10 mm | 12,000 | PSA | 2.7 lbs | 0.46 | 21 | 85 dB | 3.4 |
| MR-610TH | _ | 6" | 10 mm | 12,000 | PSA | 2.8 lbs | 0.46 | 21 | 87 dB | 3.3 |

CV: Central Vacuum

| Part Number | Model Number | Size | Orbit | RPM | Pad Face | Weight | HP | SCFM | Noise | Vib m/s² |
|-------------|--------------|------|-------|--------|-----------------|---------|------|------|-------|----------|
| MR-610THCV | ROS2 610CV | 6" | 10 mm | 12,000 | Multi-Hole Grip | 2.9 lbs | 0.46 | 21 | 81 dB | 3.4 |
| MR-850THCV | ROS2 850CV | 8" | 5 mm | 10,000 | Multi-Hole Grip | 3.5 lbs | 0.46 | 23 | 77 dB | 4.8 |

SGV: Self-Generating Vacuum

| Part Number | Model Number | Size | Orbit | RPM | Pad Face | Weight | HP | SCFM | Noise | Vib m/s ² |
|-------------|---------------------|------|-------|--------|-----------------|---------|------|------|-------|----------------------|
| MR-610THSGV | ROS2 610DB | 6" | 10 mm | 12,000 | Multi-Hole Grip | 2.9 lbs | 0.46 | 21 | 81 dB | - |





Paint Cup System, 180-850ml, Filter Lid 125µm

| Part Number | Size | Pcs/pack |
|-------------|-------|----------|
| 9190170180 | 180ml | 50 |
| 9190170400 | 400ml | 50 |
| 9190170650 | 650ml | 50 |
| 9190170850 | 850ml | 50 |

The set includes:

- 50 liners and lids with a 125µm filter
- 20 stoppers
- 1 outer hard cup + 1 collar



Paint Cup System, 180-850ml, Filter Lid 190µm

| Part Number | Size | Pcs/pack |
|-------------|-------|----------|
| 9190172180 | 180ml | 50 |
| 9190172400 | 400ml | 50 |
| 9190172650 | 650ml | 50 |
| 9190172850 | 850ml | 50 |

The set includes:

- 50 liners and lids with a 190µm filter
- 20 stoppers
- 1 outer hard cup + 1 collar



UV Paint Cup System, 400-650ml, Filter Lid 125μm

| Part Number | Size | Pcs/pack |
|-------------|-------|----------|
| 9190171400 | 400ml | 50 |
| 9190171650 | 650ml | 50 |

This paint cup system, with the black liner and lid, is UV-resistant.

The set includes:

- 50 liners and lids with a 125µm filter
- 20 stoppers
- 1 outer hard cup + 1 collar



Replacement Paint Cups

| Part Number | Size | Pcs/pack |
|-------------|-------|----------|
| 9190173180 | 180ml | 2 |
| 9190173400 | 400ml | 2 |
| 9190173650 | 650ml | 2 |
| 9190173850 | 850ml | 2 |
| | | |

Outer cup with collar.



Filter Lids 125µm

| Part Number | Size | Pcs/pack |
|-------------|--------------------------|----------|
| 9190175021 | Lids for PCS 180ml | 50 |
| 9190175022 | Lids for PCS 400ml | 50 |
| 9190175023 | Lids for PCS 650 & 850ml | 50 |

Replacement Lids



Filter Lids 190µm

| Part Number | Size | Pcs/pack |
|-------------|--------------------------|----------|
| 9190175024 | Lids for PCS 180ml | 50 |
| 9190175025 | Lids for PCS 400ml | 50 |
| 9190175026 | Lids for PCS 650 & 850ml | 50 |

Replacement Lids

MIRKA ESSENTIALS PAINT CUPS



Paint Cup Accessories

| | Part Number | Size | Pcs/pack |
|-----|--------------------|--------------------------------------|----------|
| NEW | Paint Shaker Lid | Paint Cup Lid for Shaker | 1 |
| | 9190175015 | Stoppers for Mirka Paint Cup Systems | 20 |



Dispenser for Paint Cups, 180-400ml OR 650-850ml cups

| Part Number | Size | Pcs/pack |
|-------------|-----------|----------|
| 9190175012 | 180-400ml | 1 |
| 9190175013 | 650-850ml | 1 |

Dispenser for Paint Cup Lids

| Part Number | Size | Pcs/pack |
|-------------|--------------|----------|
| 9190175010 | For all lids | 1 |

PCS SPRAY GUN ADAPTER VERSIONS

PCS Spray Gun Adapters

Stainless steel adapters connect the paint cup to the spray gun. All parts of the adapter are corrosion-resistant to both paint and thinner.

To order the correct adapter, find your spray gun on the Adapter Overview and reference the adapter shown at the top of the marked column.



PCS SPRAY GUN ADAPTER VERSIONS

PCS Spray Gun Adapter – Overview

| Mark | Model | PCS Spray Gun Adapter |
|----------|--|--|
| | Performax 05-100 primer | 12 |
| ACCU | 10/12S/19/19C | 13 |
| SPRAY | 7/07HS/ | 17 |
| | 10g/10gp | 17 |
| | 7100163226 | M2 |
| | Super Fura34 2015ECO&T | 16 16 |
| AERO | 2100ECO&T | 16 |
| METAL | Victoria 92 | 16 |
| | 2016 | 16 |
| ANI | F1-S | 2 |
| AINI | R1 mini | 19 |
| | Star QUL EVO4014/4018 | 1 |
| | M-Star | 1 |
| ASTRO | ECO-S/SX | 1 |
| | Quantum Ultra | 1 |
| | ECO-SSP | 13 |
| ACTURO | ECO-S /ECO-SX | 1 |
| ASTURO | ECO-SSP | 13 |
| | Gravity series Gravity series | 16 1 |
| | 6900 series | 1 |
| | Leonardo 6865/6872/6913/6914/6915/6918 | 12 |
| ATD | 6845mini | 7M |
| | 6900mini | 7M |
| | 6910mini | 16 |
| | 600 side cup MGI1.8 primer | 20 |
| | 630/95G | 2 |
| | BBR /M1-G | 2 |
| | 95/95SL/95SLV | 13 |
| | SV100 Siphon | 13 |
| BINKS | Model7/2001/2001V/ 2001SS | 13 |
| | Match1/1SL/Featherlite | 13 |
| | SV100 Gravity | 18 |
| | BluePoint BLP 10/13/15/16/18 BHV | 21 21 |
| | SV-50 Pro Series | 21 |
| CRS | Mini | 7M |
| | AB17G | 1 |
| DART | H827A | 1 |
| PRODUCTS | H881A | 1 |
| | H2000MG mini CVi 522G /620G/620GW | 7 2 |
| | DRD / EXL620G | 2 |
| | FLG 4 gravity | 2 |
| | FLG 615/635/643/645/647WB/648/651G/654/691/695 | 2 |
| | GFG 5/516/517/618/670Plus | 2 |
| | GTI family/DV1 | 2 |
| | JGA535G/635G PRI / TEKNA | 2 |
| 0.51 | Compact 506/510 gravity | 2 |
| DEVIL | Slg | 5 |
| BISS | FLG 4 siphon | 13 |
| | FLG 606/626 | 13 |
| | Compact 507 | 13 |
| | Compact 506/510 siphon Compact mini | 13 14 |
| | Sri family | 14 |
| | FUN, Gravity/JGX | 20 |
| | StatingLine Std. | 21 |
| | FinishLine Master Kit Std. | 21 |
| | LT200/LT300 | 1 |
| GRACO | Delta GF LT100 mini | 2 7 |
| UNACU | | |
| | Airnro sinhon | 13 |
| | Airpro siphon FinishPro HVLP | 13 13 |
| ITALCO | | |
| ITALCO | FinishPro HVLP Mini W400/W400LV/WR400 | 13 7M 1 |
| ITALCO | FinishPro HVLP Mini W400/W400LV/WR400 LPA94/ LPH440 | 13 7M 1 1 |
| ITALCO | FinishPro HVLP Mini W400/W400LV/WR400 LPA94/ LPH440 LPH400 Primer | 13 7M 1 1 |
| | FinishPro HVLP Mini W400/W400LV/WR400 LPA94/ LPH440 LPH400 Primer LPH400LV/LVB/LVX | 13 7M 1 1 1 1 |
| ANEST | FinishPro HVLP Mini W400/W400LV/WR400 LPA94/ LPH440 LPH400 Primer LPH400LV/LVB/LVX VX929 | 13 7M 1 1 1 1 1 |
| | FinishPro HVLP Mini W400/W400LV/WR400 LPA94/ LPH440 LPH400 Primer LPH400LV/LVB/LVX VX929 VXL949 Primer | 13 7M 1 1 1 |
| ANEST | FinishPro HVLP Mini W400/W400LV/WR400 LPA94/ LPH440 LPH400 Primer LPH400LV/LVB/LVX VX929 | 13 7M 1 1 1 1 1 1 |
| ANEST | FinishPro HVLP Mini W400/W400LV/WR400 LPA94/ LPH440 LPH400 Primer LPH400LV/LVB/LVX VX929 VXL949 Primer Supernova LS400 | 13 7M 1 1 1 1 1 1 1 1 |

| Mark | Model | PCS Spray Gun Adapter |
|----------------|---|--------------------------|
| ANIFCT | W300/W300LV | 16 |
| ANEST IWATA | LPH300 W100G/RG3L mini | 16 20 |
| IVVAIA | LPH100/50 mini | 20 |
| | MTPG 14 | 6 |
| MATCO | MTPGHV 13/15/17/19 | 6 |
| | MTPGHE 13/15 | 12 |
| | 700/800i | 13 |
| OPTIMA | 500/500i 800/800C/800L | 17 17 |
| | Euro 900L | 17 |
| | 4100 GTO | 9 |
| | 4400 Xtreme | 9 |
| | 4500 Xtreme | 9 |
| | 403G/433G /434G/444G /450G | 10 |
| SAGOLA | 3300G 4100G/4200G | 10 10 |
| | Mini Extreme | 10 |
| | Classic pro | 10 |
| | Classic LUX | 16 |
| | 475MINI | 19 |
| | Jet B | 1 |
| | Jet B NR-92 | 1 |
| | Jet B NR-95 QCC family | 1 3 |
| | QCC 5500 series | 3S |
| | Rosca | 5 |
| | KL-Primer | 10 |
| | MCB-93 | 10 |
| | Minijet 4 | 11 |
| | Minijet 3000B | 11 |
| SATA | KLC-B/P/RP LM-92 | 12 12 |
| SAIA | LM2000B | 12 |
| | LM2000K | 12 |
| | MCB Primer | 12 |
| | MCB 90 | 12 |
| | Jet90 | 12 |
| | Jet90-2RP Jet90-2 HVLP | 12 12 |
| | NR2000 RP | 12 |
| | NR2000 HVLP | 12 |
| | Dekor 2000 | 19 |
| | Minijet 1/2/3 | 19 |
| | FX200 | 1 |
| | FX300 HVLP Cobalt HVLP(EU) | 1 2 |
| | 775 Siphon | 13 |
| | Razor Siphon | 13 |
| | Cobalt HVLP(US) | 18 |
| CILABO | Razor primer | 18 |
| SHARP | SGF98 | 18 |
| | Platinum HVLP Titanium T1 HVLP | 18 18 |
| | Titanium 11 HVLP | 18 |
| | Finex FX1000 | 21 |
| | | |
| | Finex FX2000 Convential Finex FX3000 | 21 21 |
| | BF590 Siphon | 13 |
| | BF595 Siphon | 13 |
| | BF900EXC14 | 18 |
| SNAP-ON | BF700HPG15 | 18 |
| 5 | BF900EXC3 | 18 |
| | EXCG3 /EXC6 Saber II BF814A | 18 18 |
| | Blue point BF350/813/815 | 18 |
| TITAN | Vaper 1.4/1.7mm | 1 |
| U-POL | Maximum | 1 |
| WALCOM | GEO/ EGO | 7 |
| W. LCOW | Genesi | 12 |
| | Slim Kombat 861C | E 1 |
| | 863 | 1 |
| | 881H | 1 |
| WARWICK | H881W | 1 |
| | 904H | 1 |
| | 827-C | 12 |
| | 878 | 12 |

MIRKA ESSENTIALS TAPES + FILMS



9190113001 Foam Tape Type: Masking Tape .5" x 164', 1/Roll



9190165001 Foam Tape Premium Type: Masking Tape .79" x 164', 1/Roll



9190167001 Lifting Tape Perforated Type: Masking Tape 2" x 32.8', 1/Roll



9190220001 Black Cloth Tape Type: Specialty Tape 2" x 164', 1/Roll



9190221001 Flexi No Edge Blending Tape Type: Masking Tape .59" x 82', 1/Roll



9190222001 DUO Masking Tape Type: Specialty Tape 3" x 65.6', 1/Roll



9190320001 Grey Acrylic Double-Sided Tape Type: Fastening Tape .24" x 59', 1/Roll



9190320002 Grey Acrylic Double-Sided Tape Type: Fastening Tape .47" x 59', 1/Roll



9190320003 Grey Acrylic Double-Sided Tape Type: Fastening Tape .87" x 59', 1/Roll



9190320005 Orange Fine Line Tape Type: Masking Tape .12" x 108', 1/Roll



9190320006 Orange Fine Line Tape Type: Masking Tape .24" x 108', 1/Roll



9190320007 Orange Fine Line Tape Type: Masking Tape .47" x 108', 1/Roll



9190320008 Grey Number Plate Tape Type: Fastening Tape .24" x 16.4', 1/Roll



9191004801 100°C White Line Type: Masking Tape 1.88" x 164'



9191003601 100°C White Line Type: Masking Tape 1.4" x 164'



9191001801 100°C White Line Type: Masking Tape .7" x 164'



9191251801 Masking Tape 120° Yellow Line .71" x 180', 48/Pack



9191252401 Masking Tape 120° Yellow Line .94" x 180', 36/Pack



9191253601 Masking Tape 120° Yellow Line 1.42" x 180', 24/Pk



9191254801 Masking Tape 120° Yellow Line 1.89" x 180', 18/Pk



9190110017 Masking Film Premium 12' x 400' x 14μ, Blue



9190110018 Masking Film Premium 16' x 350' x 14μ, Blue



Masking Film Premium 20' x 250' x 14μ, Blue







DUST-EXTRACTORS

HEPA Certified to meet EPA Renovation, Repair, and Painting (RRP) Guidelines.



DE-1230-PC Dust Extractor - HEPA 15¼" x 22¼" x 22¼"



DE-1230-AFC Dust Extractor - HEPA 151/4" x 221/4" x 221/4" Automatic Filter Cleaning

| Part Number: | Volts | Frequency | Air Flow | Vacuum | Volume | Weight | Power Input | Sound Pressure | Noise, Lpa |
|--------------|-------------|-----------|----------|----------|--------------|--------|-------------|----------------|------------|
| DE-1230-PC | 110 - 120 ~ | 60 Hz | 159 cfm | 250 mbar | 8 gal (30 l) | 32 lbs | 1000 W | 62 dB | 59 dB |
| DE-1230-AFC | 110 - 120 ~ | 60 Hz | 159 cfm | 250 mbar | 8 gal (30 l) | 32 lbs | 1000 W | 62 dB | 59 dB |

DUST-EXTRACTOR FEATURES

Filter Cleaning

Choose from Automatic Filter Cleaning (AFC) or Push & Clean (PC) models.

Easily Accessible Flat Filter

Filter can easily be reached through an opening in the back.

Hose Storage -

The hose is always ready to use.

Storage -

The flat top gives space for storage cases.

The HEPA (High Efficiency Particulate Air) filter improves filtration.

High Volume Container -

8 gallons for applications where a lot of material is extracted.

Large Wheels

Easy maneuverability on uneven surfaces.

High Performance Motor & Turbine

1000 W motor and 1-stage turbine creates 250 mbar pressure and 4500 l/min airflow.

AutoStart Function -

Dust Extractor runs only when the power tool is running.

3 LAYERS OF DUST PROTECTION AND FILTRATION



DE-FDB Fleece dust bag



DE-FILT Flat filter



DE-HEPA HEPA filter





Mirka® Modular Trolley – Pro Model

Introducing the Modular Trolley – Pro Model, a mobile workbench designed to streamline the body shop workflow. Built with efficiency and organization in mind, it brings tools and supplies directly within reach, making every task faster, easier, and more ergonomic.

Its professional layout organizes essential tools and materials in a compact, accessible format, reducing unnecessary movement and minimizing downtime. Dust extractor, hoses, and tools are all contained so technicians can easily move the workbench to the vehicle or workstation, wherever it's needed.

Keeping everything organized and ready for immediate use supports a productive workday from start to finish.

FEATURES AND BENEFITS:

- Moveable hose arm with tool hooks
- Large horizontal drawer for hand tools
- Small, medium, and large vertical soft-close drawers
- Configurable tool board with abrasive storage trays
- Rubberized workbench desk
- Dedicated space for dust extractor
- Spray gun and aerosol can holders with magnetized quick-lock function
- Various hooks for tools, cable, and other items
- Trash bag holder

| Part Number: | Description: | Width | Height | Depth | Weight |
|--------------|--|-------|--------|-------|---------|
| 9194013011 | Modular Trolley - Pro Model with attachments | 51" | 78" | 20 ½" | 243 lbs |



Dust-Free Modular Trolley Pro Systems

Modular Trolley – Pro Model Dust-Free Systems completely outfit the mobile workbench so the work of the professional body shop can begin. Included are the trolley, an electric or pneumatic power tool, Push-to-Clean dust extractor with hose, hand block kit with hose, and dual tool adapter.

Dust-Free Modular Trolley Pro System - Electric



Dust-Free Modular Trolley Pro System - Pneumatic

MIDKE



| Part Number: | Description: | Tool Type | Dust Extractor | Hose | Additional Accessories |
|--------------|-----------------------------|----------------------------|-------------------|---------------------------|--|
| MUSDF-6TPSE | Modular Trolley (Electric) | 6" DEROS 650XCV 5 mm orbit | DE-1230-PC | 19.7' Hose w/ 110v Cable | T-LOC case; Sleeve for hose, Sanding block kit with hose, Dual tool adapter |
| MUSDF-6TPSP5 | Modular Trolley (Pneumatic) | 6" PROS 650CV 5 mm orbit | DE-1230-PC | 18' Hose w/ Coaxial Cable | Pneumatic box, Sanding block kit with hose, Dual tool adapter |
| MUSDF-6TPSP8 | Modular Trolley (Pneumatic) | 6" PROS 680CV 8 mm orbit | DE-1230-PC | 18' Hose w/ Coaxial Cable | Pneumatic box, Sanding block kit with hose, Dual tool adapter |

DUST-FREE SYSTEMS

Basic Dust-Free Systems include the basics to get started with dust-free sanding. Choose a 5" or 6" electric or pneumatic tool to accompany the Push-to-Clean dust extractor with hose.

Dust-Free Basic Systems – Electric



Dust-Free Basic Systems – Pneumatic



| Part Number: | Description: | Tool Type | Dust Extractor | Hose | Additional Accessories |
|--------------|--------------------------|----------------------------|-------------------|---------------------------|-----------------------------|
| MUSDF-5BSE | Basic System (Electric) | 5" DEROS 550XCV 5 mm orbit | DE-1230-PC | 19.7' Hose w/ 110v Cable | T-LOC case; Sleeve for hose |
| MUSDF-6BSE | Basic System (Electric) | 6" DEROS 650XCV 5 mm orbit | DE-1230-PC | 19.7' Hose w/ 110v Cable | T-LOC case; Sleeve for hose |
| MUSDF-5BSP5 | Basic System (Pneumatic) | 5" PROS 550CV 5 mm orbit | DE-1230-PC | 18' Hose w/ Coaxial Cable | Pneumatic box |
| MUSDF-6BSP5 | Basic System (Pneumatic) | 6" PROS 650CV 5 mm orbit | DE-1230-PC | 18' Hose w/ Coaxial Cable | Pneumatic box |
| MUSDF-6BSP8 | Basic System (Pneumatic) | 6" PROS 680CV 8 mm orbit | DE-1230-PC | 18' Hose w/ Coaxial Cable | Pneumatic box |

The **handle system** transforms the dust extractor into a central unit that contains the power sander, hose, and tool case. Maneuvering your system becomes smoother than ever as the handle adds stability and control. Just attach, grip, and glide!

Dust-Free Handle Systems – Electric



Dust-Free Handle Systems – Pneumatic



| Part Number: | Description: | Tool Type | Dust Extractor | Hose | Additional Accessories |
|--------------|----------------------------|----------------------------|-------------------|------------------------------|--|
| MUSDF-6HSE | Handle System (Electric) | 6" DEROS 650XCV 5 mm orbit | DE-1230-PC | 19.7' Hose w/ 110v Cable | T-LOC case; Sleeve for hose, Tool case fastening system |
| MUSDF-6HSP5 | Handle System (Pnueumatic) | 6" PROS 650CV 5 mm orbit | DE-1230-PC | 18' Hose w/ Coaxial Cable | Pneumatic box, Tool case fastening system |
| MUSDF-6HSP8 | Handle System (Pnueumatic) | 6" PROS 680CV 8 mm orbit | DE-1230-PC | 18' Hose w/ Coaxial Cable | Pneumatic box, Tool case fastening system |
| MUSDF-5HSE | Handle System (Electric) | 5" DEROS 550XCV 5 mm orbit | DE-1230-PC | 19.7' Hose w/ 110v Cable | T-LOC case; Sleeve for hose, Tool case fastening system |
| MUSDF-5HSP5 | Handle System (Pnueumatic) | 5" PROS 550CV 5 mm orbit | DE-1230-PC | 18' Hose w/ Coaxial Cable | Pneumatic box, Tool case fastening system |

DUST-FREE SYSTEMS

Workstation Dust-Free Systems keep your workspace optimized with a compact structure that holds tools, cables, abrasives, and more. The sturdy metal workstation fastens securely to the top of the dust extractor, creating a mobile system that includes the power sander, dust extractor, a hand block and more. The dual tool adapter means you can effortlessly switch from power sanding to hand sanding while remaining dust-free.

Dust-Free Work Station System – Electric



Dust-Free Work Station Systems – Pneumatic



| Part Number: | Description: | Tool Type | Dust Extractor | Hose | Additional Accessories |
|--------------|---------------------------------|----------------------------|-------------------|---------------------------|---|
| MUSDF-6WSE | Work Station System (Electric) | 6" DEROS 650XCV 5 mm orbit | DE-1230-PC | 19.7' Hose w/ 110v Cable | T-LOC case; Sleeve for hose, Sanding block kit with hose, Dual tool adapter, Tool case fastening system |
| MUSDF-6WSP5 | Work Station System (Pnuematic) | 6" PROS 650CV 5 mm orbit | DE-1230-PC | 18' Hose w/ Coaxial Cable | Pneumatic box, Sanding block kit with hose, Dual tool adapter, Tool case fastening system |
| MUSDF-6WSP8 | Work Station System (Pnuematic) | 6" PROS 680CV 8 mm orbit | DE-1230-PC | 18' Hose w/ Coaxial Cable | Pneumatic box, Sanding block kit with hose, Dual tool adapter, Tool case fastening system |

Dust-Free Trolley Systems have a bottom shelf that holds the dust extractor and rugged swivel wheels to provide unmatched mobility across your workshop or job site. Built-in hooks and shelves are designed for keeping abrasives, tools, and polishing supplies organized and within reach. The system includes the dust extractor and a power sander along with a hand sanding block. With the dual tool adapter, you can remain dust-free whether power sanding or hand sanding.

Dust-Free Trolley System – Electric



Dust-Free Trolley Systems – Pneumatic



| Part Number: | Description: | Tool Type | Dust Extractor | Hose | Additional Accessories |
|--------------|----------------------------|----------------------------|-------------------|---------------------------|--|
| MUSDF-6TSE | Trolley System (Electric) | 6" DEROS 650XCV 5 mm orbit | DE-1230-PC | 19.7' Hose w/ 110v Cable | T-LOC case; Sleeve for hose, Sanding block kit with hose, Dual tool adapter |
| MUSDF-6TSP5 | Trolley System (Pnuematic) | 6" PROS 650CV 5 mm orbit | DE-1230-PC | 18' Hose w/ Coaxial Cable | Pneumatic box, Sanding block kit with hose, Dual tool adapter |
| MUSDF-6TSP8 | Trolley System (Pnuematic) | 6" PROS 680CV 8 mm orbit | DE-1230-PC | 18' Hose w/ Coaxial Cable | Pneumatic box, Sanding block kit with hose, Dual tool adapter |

DUST-FREE SYSTEMS

Solutions Cart Systems keep you organized, efficient, and ready for dust-free sanding. This all-in-one, integrated system has a dust extractor and a power sander along with a hand sanding block, plus all the hoses and connectors needed. Engineered for efficiency, the cart is designed to keep everything at your fingertips, including a locking cabinet and two drawers plus a recessed work surface. The mobile platform is easy to move, while premium casters with foot pedal wheel locks ensure stability.

Dust-Free Cart System – Electric



Dust-Free Cart Systems – Pneumatic



| Part Number: | Description: | Tool Type | Dust Extractor | Hose | Additional Accessories |
|--------------|-------------------------|----------------------------|-------------------|---------------------------|--|
| MUSDF-6CSE | Cart System (Electric) | 6" DEROS 650XCV 5 mm orbit | DE-1230-PC | 19.7' Hose w/ 110v Cable | T-LOC case; Sleeve for hose, Sanding block kit with hose, Dual tool adapter |
| MUSDF-6CSP5 | Cart System (Pnuematic) | 6" PROS 650CV 5 mm orbit | DE-1230-PC | 18' Hose w/ Coaxial Cable | Pneumatic box, Sanding block kit with hose, Dual tool adapter |
| MUSDF-6CSP8 | Cart System (Pnuematic) | 6" PROS 680CV 8 mm orbit | DE-1230-PC | 18' Hose w/ Coaxial Cable | Pneumatic box, Sanding block kit with hose, Dual tool adapter |

Dust-Free LEROS Complete Systems

With a LEROS Dust-Free System, everything is ready for clean, efficient wall and ceiling sanding. Choose the full-size LEROS or the shorter LEROS-S. The Automatic Filter Clean (AFC) dust extractor, hose with sleeve, and a handle extension are included in the kit.





| Part Number: | Description: | Tool Type | Dust Extractor | Hose | Additional Accessories |
|------------------------|-----------------------|--|-------------------|----------|--|
| MIW950- DE1230AFC-4 | LEROS Complete System | 9" LEROS 950XCV 57" with cable, 5 mm orbit | DE-1230-AFC | 13' Hose | Sleeve for hose, Cable, Carry bag, Handle extension |
| MIW951- DE1230AFC-4 | LEROS Complete System | 9" LEROS-S 950XCV 35" with cable, 5 mm orbit | DE-1230-AFC | 13' Hose | Sleeve for hose, Cable, Carry bag, Handle extension |

ABRASIVE TRIAL KITS

Set your dust-free sanding system up for success with **trial kits** in a variety of proven Mirka abrasive brands. Choose from some of the most popular dust-free abrasives to try in different grits so you can discover what works best for your shop.

Iridium[™] **Dust-Free Trial Kit**



| Part Number: | Description: | 80 | 180 | 320 |
|--------------|----------------------------------|----|-----|-----|
| MUSDF-IRKIT | Iridium™ 6" disc | • | • | • |
| | Iridium™ Perf-Roll 2.75" x 33.5' | • | • | • |

Net Dust-Free Trial Kit



| Part Number: | Description: | 80 | 180 | 320 |
|--------------|----------------------------------|----|-----|-----|
| MUSDF-NETKIT | Abranet® ACE 6" disc | • | • | • |
| | Autonet® Perf-Roll 2.75" x 33.5' | • | • | • |

OSP Dust-Free Trial Kit



| Part Number: | Description: | Step 1 | Step 2 | Step 3 | Step 4 |
|--------------|-----------------------------|-----------|-----------|-----------|-----------|
| | OSP 6" disc | • | • | • | • |
| MUSDF-OSPKIT | OSP Perf-Roll 2.75" x 33.5' | • | • | • | |

Galaxy Dust-Free Trial Kit



| Part Number: | Description: | 80 | 180 | 320 |
|--------------|--------------------------------|----|-----|-----|
| MUSDF-GXYKIT | Galaxy 6" disc | • | • | • |
| | Galaxy Perf-Roll 2.75" x 33.5' | • | • | • |

Mirka° Hose Carrying Bag 🗕

After a day of dust-free sanding, the last thing you want is dust in your vehicle! With your hose contained in a Mirka® Hose Carrying Bag, it is not only easy to transport but also keeps your van and your tools clean and dust-free. The bag can also be used to transport other surface finishing supplies. Fits all Mirka hoses.

Size: 21"L x 10"W x 18.5"H.

Part number 8999899111



DUST EXTRACTOR ACCESSORIES



MIE9017211 14' MIE9016811 21' MIE9016911 34' Replacement Cords



DE-1200PB Pneumatic box



DE-FDB Fleece dust bag for DE-1230 vacuums, 5/Pkg.



DE-FILT Filter Element



DE-HEPA HEPA filter element



MIN6532011 Mirka Case T-LOC 15.7" x 11.8" x 6.2"



MIN6529211 Electric Sander Cord/Hose Straps, 6/Pkg.



DE-HANDLE Handle extension



MV-912PB Pneumatic Control Box for MV-912



MV-412FE Filter Element for MV-912



DE-TCFS Tool case fastening system



MV-912DB Fleece Dust Bag for MV-912, 5/Pkg.



MV-CLEANKIT for Mirka Dust Extractors



DE-MCF Motor Cooling Filter



8999899111 Carry Bag for Mirka Hose, Gray

HOSES + HOSE CONNECTIONS



MV-412HA Vacuum Hose with Coaxial 1" x 18'



MV-HA33 Vacuum Hose with Coaxial 1" x 33'



MIN6519411 Vacuum Hose & Adapter 1" x 13', 1/Pkg.



MIN6519211 Vacuum Hose & Adapter 1" x 33', 1/Pkg.



91100-A Hose for Hand Block 3/4" x 13'



MIE6515911 121/21 MIE6515921 19' MIE6515931 32' Sleeve for Hose and Cable



MIE6515711US Mirka Sleeve + Cable 110V + Hose 19.7' US, 1/Pkg.



MIE6515611US Mirka Sleeve + Cable 110V + Hose 32.8' US, 1/Pkg.



MPA0412 **ROS Vac Hose** 1.1" x 5.9'



MV-412DOK Vacuum Dual Operator Kit Allows use of two sanders with one dust extractor



MV-DOF-A Dual Y Air Supply Fitting



MV-DOF-V Dual Y Vacuum Fitting



MV-412HA-ADAP Adapter & Vacuum Hose 1" x 19.7"



8992515411 Adapter for DEROS/PROS Sanders 1" Soft



8992515611 Vacuum Hose Adapter 11/4"/2.12"



8391111211 Connector Air Inlet for Hand Block 3/4" / 3/4"



ACCESSORIES

HAND SANDING TOOLS + ACCESSORIES



AF4417 Grip Faced DuraBlock Hand Sanding Block 2%" x 51/2"



AF4418 Grip Faced DuraBlock Hand Sanding Block 25/8" x 11"



AF4419 Grip Faced DuraBlock Hand Sanding Block 2%" x 16"



AF44A

Hand Sanding Block Kit 6-Piece PSA/Plain, 1/Pkg.



AF44HL Hand Sanding Block Kit 7-Piece Grip, 1/Pkg.



DHP34 3" x 4" Dual Density Pad



103DGHP Hand Pad 3" Grip w/Center Hole



105HPGG8 Hand Pad 5" x 1/8" Grip w/Strap



105HPHRG Hand Pad 4%" Grip Half-Round



106HPHRG Hand Pad 5%" Grip Half-Round



121-002 Hand Sanding Block 2.5" x 5" x 5%" Plain



135G Hand Pad 3"x5" Grip



150G Hand Pad 5" Grip



HB-39 Handy Sanding Block 3" x 9", Grip, 55H



HB-39KIT Handy Block Kit 3" x 9" Grip Asst., 55H, w/Hose



KITOOROUND Roundy Kit, 1/Pkg



91402 Medium, Grip Faced Multi-Hole Vacuum Block 2¾" x 5"



91502 Stiff, Grip Faced Multi-Hole Vacuum Block 2¾" x 7½"



MVHB35 Grip Faced, Multi-Hole Vacuum Block, 2¾" x 5"



MVHB38 Grip Faced, Multi-Hole Vacuum Block, 2¾" x 8"



Multi-hole vacuum block with four grip-faced attachments (Convex, Concave, Slightly Concave and Flat), 2¾" x 8"



9116F Flexible Grip Faced, Multi-Hole Vacuum Block, for convex and concave shapes 2¾" x 16½"



9116R Rigid Grip Faced, Multi-Hole Vacuum Block, for straight sided shapes 2¾" x 16½"



9190143011 Roundy Dust-Free Hand Block, 1/Pkg



9300 Deco Sander - A flat, dust-free sanding head connects to a telescopic tube via flexible joint that allows it to sit flat against walls and ceilings. 2¾" x 8" Grip 113H, 1/Pkg.

89





1079H-R .79" Backup Pad Hard, PSA, with Twist-Lock



1125G 11/4" Backup Pad Medium, Grip 1/4 - 20 thread



1125H-R 11/4" Backup Pad Hard, PSA, with Twist-Lock Attachment



1125S-R

Attachment

11/4" Backup Pad

Soft, PSA, with Twist-Lock



1125SG-R 11/4" Backup Pad Soft, Grip, with Twist-Lock Attachment





1132-R 11/4" Backup Pad Soft, PSA, Quick-Lock CPD



912SGV 2" Backup Pad Soft, Grip, Quick-Lock



102GG 2%" Backup Pad Medium, Grip 5/16 - 24 thread



913G 3" Backup Pad Medium, Grip 1/4 - 20 thread



913GV 3" Backup Pad Medium, Grip, Multi-Hole 1/4 - 20 thread





913GV-A 3" Backup Pad Grip, Multi-Hole w/adapters. For common sanding tools



8294791211 3" x 1/4" Backup Pad Medium, 6-Hole, Grip



8294791311 3" x 1/4" Backup Pad Medium, Grip



103 31/2" Backup Pad Stiff, PSA 5/16 - 24 thread



103GG 31/2" Backup Pad Stiff, Grip 1/16 - 24 thread



103HD 31/2" Backup Pad Heavy-Duty, PSA 5/16 - 24 thread



105 5" Backup Pad Medium, PSA 5/6 - 24 thread



105B 5" Backup Pad Medium, PSA 5∕16 - thread



105G 5" Backup Pad Medium, Grip % - thread



105GG 5" Backup Pad Medium, Grip, J Hook 5/16 - 24 thread



105GGP 5" Backup Pad Medium, Grip, J Hook % x 24 thread



105GV 5" Backup Pad Medium, 5-Hole Grip, 5/16 - 24 thread



105GVBD 5" Backup Pad Multi-Hole Grip for Black and Decker 5" electric tool



105H 5" Backup Pad Medium, PSA, Hardened Shank, % - 24 thread



105HD 5" Backup Pad Hard, Heavy-Duty, PSA



105HDGP 5" Backup Pad Hard, Grip, Heavy-Duty, Palm Hook, % - 11 thread



5" Backup Pad Medium with Flexible Edge, PSA, 5/16 -24 thread

105P



105PG 5" Backup Pad Medium with Flexible Edge, Grip, 5/6 - 24 thread



105S 5" Backup Pad Soft, PSA 5/16 - 24 thread




105SG 5" Backup Pad Soft, Grip 5/16 - 24 thread

69



105SGV 5" Backup Pad Soft, 5-Hole, Grip % - 24 thread



105V 5" Backup Pad Medium, 5-Hole, PSA 5/16 - 24 thread




915GV 5" Backup Pad Multi-Hole, Grip 5/6 - 24 thread



915GV28 * 5" Backup Pad Medium, Multi-Hole, Grip 5/16 - 24 thread



915GV28-130G 5" Backup Pad Medium, Multi-Hole, Grip 5/6 - 24 thread. Allows for use of 5" abrasives on 6" sander



915SGV 5" Backup Pad Soft, Multi-Hole



915SGV28 * 5" Backup Pad Soft, Multi-Hole, Grip 5/6 - 24 thread



MPADBU-5 5" Backup Pad Grip



106 6" Backup Pad Medium, PSA 5/16 - 24 thread



106GG 6" Backup Pad Medium Grip 5/6 - 24 thread



106GV 6" Backup Pad Medium, 6-Hole, Grip % - 24 thread



106P 6" Backup Pad Flexible Edge, PSA 5/16 - 24 thread



106S 6" Backup Pad Soft, PSA 5/16 - 24 thread



106SG 6" Backup Pad Soft, Grip 5/16 - 24 thread




106SGV 6" Backup Pad Soft, 6-Hole, Grip 5/16 - 24 thread




906GV 6" Backup Pad Medium, 16-Hole Plenum Vacuum, Grip 5/16 - 24 thread



916**G**V 6" Backup Pad Medium, Multi-Hole, Grip % - 24 thread



916GV48* 6" Backup Pad Medium, 48-Hole, Grip 5/6 - 24 thread



916SGV 6" Backup Pad Soft, Multi-Hole, Grip 5/16 - 24 thread



916SGV48 * 6" Backup Pad Soft, Multi-Hole, Grip 5/16 - 24 thread



MPAD-6FP 6" Backup Pad Soft, PSA, % - 11 thread



MPADBU-6 6" Backup Pad Grip



916GVMF 6" Backup Pad Multifit, Grip, 5/16" thick



MPADBU-7 7.875" Backup Pad Grip



108 8" Backup Pad PSA, % - 11 thread



108GG 8" Backup Pad Grip, % - 11 thread



108GV 8" Backup Pad Grip, 8-Hole



108M5 8" Backup Pad Stiff, PSA, 5-Hole, 5/6" Nat'l Detroit



908GV 8" Backup Pad Medium, Multi-Hole, Grip for MR-850THCV



908M5GV 8" Backup Pad Grip, 8" Ntl. Detroit



MIW9514312 9" Backup Pad Grip for Mirka® LEROS



MIW9564411 9" Backup Pad Grip, Styro for Mirka® LEROS



934 3" x 4" Backup Pad PSA, Tapers at the top



934GV 3" x 4" Backup Pad Multi-Hole, Grip



934GV-E (electric) 3" x 4" Backup Pad 29-Hole, Grip



935GV 3" x 5" Backup Pad Multi-Hole, Grip w/pad saver



935GV-E (electric) 3" x 5" Backup Pad Multi-Hole, Grip, w/pad saver



938GV 3" x 8" Backup Pad Multi-Hole, Grip



938GV-E (electric) 3" x 8" Backup Pad Multi-Hole, Grip



963GV 4" x 6" x 6" Backup Pad Medium, Multi-Hole, Grip

INTERFACE PADS



1033 3" dia. 1/2" thick Grip



9133 3" dia. 3/8" thick Grip, 6-Hole



9135 3" x 5" 1/4" thick Multi-Hole Grip



9934 3" x 4" x 1/4" Grip, 33-Hole



8294750610 3" x 4" .24", Soft



8294751010 3" x 4" 4", Medium



1055F 5" dia. 1/4" thick Grip, 5-Hole



1055Y 4%" dia. 1" thick Grip, 5-Hole



9155 / 9155RP (1/Pkg) 5" dia. 3/8" thick Multi-Hole Grip



9155-5 5" dia. 1/4" thick Multi-Hole Grip



Groove Interface Pads

Now, precision sanding of grooves and indentations using a power tool is possible. Just tear off a segment of the Groove Interface that matches the width of the indentation to be sanded.

Place these on the sanding plate of a Mirka® DEOS 343XCV and attach the appropriate Abranet® or Abranet® Ace abrasive on top. Begin sanding and extracting dust for efficient, consistent results.

Part numbers: 8294750610 (soft), 8294751010 (medium)



INTERFACE PADS



91528 5" dia. ¾" thick Multi-Hole Grip



1066 6" dia. ½" thick Grip, 6-Hole



1066F 6" dia. ¼" thick Grip



1066SF 6" dia. 3/4" thick Grip, Soft Faced



9116-M 6" dia. 1/5" thick Net Interface, MIRLON



9166 / 9166RP (1/Pkg) 6" dia. 3/8" thick Multi-Hole Grip



9166-5 6" dia. ¾" thick Multi-Hole Grip



82S6001001 9" dia. 5/32" thick Net Interface



9199 9" dia. 1/8" thick Grip, 25-Hole



MIW9535611 9" dia. 1/8" thick Grip, 9-Hole, Styro



91495 / 91495RP (1/Pkg) 2¾" x 5" x %" Grip, Block, Multi-Hole



91505 / 91505RP (1/Pkg) 2¾" x 7¾" x ¾" Grip, Block, Multi-Hole



91663RP 4" x 6" x 6", ¼" thick 32-Hole

PROTECTOR PADS



9138 2¾" x 7¾" x 1%" Multi-Hole Grip



9947 3" dia. %" thick Multi-Hole Grip



99528 5" dia. 1/8" thick Multi-Hole Grip



9955 / 9955RP (2/Pkg) 5" dia. 1/8" thick Multi-Hole Grip



9956 / 9956RP (2/Pkg) 6" dia. 1/8" thick Multi-Hole Grip



9956-MF 6" dia. Multifit, Grip



9958 8" dia. 1/8" thick Multi-Hole Grip



9134 3" x 4" x 1/8" Multi-Hole Grip



9935 3" x 5" 1/8" thick Multi-Hole Grip



8295902011 4" x 6" x 6" Grip, 32-Hole



9999 9" dia. Grip, 25-Hole



9193500111 Black Dry Guide Coat 100g



9193600111 White Dry Guide Coat 100g



S-BLADE Shark Blade Denibbing Tool 2"×1"



SR-CDBOT Finessing Damper 1.5" x 1.5" x 3", 2 oz. (60mL)



MINF Denibbing Mini-File .79"x1.65", Fine/Coarse



M-9915G Microfiber Cleaning Cloth 15¾" x 15¾", Grey 2/pack



MPA0465 MR SGV Series Paper Dustbag Insert (10/pack / 9" x 17")



MPA0110 MR SGV Series Cloth Vacuum Bag (1 Pack / 9.25" x 18")



MRP-SGVB PROS SGV Series Fleece Dustbag (3 Pack / 8.5" x 12.5")



BPA10825 Intelligent Battery max 12 V 2.5Ah



BPA10850 Intelligent Battery max 12 V 5.0Ah



BCA108 Battery Charger **BCA108PC** Power Cord for charger (sold separately)



MPAD-QD Quick Disconnect Pad Adapter



DE-WSS Work Station Shelf for Dust Extractor



DE-WS Work Station for Dust Extractor



MAI-CART-912 Mirka Smart Cart / Solution Trolley



9190310111 **Dust Extractor Trolley**



MAI-STOOL-13 Mirka Bulldog Counter Stool, 2-Ring Swivel, 13.5" d cushion x 29.5" h x 21.25" w at base

Grit Comparison Chart

| MICRON | US CAMI | FEPA'P' | JAPAN JIS |
|--------|---------|---------|-----------|
| 500 | 36 | 36 | 36 |
| 430 | 40 | | |
| 425 | | 40 | |
| 350 | 50 | | 40 |
| 336 | | 50 | |
| 300 | | | 50 |
| 270 | 60 | 60 | |
| 260 | | | |
| 250 | | | 60 |
| 210 | | | 70 |
| 200 | | 80 | |
| 192 | 80 | | |
| 177 | | | 80 |
| 162 | | 100 | |
| 149 | | | 90 |
| 140 | 100 | | |
| 125 | | 120 | 100 |
| 116 | 120 | | |
| 100 | | 150 | 120 |
| 93 | 150 | | |
| 82 | 180 | 180 | 150 |
| 68 | 220 | 220 | 180 |
| 60 | | 240 | 240 |
| 52 | 240 | 280 | 280 |
| 46 | | 320 | 320 |
| 42 | 280 | | |
| 40 | | 360 | 360 |
| 35 | 320 | 400 | 400 |
| 30 | | 500 | |
| 28 | 360 | | 500 |
| 26 | | 600 | 600 |
| 22 | 400 | 800 | 700 |
| 18 | 500 | 1000 | 800 |
| 15 | 600 | 1200 | 1000 |
| 13 | | 1500 | 1200 |
| 10 | | 2000 | 1500 |
| 8 | | 2500 | 2000 |
| 7 | | 3000 | 2500 |
| 6 | | | |
| 5 | | 5000 | 3000 |
| 3 | | | 4000 |

All products shown in the catalog are P graded with a few exceptions. Abralon* (except J3), Galaxy, Gold Film 23-6NHF 800-1500, Iridium, Mini File Belts, Q.Silver® 2C-611 Series, SR discs, and Ultimax® Ligno are not P grits.

Index

| Abrasives | 3-24 | Jepuflex Antistatic Belts | 31 |
|-----------------------------------|-------|---|--------------|
| Abralon° | 4 | LEROS | 46, 63 |
| Abralon° J3 | 4 | LEROS-S | 46, 63 |
| Abranet* | 5, 65 | Marine Polishing Kit | 39 |
| Abranet® Ace | 6 | Ligno | 16 |
| Abranet® Ace HD | 6 | Masking Film | 58 |
| Abranet® Max Belts | 29 | Masking Tape | 58 |
| Abrasive Belts | 28-33 | Microstar [®] | 14 |
| Abrasive Trial Kits | 64 | Mini File Belts | 33 |
| Accessories | 66-72 | Mirlon [®] | 15 |
| Autonet® | | Mirlon Total® | 15 |
| Backup Pads | | Miscellaneous Accessories | |
| Bags, Vacuum | | Modular Trolley – Pro Model | 2, 60 |
| Basecut | | MR-Series Pneumatic Tools (CV, NV, SGV) | |
| Batteries | | Multifit | |
| Belt Joint Types | 31-32 | New Products | |
| Caratflex | | OSP | |
| Coarse Cut | | Paint Cups and Dispensers | |
| Cordless File Belt Sander (FBS-B) | | PCS Spray Gun Adapters | |
| Cordless Tools | • | Pneumatic Belt Sanders | |
| DEOS | | Pneumatic Tools | |
| DEOS Delta | | Polarshine* | |
| | | | |
| DEROS DE COOY | | Polarstar* SR | |
| DEROS RS 600X | • | Polish | |
| Dust Extractor Accessories | | Polishing Pads | |
| Dust Extractors | | Power Tools | |
| Dust-Free Sanding Systems | | Pro Finishing Solution | |
| Essentials | | PRO Iridium™ 1250 | |
| Fastening Tape | | Product Number Reference | |
| File Belt Sander (FBS-B) | · | PROS Pneumatic Tools (CV, NV, SGV) | |
| Film, Masking | | Protector Pads | |
| Galaxy | 8, 65 | Q.Silver [®] | 19 |
| Gold | 9 | Safety Warnings | 78 |
| Gold Film | 10 | Sanding Sponges | 20-22 |
| Gold ProFlex | 11 | Sanding Systems | 25-27, 59-64 |
| Gold Soft | 11 | Sica Closed Belts | 32 |
| Golden Finish | 26 | Sica Fine Stearate Belts | 32 |
| Goldflex Soft | 11 | Specialty Tape | 58 |
| Grinding Discs | 34-35 | Styro System | 23 |
| Grit Comparison Chart | | Surface Conditioning Belts | 33 |
| Guide Coat | 73 | Sustainable Mirka | 77 |
| Hand Sanding | 67 | Symbols | 1 |
| Hiolit [®] XO / JCA2A0 | 18 | Tapes + Film | 57 |
| Hiolit® JCA2A0 Belts | | Trolleys | |
| Hiolit° XO Belts | | Two-Handed Tools | |
| Hoses and Connections | | Ultimax [®] Belts | |
| Interface Pads | | Ultimax° Ligno | |
| Iridium™ | | Workstation | |
| Iridium™ SR | | WPF Pro | · |
| Jepuflex Antistatic | | ***1 110 | 24 |
| JChallev Ultrisraric | 14 | | |



| Notes | |
|-------|--|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |



| Notes | |
|-------|--|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

Safety Warnings:



These symbols are found on all Mirka SOPs, as well as the product packaging for Mirka abrasives. Specific requirements for personal protective equipment (PPE) are presented in many different OSHA standards, published in 29 CFR.



Wear appropriate eye and face protection and ensure that the selected form of protection is appropriate to the work being performed and properly fits each worker exposed to the hazard.



Use gloves specifically designed for the hazards and tasks found in the workplace. The nature of the hazard and the operation involved will affect the selection of gloves.



If engineering and work practice controls do not lower employee exposure to workplace noise to acceptable levels, employees must wear appropriate hearing protection.



Selecting the right respirator requires an assessment of all the workplace operations, processes or environments that may create a respiratory hazard.



Read and follow all instructions contained in Technical Data Sheets and User Manuals.

The User is responsible for determining whether the Mirka product is fit for a particular purpose and suitable for the User's application.

The User is also responsible for complying with any applicable safety and health-related regulations and for taking safety and healthrelated precautions when using Mirka products. This includes, but is not limited to: wearing safety glasses, face masks, gloves, and protective clothing, if necessary, following instructions and warning labels, and operating Mirka products safely including at safe operating speeds.

By User's purchase or use of Mirka products, User acknowledges, represents, and warrants that User will: (a) comply with the foregoing, (b) assume all risks in connection with the use of Mirka products, and (c) read and understand the Mirka Warranty Policy.



SUSTAINABLE MIRKA

For You and the Environment

Our business is focused on providing the best tools and solutions to both surface finishing and the precision industry. To be the most sustainable choice, we are digging deep down to the core of our company to figure out what it really means to be sustainable. We have accomplished a great deal already and have many more initiatives we will take on in the future.

For us at Mirka, it has always been clear to not waste financial or material resources—our own or those of our customers. It is equally clear to preserve the planet's resources. Sustainability is a natural extension of this approach. It means taking the economy, the earth, and people into consideration when we make business decisions—now and for future generations.

We work hard to conserve energy and raw materials, reduce waste, increase recycling, and decrease the use of persistent chemicals. We develop healthier, safer, and more efficient products and processes for our customers and employees. For example, our dust-free sanding systems help protect the lungs while giving a cleaner and better surface finish.



Mirka USA

2375 Edison Blvd. Twinsburg, OH 44087

Tel. 800-843-3904 sales.us@mirka.com





mirka.com/en-us

Mirka Canada Inc.

2755 Boulevard Pitfield, Saint-Laurent, QC H4S 1T2

Tel. 855-234-6385 Tel. 514-400-3783 custserv.ca@mirka.com





mirka.com/en-ca

The User is responsible for determining whether the Mirka product is fit for a particular purpose and suitable for the User's application.

The User is also responsible for complying with any applicable safety and health-related regulations and taking any safety and health-related precautions when using Mirka products. This includes, but is not limited to: wearing safety glasses, face masks, gloves, and protective clothing, if necessary; following instructions and warning labels; and operating Mirka products safely including at safe operating speeds.

By User's purchase or use of Mirka products, User acknowledges, represents, and warrants that User will: (a) comply with the foregoing; (b) assume all risks in connection with the use of Mirka products; and (c) read and understand the Mirka Warranty Policy.

Environmental responsibility is a natural part of Mirka's activities and product development. We make sure to take the environment into consideration in all our activities by following the environmental management system ISO 14001 and by offering unique products like our NET sanding discs that allow for a cleaner and therefore healthier work place.



Proudly Supplied By

