FASTENMASTER PRODUCT GUIDE





CENTRALIA, IL 866.755.7636 MOBERLY, MO 800.892.5850 MT. PLEASANT, IA 800.258.5809 SPRING HILL, KS 800.490.4320

Proudly Supplied By



Visit our website at www.midambuilding.com











TimberLOK[®]

Heavy Duty Wood Screw



HeadLOK[®]

Heavy Duty Flathead Fastener



LedgerLOK[®]

Ledger Board Fastener



HEX HEAD STYLE

Features:

- No predrilling
- Faster and easier than 3/8" lag screws • Countersinking head style
- Guaranteed corrosion resistance
- ACQ approved
- IBC/IRC code compliant. ICC-ES ESR-1078

Lengths: 2-1/2", 4", 6", 8", 10"

Packaging Quantities:

12pc clamshell, 50pc box, 250pc bucket, 500pc bucket (2-1/2" only) Single fasteners also available in select sizes



ThruLOK[®]

Carriage & Through-Bolt Replacement



FlatLOK[®]

Structural Wood Screw



Lateral Tension System[®]

Code Compliant Lateral Deck Attachment



Features:

• No predrilling

ICC-ES ESR-1078

• Replaces traditional 1/2" lag screws

Additional lengths available


- Hex washer head style on LedgerLOK • TORX[®] ttap[®] Drive System
- on Flat Head style
- Guaranteed corrosion resistance. ACQ approved
- IBC/IRC code compliant ICC-ES ESR-1078

Lengths: 3-5/8", 5"

Packaging Quantities:

12pc clamshell, 50pc box, 250pc bucket Single fasteners also available in select sizes







FastenMaster PRO Driven



Features:

- No predrillina
- Faster and easier than 1/2" carriage or through-bolts
- No drill bits or wrenches required
- Galvanized coating meets IRC ACQ requirements
- IBC/IRC code compliant ICC-ES ESR-1078
- Lifetime performance guarantee
- Lengths: 6-1/4", 7", 8", 9-1/2"

Packaging Quantities:

24pc box, Single fasteners also available in select sizes

Features:

- No predrilling
- Strip-out resistant #40 TORX[®] ttap[®] drive system
- Guaranteed corrosion resistance ACQ approved
- Approved for single-sided installation
- Code compliant based on testing per ICC-ES AC233

Lengths: 2-7/8", 3-1/2", 4", 4-1/2", 5", 6", 6-3/4"

Packaging Quantities:

50pc box, 250pc bucket, 500pc bucket (2-7/8" only) 200pc bucket (6-3/4" only) Single fasteners also available in select sizes

Features:

- Meets the 2015 and 2018 IRC
- ACQ Approved Coating
- No pre-drilling required
- No interior access needed to install

Packaging Quantities:

- Each kit contains:
- (4) Lateral Tension Brackets,
- (4) Transfer Screws
- (32) Bracket Mounting Screws
- (2) Driver Bits







FrameFAST[™]

Structural Framing System



FrameFAST[™] Installation Heads

- Drive with confidence using FrameFAST[™] application specific installation heads
- Structural connections are completed with precise fastener location, accurate installation angle, and optimized thread engagement
- Secure roof trusses and rafters to wall plates with the Truss-To-Top Plate head
- Fasten along the continuous load path with Stud-to-Plate and Plate-to-Rim installation heads

The FrameFAST System:

- Secure roof trusses and establish a continuous load path 5x faster by eliminating ladders, nail guns and compressors
- Critical connections are made with ease as workers stand safely on the floor.
- Patented delivery system ensures consistent installation every time
- Code-compliant across USA and Canada

FrameFAST Fastener:

- 6" threaded fastener replaces framing clips, straps, and ties
- 200 fasteners per box. Each box includes
- one 6" TP25 TORX Plus drive bit for use with the FrameFAST tool

FrameFAST Tools:

- 3 power options make it easy to choose the FrameFAST tool that's right for your crew
- Fully assembled tools complete with cordless drivers by Milwaukee and DEWalt. Also available with corded driver by Milwaukee.
- Each tool includes one Truss-to-Top Plate installation head



PAMFast[™]

AutoFeed Screw System



PAMFast Tools:

- Fasten subfloor and decking while standing comfortably or convert to a short tool to fasten drywall, roof tiles, and more
- Fully assembled tools come complete with cordless screw guns by DeWalt and Makita or chose a kit to attach to your own screw gun*
- Also available with a corded Milwaukee screw gun



*Not compatible with all screw guns. For a list of compatible screw guns visit fastenmaster.com/PAMFast

NLB Connector[™]

For Non-Load Bearing Wall to Truss Connections



TrussBRACE

Roof Truss Support



Features:

- Increase productivity on the jobsite by installing lateral and diagonal truss bracing in one step
- Up to 40% stronger than common truss bracing techniques*
- No need to remove temporary bracing prior to installing roof sheathing
- Web member bracing increases safety by allowing installer to work from the bottom chord of the truss

Packaging Quantities:

30 per box



The PAMFast System

- 2-in-1 interchangeable length tool is a versatile whole home fastening system.
- Smooth Advancement Technology delivers consistent fastening with no jams.
- PAMMax fastener belt holds up to 40% more fasteners so workers spend more time driving screws and less time reloading.
- PAMFast Fasteners: Featuring PAMDrive 6-lobe recess for improved bit life and fewer cam-outs

Packaging Quantities:

50 screws per strip, 1,000 screws per box, 6 boxes per master carton



Features:

- Provides lateral stability to non-load bearing walls while allowing vertical movement of structural members above
- Installs 8x faster while workers stand safely of the floor
- Code compliant, ACQ Approved

Lengths: 6"


Packaging Quantities:

50pc box with NLB Connector screws pre-assembled with sleeves, 1 NLB setting tool and 1 hex driver bit



Cortex[®] Deck

Hidden Fastening System for Decking, First/Last, Stairs & Perimeter Boards



Cortex[®] FASCIA

Hidden Fastening System for Fascia



Features:

Features:

drive system • Perfect color match

ACQ approved

Length: 2-1/2"

• Engineered for fascia expansion/contraction delivering a long lasting, beautiful finished look

100 sqft (350 screws, 400 plugs, 3 setting tools)

300 sqft (1050 screws, 1200 plugs, 6 setting tools)

- Plugs made from Trex fascia board
- Strip-out resistant #20 TORX[®] ttap[®] drive system

• Collated Cortex plugs are 50% faster

Strip-out resistant #20 TORX[®] ttap[®]

• Guaranteed corrosion resistance

• Also available in loose plugs

Packaging Quantities:

Length: 1-3/4"

Packaging Quantities:

50 LF (100 screws, 105 plugs, 1 counterbore tool and 1 setting tool)



ortex

-

FASCIA

當

TrapEase[®] 3 & TrapEase[®] FASCIA

Color Matched Deck Screw and Fascia Fastener



GuardDog®

Exterior Wood Screw



TigerClaw

Hidden Fastening Systems for Grooved Decking



Cortex[®] Trim

Hidden Fastening System for PVC Trim



Close up of pre-aligned grain plug

Features:

- Installs 50% faster than traditional trim fasteners
- Strip-out resistant #20 TORX[®] ttap[®] drive system

Lengths: 2", 2-3/4"

Packaging Quantities: (Loose Plugs) 50 LF (75 screws, 100 plugs, 1 setting tool)

(Loose and Collated Plugs) 250 LF (375 screws, 400 plugs, 3 setting tools) 750 LF (1125 screws, 1200 plugs, 6 setting tools)







Features:

- Head painted to match board
- Corrosion and fade resistant
- Strip-out resistant #20 TORX® ttap[®] drive system

TrapEase Lengths: 2-1/2", 3"

Packaging Quantities:

75pc box, 350pc bucket, 1,050pc bucket

Fascia Length: 1-3/4"

Fascia Packaging Quantities:

100 LF kit (200 screws, 1 counterbore tool, and 1 driver bit)

Features:

- TORX[®] ttap[®] drive system delivering stick fit, wobble-free installation
- Guaranteed corrosion resistance for the life of the project. ACQ Approved.
- Sharp type 17 point for quick installation
- Nibs under the head delivers a clean finished look on all projects

Lengths: 1-5/8", 2", 2-1/2", 3", 3-1/2"

Packaging Quantities:

75pc box, 350pc box, 1,750pc bucket 1,350pc bucket for 3-1/2" only

Features:

- TC-G fits most 5/4" grooved decking
- TC-120 fits 3/4" hardwood decking with no predrilling
- Ultimate corrosion resistance
- Strong connection between decking and joists
- Requires no special tools

Packaging Quantities:

TC-G, 50 sqft bag with screws, 500 sqft bucket for use with pneumatic gun

TC-120, 50 sqft bag with screws, 500 sqft bucket with screws









Ask us about a FREE Tool First

Time User

Program

