

CH.BMC.D.GSF.4 **Bain Marie**

Drop-in - Counter Line



Product Code:

СН		
BMC		
D		
GSF		

Bain Marie - Counter Line Drop-in Flat Glass Gantry -Stainless Steel Fixings 4 Modules

Optional Extras:

Radius Well


4

Add R to code after the .D (If required, must be nominated at time of order)

Technical Data:

Dimensions: W x D x H: Cutout Dimensions: Total Connected Load: **Electrical Connection:** Water Connection: Waste Connection:

1537 x 825 x 661 1520 x 805 3.9kW 240V 1Ø + N + E 15mm 50mm



Front Elevation

87 Service 153 - Connections End Elevation

15

809 - Gantry

All Culinaire products are supplied with a 12 month parts and labour warranty as standard.

Due to continuous product research and development, the information contained herein is subject to change without notice. Revision: September 2, 2020 - B

www.stoddart.com.au www.stoddart.co.nz






Culinaire Heated

CH.BMC.DR.GSF.4

Product Information:

- This display is designed to be installed into a cut-out in a new or existing bench top which allows for simple installation
- Pans are recessed to minimise water condensation on surrounding bench top
- Double skinned air insulated on all sides to minimise heat to external panels
- Robust construction from 304 grade stainless steel with a No.4 finish
- Adjustable digital temperature controller allows food to be held between +65°C to +90°C (food must be heated above 65°C before being placed in bain marie)
- Wet or dry operation (temperature varies greatly when run dry, should not be left unattended for long periods of time)
- Fitted with 10mm thick toughened glass gantry with overhead Quartz IR heat lamps to provide heat and illumination to the product below
- Individual On/Off switches to operate bain marie and overhead gantry heat lamps
- Overhead heat lamps are fully adjustable via a solid-state voltage controller for accurate temperature selection
- Water inlet at opposite end to drain for ease of cleaning
- Ready for connection to hot water inlet and waste, valves supplied loose for onsite connection to services
- Suits gastronorm pans up to 150mm deep (sold separately).



Plan View