

## CH.BMC.U.GSB.4

# **Bain Marie**

#### **Under Bench - Counter Line**



### **Product Information:**

- This display is designed to be mounted under a custom made bench top of your choice (manufactured & fitted by others)
- Pans are recessed to minimise water condensation on surrounding bench top
- Double skinned air insulated on all sides to minimise heat to external panels
- Robust construction from 304 grade stainless steel with a No.4 finish
- Adjustable digital temperature controller allows food to be held between +65°C to +90°C (food must be heated above 65°C before being placed in bain marie)
- Wet or dry operation (temperature varies greatly when run dry, should not be left unattended for long periods of time)
- Fitted with 10mm thick toughened glass gantry with overhead Quartz IR heat lamps to provide heat and illumination to the product below
- Gantry is detachable and height adjustable for ease of installation.
   To be connected by an electrician
- Individual On/Off switches to operate bain marie and overhead gantry heat lamps
- Overhead heat lamps are fully adjustable via a solid-state voltage controller for accurate temperature selection
- Water inlet at opposite end to drain for ease of cleaning
- Ready for connection to hot water inlet and waste, valves supplied loose for onsite connection to services
- Suits gastronorm pans up to 150mm deep (sold separately).

#### **Product Code:**

CH Culinaire Heated

BMC Bain Marie - Counter

Line

U Under Bench

GSB Flat Glass Gantry - Black

Painted Centre Section -

Adhesive Fix

4 Modules

## Optional Extras: Radius Well

Add R to code after CH.BMC.UR.GSB.4

the .U

(If required, must be nominated at time of

order)

# 

Plan View


### **Technical Data:**


www.stoddart.co.nz

Dimensions: W x D x H: 1523 x 691 x 661
Cutout Dimensions: 1395 x 545
Total Connected Load: 3.9kW

Electrical Connection: 240V 1Ø + N + E

Water Connection: 15mm
Waste Connection: 50mm





All Culinaire products are supplied with a 12 month parts and labour warranty as standard.





