

CH.BMHM.GA.3

Mobile Bain Marie Hot Cupboard

Mobile - A-Frame Gantry - Heat Lamps

Product Information:

- Unit comes complete with CH.BMHM mobile bain marie hot cupboard plus A-frame heated gantry fully fitted and wired. Gantry is welded to bench top
- Adjustable digital temperature controller allows food to be held between +65°C to +90°C (food must be heated above 65°C before being placed in the bain marie or hot cupboard)
- Wet or dry operation to bain marie (temperature varies greatly when run dry, should not be left unattended for long periods of time)
- Hot cupboard features a fan forced heating system which offers energy efficiency, faster heat up times and even heat distribution
- Manual fill and manual empty. Valve operated waste designed to empty over a floor waste
- Gantry constructed from 304 grade stainless steel with a No.4 finish and 6mm toughened glass ends
- Overhead Quartz IR heat lamps provide heat and illumination to the product below
- Indvidual On/Off switches to operate bain marie and overhead gantry heat lamps
- Plug and lead fitted for connection to power when stationary
- Front glass, sliding doors and sneeze guards can be either added as optional extras at the time of order and fitted in factory or ordered at a separate date for easy fitting by customer
- Stainless steel work shelf fitted to fold down brackets can be added as an optional extra at the time of ordering. This item is factory fitted at the time of manufacture.



Product Code:

CH Culinaire Heated вмнм Bain Marie Hot Cupboard - Mobile

GΑ A-Frame Gantry 3 3 Modules


Optional Extras:

Front Glass CA.GAF.3 Sliding Doors CA.GAD.3 Sneeze Guard CA.GAS.3

Work Shelf

Factory Fitted (If required, must be nominated at time of order)

CA.WS.3



1208 O/A

Plan View

Accessories:


Cross Pan Dividers **CA.PXS**

Technical Data:

Dimensions: W x D x H: 1208 x 679 x 1375

Total Connected Load: 3.5kW

Electrical Connection: 15A plug & lead fitted



Front Elevation

End Elevation

All Culinaire products are supplied with a 12 month parts and labour warranty as standard.

Due to continuous product research and development, the information contained herein is subject to change without notice.







