

INCOGNEETO™ Under-Counter Buffet Warmer

B652.U2

660904

PROJECT
ITEM
QUANTITY
DATE

TECHNICAL DATA:

Dimensions (W x D x H):	445 x 445 x 114
Total Weight:	6.8Kg
Wall Clearance:	51mm (152mm below)
Max Ambient Temperature:	50°C
Model:	B652.U2
Total Connected Load:	0.65kW
Volts (Single Phase):	220-240 V
Amps	10A

387mm (15.25*






 1. Chafing Dish
 4. Plywood Substrate

 2. Magneeto™ 2 Trivet
 5. Incogneeto™ Unit

 3. Stone Countertop
 5.





*Induction cooking requires the use of induction-compatible (i.e. magnetic) cookware.



Due to continuous product research and development, the information contained herein is subject to change without notice. Revision: January 14, 2020 1:02 PM

www.stoddart.com.au www.stoddart.co.nz The CookTek[®] Incogneeto[™] is an under-counter buffet warmer designed to mount under natural stone or "engineered" stone countertops – no cutting of the stone is required. The Magneeto[™] trivet (one included with purchase) is placed on the countertop and acts as a temperature sensor, communicator, and locator device which allows the effcient heating of any induction-compatible pan through the stone countertop.*

FEATURES:

- Under counter design with a polycarbonate top and aluminium housing
- Includes Magneeto[™] 2 wireless receiver a trivet-like device used on the countertop to locate the heat zone
- Standard selectable temperature settings: 65°C / 70°C / 75°C / 80°C / 85°C, with lower temperature selections via the keypad
- Accommodates up to a 305mm induction-compatible enamel cast ironware or traditional chafer
- Can be safely used under natural stone, or engineered 'stone' countertops
- Automatic pan detection allows for instant energy transmission to pan; almost no energy consumption when pan is not present
- Lock feature prevents unwanted setting changes
- Large range of accessories available, please contact your Stoddart professional for additional information
- It is important that there is adequate ventilation and clearance in the cabinetry housing the Incogneeto units. Follow the below link for installation guidelines or contact Stoddart on (07) 3440 7600
 www.stoddart.com.au/b652-u2.html

