

# **Technical Data Sheet**

# CR.BB.U.AG.RB.PC.7

# **Back Bar Refrigerators** Refrigerated

Horizontal



### **Product Code:**

- CR = Culinaire Refrigerated
- BB = Back Bar
- U = Under Bench
- AG = Aluminium Framed Glass RB
  - = Remote Control Box
    - = Powder Coated
    - = 7 Door

CR.BB.U.SG.RB.PC.7

CR.BB.U.SGR.RB.PC.7

CR.BB.U.AG.RB.EL.PC.7

CR.BB.U.AG.RBL.PC.7

CR.BB.U.AG.SCL.PC.7

# **Optional Extras:**

PC

7

Frameless Glass Doors

- Add FG to code CR.BB.U.FG.RB.PC.7

#### Stainless Steel Framed Glass Doors, **Continuous Folded Handle**

- Add SG to code

Stainless Steel Framed Glass Doors, **Recessed Handle** 

- Add SGR to code

Equipment Legs

- Add EL to code - Factory fitted

(If Required, must be nominated at time of order)

# Left Hand Services

#### **Remote Control Box**

- Add L to code

# Self Contained

Self Contained Right Hand


- Add SC to code CR.BB.U.AG.SC.PC.7

#### Self Contained Left Hand


- Add SCL to code

# **Technical Data:**

Dimensions: W x D x H:	3750 x 700 x 960
* Remote Refrigeration Load:	3050 watts at -10°C SST
Refrigerant Type:	R507 or 404A
Pipe Connection Inlet	1/2"
Pipe Connection Outlet	1/4"
Total Connected Load:	1.8kW
Electrical Connection:	240V 1Ø + N + E












- **Product Information:**
- Keeps contents at a cool +1°C to +4°C in 32°C ambient temperature
- Air blown from rear to front over a full length cross fin coil to ensure maximum recovery and even temperature in the busiest environments
- High impact, low energy L.E.D. lighting ensures maximum product visibility
- Aluminum framed low energy double glazed, heated and toughened glass doors are self-closing and self-sealing to ensure ease of operation & improved efficiency (as standard)
- Serviceable heater wire in cabinet fascia to prevent condensation •
- Choice of either stainless steel or black internal and external finishes (as standard)
- All doors are left hand hinged with hold open stays, as standard. Contact your local sales rep for other door configurations
- The refrigerator is plinth mounted as standard. 150mm equipment legs available as an optional extra, must be specified at the time of ordering
- All services are at the right hand end of the refrigerator as standard. Can be ordered as left hand by adding"L" to code (refer left hand services)
- Supplied with 4 adjustable shelves per door
- Available in 2-7 doors •
- Supplied with a control box for connection to a remote condenser unit to be supplied separately and connected by a qualified refrigeration contractor and electrician
- Condensate is to be plumbed to waste

Self Contained Refrigerators (contact your Stoddart representative)

- Self contained refrigerators are available in 2-4 doors
- Condensate is to be plumbed to waste



Plan View

Note: Refrigeration load is calculated at the cabinet Due to continuous product research and development, the information contained herein is subject to change without notice

#### Manufactured By:

Tom Stoddart Pty Ltd. ABN 16 009690251 39 Forest Way, Karawatha 4117 Queensland Australia Tel: +61 7 3440 7600 Fax: +61 7 33441000 Web site: www.stoddart.com.au