





Specifications

SEHG062WT W x D x H (mm) 1123 x 925 x 879 Weight 223kg 6 X 2/1GN Capacity 72MJ/Hr / 72MJ/Hr Gas (Natural / Universal 1.4 kW 230V 1∅ + N + E Power

Water Quality Requirements

Cold Water Connection 150-600 kpa **Hardness** 60-100ppm TDS <100mg/L PH Value 7.0 - 8.0 **CI2 Free Chlorine** <0.5mg/L **CI Chloride** <32mg/L **Alkalinity** <20ma/L SiO2 Silica <10mg/L

Legend

Electrical connection A

Gas inlet В

C Softened water inlet

D Water inlet valve

Ε Drain connection

F Cavity vent

G Gas fumes exhaust

н Detergent and rinse aid inlet

Due to continuous product research and development, the information contained herein is subject to change without notice

Revision: 01 - 27/07/2020 - A


www.stoddart.com.au www.stoddart.co.nz


SEHG062WT


Premium Gas Combi Oven 6 x 2/1GN


Product Information:

- Natural or Universal Gas available (advise required gas type when ordering)
- Highly efficient boiler unit that reduces time, water & energy consumption
- Steam Tuner (patented) for optimum results by controlling the Quantity and Quality of steam saturation
- Symbiotic Steam (patented) system combines Boiler Integration with High Efficiency Steam Generator to provide unique, precise and continuous moisture
- Meteo System (patented) for precise humidity control in the cooking chamber
- Large 9" innovative touchscreen interface
- Tablet cleaning for convenience, liquid detergent dispenser installed if preferred
- Easy Service function, enables different dishes to be cooked to various levels at the same time
- Over 120 pre-set cooking programs, with the possibility of 1,000+ additional programs to be stored with up to 9 phases per program
- Recipe Tuner interface makes it possible to modify and personalise various
- Automatic, multi-level, regeneration, sous vide, overnight cooking and smoking programs
- 6 speed Inverter controlled fan
- LED lighting for superior cavity illumination
- Wi-Fi for live service monitoring & assistance of the unit through the Giorik/ Stoddart Cloud
- Supplied with multi-point core temperature probe, integrated hand shower, drain kit and advanced scale reduction filter
- Left hand hinge door option available, this variation is 300mm wider and is made to order
- 24-month warranty









*Drain line must be vented

