



Product Details

- Electrical Connection: 10Amp Plug & Lead supplied
- : 230V, 5.9A, 1400W
- Waste : 20mm with drain hose attached
- Unit Controls : Switch for main power
- : Dixell controller with digital readout
- Refrigeration Info : Type - R507
- : Charge - 1500g
- : Climate Class - 3

REV/VER.	REVISED BY	DATE	REVISION DESCRIPTION	STATUS
F1	N Wooler	20/04/2016	New SW file name structure introduced. 1 generic compressor housing used. All part revisions have changed. Approx: 01/08/2012 Carell controller was replaced with a Dixell controller. Approx: 19/03/2012 Cubigel condensing unit was replaced with Kirby condensing unit. Refer to each part drawing for more details. Unit was previously known as SP-WCFS25SS.	For Manufacture
E	M Sheehan	20/08/2010	Door system changed to nylon roller guides & channel.	For Manufacture
D	C Booth	03/10/2006	End profile angle changed from 72° to 70°.	For Manufacture
C	C Booth	25/03/2006	Part -p005 dimension change.	For Manufacture
B	C Booth	11/03/2005	Some parts re-designed. Refer to each part drawing for more details.	For Manufacture
A	C Booth	22/11/2004	Original design.	For Manufacture



www.stoddart.com.au

NAME	SIGNATURE	DATE	UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS
C Booth		22/11/2004	
Weight: Surface Area:			MATERIAL: THICKNESS: FINISH:
DWG No: W-CFSS25-d01 F1			Dwg. Issue: 3

DO NOT SCALE DRAWING This drawing remains the property of Tom Stoddart Pty Ltd ABN 16 009 690 251 & cannot be reproduced without prior permission. A3 Sheet 1 of 18
File Location: G:\03_Engineering\Woodson\W-CFSS2x Cold Food Display; Self Serve\01_Solidworks\W-CFSS25 5 Mod\