URINALS

Sani Grate - Walk-On Urinal

Model: SPPL.UR.G.xxxx.yy

SPPL = Stoddart Plumbing Product

UR = Urinal G = Grated

xxxx = Nominated Length
yy = T - top water entry
= R - rear water entry
= R - right waste

= L - left waste eg.: for specification and ordering quote


Code: SPPL.UR.G.1800.RR


*L & U shaped configurations available.




Features and Benefits:

- Fully supported on legs for easy installation (no need to fill void under trough with slurry)
- 610mm depth sides for superior hygiene
- Concealed vandal resistant sparge to ensure proper wash with each flush
- The unit can be set into floor (recessed so the top grate is flush with floor), or set on floor (can be fitted with optional stainless steel front kick panel)
- Stainless steel grate is high strength, slip resistant, and hinged for cleaning access
- Internal corners have large radius for easy cleaning and effective drainage
- Fall to waste of 1:80 ensures proper drainage
- Compressed fibre-cement backing provides 'anti-drum' noise suppression
- Optional freestanding finished end panels available where there are no walls
- Top edge can have either returned finished edge or tile edge
- Custom lengths available





Front View



End View

Specifications:

Construction: Fully welded 1.2mm thick 304 stainless steel

construction, no.4 satin finish.

Water Connection: Top entries in ø25 and ø38 dia. Rear entry in

25mm pressure pipe. Custom inlet positions available. Designed for WELS approved flush

devices.

Waste Connection: 50mm to 100mm dropper outlets available

Custom waste positions available.

Sold Separately

Flushing Device Options:





FD.CI.PC

FD.EUFS.MIC



Revision: A -14/05/2021







www.stoddart.com.au www.stoddart.co.nz

the information contained herein is subject to change without notice.