# **URINALS**

# Maxi Step Urinal

## Model: SPPL.UR.MS.xxxx.yy

SPPL = Stoddart Plumbing Product

UR = Urinal
MS = Maxi Step
xxxx = Nominated Length
yy = T = top entry water supply
= R = rear entry water supply
= L = left end waste

= R = right end waste eg.: for specification and ordering quote

Code: SPPL.UR.MS.1500.TL

#### \*L & U shaped configurations available.



## Specifications:

Construction: Fully welded 1.2mm thick 304 stainless steel

construction, no.4 satin finish.

Water Connection: Top entries in ø25 and ø38 dia. Rear entry in 25mm pressure pipe. Custom inlet positions

25mm pressure pipe. Custom inlet positions available. Designed for WELS approved flush


devices.


Waste Connection: 50mm to 100mm dropper outlets available


Custom waste positions available.

#### Features and Benefits:

- Fully supported on legs for easy installation (no need to fill void under trough with slurry)
- 600mm depth sides for superior hygiene
- Concealed vandal resistant sparge to ensure proper wash with each flush
- The unit can be set into floor (recessed so the top grate is flush with floor), or set on floor (can be fitted with optional stainless steel front kick panel)
- Stainless steel grate is high strength, slip resistant, and hinged for cleaning access
- Internal corners have large radius for easy cleaning and effective drainage
- Fall to waste of 1:80 ensures proper drainage
- Compressed fibre-cement backing provides 'anti-drum' noise suppression
- Optional freestanding finished end panels available where there are no walls
- Top edge can have either returned finished edge or tile edge
- · Custom lengths available







Front View

End View

## Sold Separately

Flushing Device Options:





FD.CI.PC

FD.EUFS.MIC









Due to continuous product research and development, the information contained herein is subject to change without notice.



