TOILETS

Close Coupled Toilet Suite - Access Compliant

Model: SPPL.TP.CC2.D

SPPL = Stoddart Plumbing Product

TP = Toilet Pan
CC2 = Close Coupled
D = Disabled Access

eg.: for specification and ordering quote

Code: SPPL.TP.CC2.D



Specifications:

Construction: 2mm thick, 304 stainless steel no.4 satin finish
Flushing: WELS approved 4.5L full flush/3L half flush

Water Connection: 15mm BSP connection
Waste Connection: P-S Q bend adaptor supplied

Unit Fixing: The unit has holes for fixing to floor and wall.

A Z-clip is supplied to secure the front of the base to the floor when unit is pushed to wall

Model No.	L x D x H (mm)		
TP.CC2.D	367 x 800 x 1067		
	Inlet Height	Outlet Height	Waste Set-Out
	420 ± 3	251 ± 3	~ 195 Standard Bend (not supplied)

ASSDA

Due to continuous product research and development, the information contained herein is subject to change without notice.


Revision: B - 19/04/2021


WWW.stoddart.com.au

www.stoddart.co.nz

Features and Benefits:


- Smooth hydraulically formed radius to outer and inner edges provide safety and user comfort
- Formed stainless seat provides superior comfort, hygiene and strength
- Optional Thermoplastic seat can be added (refer below)
- Secure flushing device access cover fastened with Torx security screws
- Engineered flushing rim prevents hiding of contraband while allowing free flow of flush water
- Stainless steel construction provides superior strength, superior hygiene and long service life
- Optional 316 grade stainless steel suitable for highly corrosive and coastal environments
- Powder coated to colour of choice optional
- Access compliant, back rest included





Plan View





Front View

End View

321

Sold Separately

Toilet Seat Options:















