### **TROUGHS**

# Knee Operated Wash Trough

### Model: SPPL.WT.KO.x.yyyy

SPPL = Stoddart Plumbing Product

WT = Wash Trough
KO = Knee Operated
x = L = Left Waste
= R = Right Waste
yyyy = Nominated Length


eg.: for specification and ordering quote

Code: SPPL.WT.KO.R.1200.


# Features and Benefits:

- Easy Push front panel for hygienic hands free washing
- Timed flow valve with automatic shut off
- Radius corners for easy cleaning, hygiene and safety
- 50mm waste outlet can be positioned at either left or right hand end
- Each Easy Push panel is backed with 18mm ply and double skinned to provide a robust and durable application
- Easy mount bracket has adjustable fixing positions
- Freestanding frame option available





Dian View



Front View

#### **Specifications:**

Construction: Fully welded seamless 304 grade 1.2 mm thick

stainless steel construction, no.4 satin finish. 150mm x 20mm splashback for cleanliness, safety and secure mounting to wall.

Water Connection: 15mm (1/2") BSP

Waste Connection: 50mm PVC waste supplied


Activation Valve: Timed flow valve is fitted to each knee operated

push panel

Unit Fixing: The unit is supplied with stainless steel wall

mounting brackets, includes  ${\sf Z}$  clips

Model No.	L x D x H (mm)	No. of Spouts
SPPL.WT.KO.x.1200	1200 x 445 x 375	2
SPPL.WT.KO.x.1800	1800 x 445 x 375	3
SPPL.WT.KO.x.2400	2400 x 445 x 375	4
Custom depths available		







Due to continuous product research and development, the information contained herein is subject to change without notice.

Revision: A - 18/06/2021

www.stoddart.com.au www.stoddart.co.nz

