Wash Basin Knee Operated - Type 2

Model: SPPL.WB.KO2.xxx

SPPL = Stoddart Plumbing Product

WB = Wash Basin

KO2 = Knee operated, with lower plumbing shroud


xxx = 300 = 300mm splashback eg.: for specification and ordering quote

Code: SPPL.WB.KO2.300

Features and Benefits:


- Hygienic hands free use with knee operated front panel
- Timed flow valve provides effective hand washing and saves water
- Security bubbler has WELS 6 star rating and is preferred by councils for use in public areas due to its extra vandal resistance
- A 300mm splashback can be ordered with the unit for easy installation and to comply with plumbing requirements of most authorities and removes the need for tiling
- Easy mount single piece stainless steel bracket has multiple fixing holes for a quick installation by plumber
- Stainless steel shroud fully encloses plumbing for additional hygiene and security while preventing unauthorised tampering with plumbing fittings
- Complies with AS 1428.1-2001 for disabled access








Plan View





Front View

End View

Specifications:

Construction: 304 grade stainless steel construction, no.4

finish. Fully pre-plumbed. Knee operated timed

flow valve.

Water Connection: 15mm (1/2" BSP). Additional water strainer/filter

to protect valves from water-borne dirt and

scale is fitted as standard.

Waste Connection: 40mm PVC waste supplied (Trap by others)

Unit Fixing: Unit is supplied with wall mounting bracket with

10mm fixing holes.

Fixing Height: The unit can be mounted at 800 - 830mm

above finished floor level for disabled use.

Model No.	L x D x H (mm)
SPPL.WB.KO2.xxx	500 x 420 x 575









Due to continuous product research and development, the information contained herein is subject to change without notice.

Revision: D -11/06/2021



