



FG7817PT


.700



Product Information:

- Class leading, European style, professional quality and reliability since 1963
- 700 series, electric 2 x 17 litre, double pan fryer (118.8 MJ/h)
- Open pan design with external burners
- Electronic ignition, high efficiency, stainless steel burners complete with flame failure device, pilot burner and Hi-limit temperature protection with manual reset
- Temperature regulation via thermostat (100°C 195°C)
- · Thermostat bulbs protected against accidental impact
- Cold zone on the bottom of the tank to collect residues and prevent tainting of oil
- 2x 310x345mm single tanks with oil drainage via ball valve into integrated oil capture drawer
- Indicator lights to monitor the correct operation of the appliance
- Robust 304 grade stainless steel construction with rounded corners for improved cleaning
- Pressed top work surface with raised edges to protect from overflow
- Enclosed base with front access doors
- Height adjustable stainless steel feet for a 900mm working height
- Supplied with removable mesh basket support, 2x 300x310x120mm baskets and lids
- · 24-month warranty

General Drawing:



SPGI.2012895 x 4 required for double pan

Due to continuous product research and development, the information contained herein is subject to change without notice. Revision: 01 - 05/01/2022 - A

www.stoddart.com.au www.stoddart.co.nz







Specifications:

Model	FG7817PT		
W x D x H (mm)	800 x 720 x 1054		
Weight	121kg		
Oil Capacity	2 x 17L		
Packed Dimensions (mm)	845 x 825 x 1200		
Packed Weight (mm)	131kg		
Electrical Connection		1Ø + N + E 240VAC / 50Hz / 0.2kW 10A plug & lead fitted	
	Natural	Universal LPG	

 Gas Connection
 1/2" BSP
 1/2" BSP

 Minimum Normal Test Gas Pressure
 1.3 kPa
 2.75 kPa

 Maximum Normal Test Gas Pressure
 3.5 kPa
 3.5 kPa

 Nominal Test Point Pressure
 1.0 kPa
 2.65 kPa

 Total Nominal Gas Consumption
 118.8 MJ/h
 118.8 MJ/h

Note: It is the responsibility of the installing gas plumber to ensure correct supply and connection sustaining appropriate pressure, when all installed gas appliances are operating at maximum.

Legend:

A Gas Connection

B Electrical Connection