## **TOILETS**

## Pan - TP3 Access Compliant

## Model: SPPL.TP.3.D

SPPL = Stoddart Plumbing Product

TP = Toilet Pan 3 = Type 3

D = Disabled Access (H460mm, L800mm)

eg.: for specification and ordering quote

Code: SPPL.TP.3.D



## Specifications:

Construction: Toilet bowl and Trap – 304 stainless steel.

Seat, Body and shroud – 2mm 304 stainless steel no.4 satin finish (Options; Super Heavy

Duty: 3mm 304 outer body).

Flushing: WELS approved 4.5L full flush/3L half flush.

Flushing device must be able to deliver 1.4 litres per second to the toilet pan (as per

4S1172).

Water Connection: Inlet Key-Seal supplied for 40mm flush pipe.

Waste Connection: P trap standard, with rubber coupling included

to suit 100mm PVC.

Optional P-S adaptors can be ordered separately not supplied as standard.

Unit Fixing: The unit is designed to be fixed to the rear wall with 4 bolts. A Z-clip is supplied to secure

the front of the base to the floor.

Model No.	L x D x H (mm)		
SPPL.TP.3.D	367 x 800 x 460		
	Inlet Height	Outlet Height	Waste Set-Out
	420 ± 3	251 ± 3	195 ± 5 Standard Pan Bend (not supplied)

# ASSDA


Due to continuous product research and development, the information contained herein is subject to change without notice.


Revision: B3 - 16/06/23


## www.stoddart.com.au www.stoddart.co.nz


#### Features and Benefits:

- 2mm heavy duty (1000kg) load carrying capacity
- Plumbing and fixing points are concealed for security and vandal resistance
- Access to plumbing is via side access panels
- Anti-contraband flushing rim
- Seat has smooth hydraulically formed radius to both outer and inner edges for safety and comfort and has a self draining seat surface for improved hygiene
- · All external corners are rounded with a smooth radius for safety
- These toilets can be flushed with either a flush valve or in wall cistern (ordered separately)
- Powder coated to colour of choice optional
- Optional 316 grade stainless steel suitable for highly corrosive and coastal environments
- Access compliant









Front View

End View

## Sold Separately

## Flushing Device Options:



.00.







FD.CI.IW.MDF



CMPL.0915



FD.CI.IW.PRF FD.CI.IW.PF



CMPL.0814









CMPL.1005

