TOILETS

Toilet Pan - TP4 Standard

Model: SPPL.TP.4.S

SPPL = Stoddart Plumbing Product

TP = Toilet Pan 4 = Type 4

= S = Standard (H400mm, L650mm) S

eg.: for specification and ordering quote

Code: SPPL.TP.4.S



Specifications:

Construction: Toilet bowl and Trap – 304 stainless steel.

Seat, Body and shroud – 2mm 304 stainless steel no.4 satin finish (Options; Super Heavy

Duty: 3mm 304 outer body).

Flushing: WELS approved 4.5L full flush/3L half flush.

Flushing device must be able to deliver 1.4 litres per second to the toilet pan (as per

AS1172).

Inlet Key-Seal supplied for 40mm flush pipe. Water Connection:

P trap standard, with rubber coupling included Waste Connection:

to suit 100mm PVC.

Optional P-S adaptors can be ordered separately not supplied as standard.

Unit Fixing: The unit is designed to be fixed to the rear wall with 4 bolts. A Z-clip is supplied to secure

the front of the base to the floor.

Model No.	L x D x H (mm)		
SPPL.TP.4.S	367 x 650 x 460		
	Inlet Height	Outlet Height	Waste Set-Out
	360 ± 3	191 ± 3	~ 175 Plastec Universal Pan Bend


Due to continuous product research and development, the information contained herein is subject to change without notice.

Revision: A3 - 16/06/23


www.stoddart.com.au www.stoddart.co.nz

Features and Benefits:

- 2mm heavy duty (1000kg) load carrying capacity
- Hydraulically formed seat with smooth radius to inner and outer edges for safety and comfort
- Self draining surface for improved hygiene
- Concealed plumbing and fixing points for security and vandal resistance
- Top secure access panel
- Anti-contraband flushing rim
- Powder coated to colour of choice optional
- These toilets can be flushed with either a flush valve or cistern (ordered separately)
- Optional 316 grade stainless steel suitable for highly corrosive and coastal environments







Front View End View

Sold Separately

Flushing Device Options:



FD.CI.IW.PRF.CB

Toilet Seat Options:



FD.CI.IW.MDF FD.CI.IW.EFV

FD.CI.IW.PRF



CMPL.0814







