## **TOILETS**

# Wall Hung Toilet Pan - Ambulant

### Model: SPPL.TP.WH.4.A

SPPL = Stoddart Plumbing Product

TP = Toilet Pan WH.4 = Wall Hung Type 4 A = Ambulant


eg.: for specification and ordering quote

Code: SPPL.TP.WH.4.A

#### Features and Benefits:

- Hydraulically formed seat with smooth radius to inner and outer edges for safety and comfort.
- Seat area is sloped to drain into the bowl for improved hygiene
- Heavy duty (500kg) load carrying capacity (depending on wall structure)
- Concealed plumbing and fixing points for security and vandal resistance
- Engineered flushing rim prevents hiding of contraband while allowing free flow of flush water
- Powder coated to colour of choice optional
- Optional 316 grade stainless steel suitable for highly corrosive and coastal environments
- These toilets can be flushed with either a flush valve or in-wall cistern (ordered separately)
- Meets Ambulant requirements when mounted at correct height








Plan View

Rear View





Front View

End View

# Specifications:

Construction: Toilet bowl and Trap – 304 stainless steel.

Seat, Body and shroud  $-2\text{mm}\ 304$  stainless

steel no.4 satin finish

Flushing: WELS approved 4.5L full flush/3L half flush.

Flushing device must be able to deliver 1.4 litres per second to the toilet pan (as per

AS1172)

Water Connection: Inlet Key-Seal supplied for 40mm flush pipe.

Waste Connection: P trap standard, with rubber coupling included

to suit 100mm PVC.

Unit Fixing: The unit is designed to be fixed to the rear

wall with 4 x Ø16 stainless steel bolts.

Sold Separately

Flushing Device Options:





FD.CI.IW.EFV





CMPL.1005

.00.

FD.CI.IW.MDF

33.

FD.CI.IW.PRF

FD.CI.IW.PRF.CB

CMPL.0814







Due to continuous product research and development, the information contained herein is subject to change without notice.

Revision: A3 - 16/06/23





